

FP SERIES 1K/1.5K/2K

The blackout beauty



1k Backpanel



1.5k / 2k Backpanel

The line-interactive FP-Series UPS with a compact size can provide stable power protection against surges and spikes. It is ideal for PC users or small business companies, as well as for small telecom applications.

Its embedded microprocessor controller guarantees high reliability. It can automatically restart while AC power is recovering. With Simulated sine wave, off-mode charging, and cold start function, it will be a good choice.

Model	FP 1000	FP 1500	FP 2000
Capacity	1000 VA / 600W	1500 VA / 900W	2000 VA / 1200W
Input/Voltage	110/120 VAC or 220/230/240 VAC		
Input/Voltage Range	81-145 VAC / 162-290 VAC		
Input/Frequency	60/50 Hz (auto sensing)		
Output/Voltage	±10%		
Output/Frequency Range	60 Hz or 50 Hz ±1 Hz		
Output/Transfer Time(Typical)	Typical 2-6 ms		
Output/Waveform(Batt. Mode)	Simulated Sine Wave		
Battery/Battery Type & Number	12V / 7 Ah x 2	12V / 9 Ah x 2	12V / 9 Ah x 2
Battery/Typical Recharge Time	4-6 hours recover to 90% capacity		
Physical/Dimension, DxWxH (mm)	320 x 130 x 182		
Physical/Net Weight (kgs)	8.2	10.4	11