



## Designer Bluetooth Desktop

Version Information Product Name	Microsoft® Designer Bluetooth Desktop	
Keyboard Version	Microsoft Designer Bluetooth Keyboard	
Mouse Version	Microsoft Designer Bluetooth Mouse	
Product Dimensions	Microsoft Designer Bruetooth Mouse	
	450: 4 (000 19: 4 )	
Keyboard Length	15.3 inches (389 millimeters)	
Keyboard Width	4.41 inches (112 millimeters)	
Keyboard Depth/Height	0.78 inches (19.8 millimeters)	
Keyboard Weight	14.8 ounces (420 grams) includes 2 AAA alkaline batteries; battery weight may vary	
Mouse Length	4.22 inches (107 millimeters)	
Mouse Width	4.2.2 inches (60.1 millimeters) 2.36 inches (60.1 millimeters)	
Mouse Depth/Height	1.02 inches (25.8 millimeters)	
Mouse Weight	2.82 ounces (80 grams) includes 2 AAA alkaline battery; typical battery weight may vary	
ompatibility and Localization		
Interface	Bluetooth® Low Energy Compatible 4.0	
Operating Systems <sup>1</sup>	Microsoft Windows 8.1, Windows 8, Windows RT 8.1, and Windows RT 8	
Operating dystems	• Mac OS10.10+ • Android 4.4+	
	<sup>1</sup> Device must support Bluetooth 4.0 or higher. Microsoft.com/hardware/compatibility.	
T   0   5   1		
Top-line System Requirements	Requires a PC that meets the requirements for and has installed one of these operating systems:  For a Windows-based PC:  Windows 8.1, Windows RT 8.1, or Windows RT 8	
	For other operating systems:	
	• Mac OS10.10+	
	Android 4.4+	
Compatibility Logos	Compatible with Microsoft Windows 8	
,	Bluetooth Smart logo	
	Android logo	
Koyboard Localization	- Available language sets will vary by product and sales channel.	
Keyboard Localization		
	104 key configuration: Arabic, Chinese (Simplified), Chinese (Traditional), Czech, English (Canada), English (North America), International English	
	(Euro), International English (ROW), Greek, Hebrew, Russian, and Thai	
	105 key configuration: All Nordic, English (UK), French (Belgium/Azerty), French (Canada), French (France), German (Germany), German	
	(Switzerland/Luxemburg), Hungarian, Iberian, Italian, Spanish (Euro), Spanish (Latam), and Turkish	
	106 key configuration: Korean	
	107 key configuration: Brazilian (Portuguese)	
	109 key configuration: Japanese	
Wireless Technology	N 5 DESCRIPTION (D) 4 d 4 5 3	
Wireless Platform	Nordic nRF51822 (Bluetooth Low Energy)	
Wireless Frequency	2.4 GHz frequency range	
Wireless Range	32 feet (10 meters) in open air, up to 16 feet (5 meters) in office environment typical	
Bluetooth Profile Support	HID Over Gatt Profile (HOGP)	
Fracking Technology	The oral can't tome (troof)	
Mouse Tracking System	Microsoft-proprietary BlueTrack™ Technology	
Imaging Rate	Dynamically adaptable to 2400 frames per second	
X-Y Resolution	1000 points per inch (39.4 points per millimeter)	
Tracking Speed	Up to 10 inches (254 millimeters) per second	
Power Requirements		
Battery Type and Quantity	Keyboard: 2 AAA alkaline batteries (included)	
Dattery Type and Quantity	Mouse: 2 AAA alkaline batteries (included)	
Battery Life	Keyboard: Up to 12 months typical	
	Mouse: Up to 6 months typical	
Product Feature Performance		
QWERTY Key Life	5,000,000 actuations per key	
Function Key Features	Windows 8 Charms keys and Windows Start key	
Function Key Life	500,000 actuations per key	
Media Key Features	Mute, Volume -, Volume +, Pause/Play, Page -, and Page +	
Media Key Life	500,000 actuations per key	
Typing Speed	200 characters per minute	
Mouse Button Features	3 buttons	
	3,000,000 actuations at no more than 2.5 actuations per second	
Right & Left Button Life		
Mouse Scrolling Features	Standard vertical scrolling	
Mouse Scrolling Features Wheel Vertical Scrolling Life	Standard vertical scrolling  • 100,000 revolutions (away from user)  • 300,000 revolutions (towards user)	
Mouse Scrolling Features Wheel Vertical Scrolling Life Storage Temperature & Humidity	Standard vertical scrolling  • 100,000 revolutions (away from user)  • 300,000 revolutions (towards user)  -40 °F (-40 °C) to 140 °F (60 °C) at < 5% to 65% relative humidity (non-condensing)	
Mouse Scrolling Features Wheel Vertical Scrolling Life Storage Temperature & Humidity Operating Temperature & Humidity	Standard vertical scrolling  • 100,000 revolutions (away from user)  • 300,000 revolutions (towards user)	
Mouse Scrolling Features Wheel Vertical Scrolling Life Storage Temperature & Humidity Operating Temperature & Humidity Certification Information	Standard vertical scrolling  • 100,000 revolutions (away from user)  • 300,000 revolutions (towards user)  -40 °F (-40 °C) to 140 °F (60 °C) at < 5% to 65% relative humidity (non-condensing)  32 °F (0 °C) to 104 °F (40 °C) at <5% to 80% relative humidity (non-condensing)	
Mouse Scrolling Features Wheel Vertical Scrolling Life Storage Temperature & Humidity Operating Temperature & Humidity Pertification Information Country of Manufacture	Standard vertical scrolling  • 100,000 revolutions (away from user)  • 300,000 revolutions (towards user)  -40 °F (-40 °C) to 140 °F (60 °C) at < 5% to 65% relative humidity (non-condensing)  32 °F (0 °C) to 104 °F (40 °C) at <5% to 80% relative humidity (non-condensing)  People's Republic of China (PRC)	
Mouse Scrolling Features Wheel Vertical Scrolling Life Storage Temperature & Humidity Operating Temperature & Humidity Pertification Information Country of Manufacture ISO 9001 Qualified Manufacture	Standard vertical scrolling  • 100,000 revolutions (away from user)  • 300,000 revolutions (towards user)  -40 °F (-40 °C) to 140 °F (60 °C) at < 5% to 65% relative humidity (non-condensing)  32 °F (0 °C) to 104 °F (40 °C) at <5% to 80% relative humidity (non-condensing)  People's Republic of China (PRC)  Yes	
Mouse Scrolling Features Wheel Vertical Scrolling Life Storage Temperature & Humidity Operating Temperature & Humidity Pertification Information Country of Manufacture	Standard vertical scrolling  • 100,000 revolutions (away from user)  • 300,000 revolutions (towards user)  -40 °F (-40 °C) to 140 °F (60 °C) at < 5% to 65% relative humidity (non-condensing)  32 °F (0 °C) to 104 °F (40 °C) at <5% to 80% relative humidity (non-condensing)  People's Republic of China (PRC)	
Mouse Scrolling Features Wheel Vertical Scrolling Life Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Country of Manufacture ISO 9001 Qualified Manufacturer	Standard vertical scrolling  • 100,000 revolutions (away from user)  • 300,000 revolutions (towards user)  • 300,000 revolutions (towards user)  • 40 °F (-40 °C) to 140 °F (60 °C) at < 5% to 65% relative humidity (non-condensing)  32 °F (0 °C) to 104 °F (40 °C) at < 5% to 80% relative humidity (non-condensing)  People's Republic of China (PRC)  Yes  Yes  This device complies with all applicable worldwide regulations and restrictions including, but not limited to: EU directive 2002/95/EC on the Restriction	
Mouse Scrolling Features Wheel Vertical Scrolling Life Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Country of Manufacture ISO 9001 Qualified Manufacturer ISO 14001 Qualified Manufacturer	Standard vertical scrolling  • 100,000 revolutions (away from user)  • 300,000 revolutions (towards user)  -40 °F (-40 °C) to 140 °F (60 °C) at < 5% to 65% relative humidity (non-condensing)  32 °F (0 °C) to 104 °F (40 °C) at < 5% to 80% relative humidity (non-condensing)  People's Republic of China (PRC)  Yes  Yes  This device complies with all applicable worldwide regulations and restrictions including, but not limited to: EU directive 2002/95/EC on the Restriction the Use of Certain Hazardous Substances in Electrical and Electronic Equipment and EU Registration Evaluation and Authorization of Chemicals	
Mouse Scrolling Features Wheel Vertical Scrolling Life Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Country of Manufacture ISO 9001 Qualified Manufacturer ISO 14001 Qualified Manufacturer Restriction on Hazardous Substances	Standard vertical scrolling  • 100,000 revolutions (away from user)  • 300,000 revolutions (towards user)  -40 °F (-40 °C) to 140 °F (60 °C) at < 5% to 65% relative humidity (non-condensing)  32 °F (0 °C) to 104 °F (40 °C) at <5% to 80% relative humidity (non-condensing)  People's Republic of China (PRC)  Yes  Yes  This device complies with all applicable worldwide regulations and restrictions including, but not limited to: EU directive 2002/95/EC on the Restriction the Use of Certain Hazardous Substances in Electrical and Electronic Equipment and EU Registration Evaluation and Authorization of Chemicals (REACH) regulation regarding Substances of Very High Concern.	
Mouse Scrolling Features Wheel Vertical Scrolling Life Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Country of Manufacture ISO 9001 Qualified Manufacturer ISO 14001 Qualified Manufacturer	Standard vertical scrolling  • 100,000 revolutions (away from user)  • 300,000 revolutions (towards user)  • 40 °F (-40 °C) to 140 °F (60 °C) at < 5% to 65% relative humidity (non-condensing)  32 °F (0 °C) to 104 °F (40 °C) at < 5% to 80% relative humidity (non-condensing)  People's Republic of China (PRC)  Yes  Yes  This device complies with all applicable worldwide regulations and restrictions including, but not limited to: EU directive 2002/95/EC on the Restriction the Use of Certain Hazardous Substances in Electrical and Electronic Equipment and EU Registration Evaluation and Authorization of Chemicals (REACH) regulation regarding Substances of Very High Concern.  This Class B digital apparatus complies with Part 15 of the U.S. Federal Communications Commission (FCC) rules, Canadian ICES-003, and RSS-21	
Mouse Scrolling Features Wheel Vertical Scrolling Life Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Country of Manufacture ISO 9001 Qualified Manufacturer ISO 14001 Qualified Manufacturer Restriction on Hazardous Substances	Standard vertical scrolling  • 100,000 revolutions (away from user)  • 300,000 revolutions (towards user)  -40 °F (-40 °C) to 140 °F (60 °C) at < 5% to 65% relative humidity (non-condensing)  32 °F (0 °C) to 104 °F (40 °C) at <5% to 80% relative humidity (non-condensing)  People's Republic of China (PRC)  Yes  Yes  This device complies with all applicable worldwide regulations and restrictions including, but not limited to: EU directive 2002/95/EC on the Restriction the Use of Certain Hazardous Substances in Electrical and Electronic Equipment and EU Registration Evaluation and Authorization of Chemicals (REACH) regulation regarding Substances of Very High Concern.  This Class B digital apparatus complies with Part 15 of the U.S. Federal Communications Commission (FCC) rules, Canadian ICES-003, and RSS-21 Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference	
Mouse Scrolling Features Wheel Vertical Scrolling Life Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Country of Manufacture ISO 9001 Qualified Manufacturer ISO 14001 Qualified Manufacturer Restriction on Hazardous Substances	Standard vertical scrolling  • 100,000 revolutions (away from user)  • 300,000 revolutions (towards user)  • 40 °F (-40 °C) to 140 °F (60 °C) at < 5% to 65% relative humidity (non-condensing)  32 °F (0 °C) to 104 °F (40 °C) at < 5% to 80% relative humidity (non-condensing)  People's Republic of China (PRC)  Yes  Yes  This device complies with all applicable worldwide regulations and restrictions including, but not limited to: EU directive 2002/95/EC on the Restriction the Use of Certain Hazardous Substances in Electrical and Electronic Equipment and EU Registration Evaluation and Authorization of Chemicals (REACH) regulation regarding Substances of Very High Concern.  This Class B digital apparatus complies with Part 15 of the U.S. Federal Communications Commission (FCC) rules, Canadian ICES-003, and RSS-21	
Mouse Scrolling Features Wheel Vertical Scrolling Life Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Country of Manufacture ISO 9001 Qualified Manufacturer ISO 14001 Qualified Manufacturer Restriction on Hazardous Substances	Standard vertical scrolling  • 100,000 revolutions (away from user)  • 300,000 revolutions (towards user)  • 40 °F (-40 °C) to 140 °F (60 °C) at < 5% to 65% relative humidity (non-condensing)  32 °F (0 °C) to 104 °F (40 °C) at <5% to 80% relative humidity (non-condensing)  People's Republic of China (PRC)  Yes  Yes  This device complies with all applicable worldwide regulations and restrictions including, but not limited to: EU directive 2002/95/EC on the Restriction the Use of Certain Hazardous Substances in Electrical and Electronic Equipment and EU Registration Evaluation and Authorization of Chemicals (REACH) regulation regarding Substances of Very High Concern.  This Class B digital apparatus complies with Part 15 of the U.S. Federal Communications Commission (FCC) rules, Canadian ICES-003, and RSS-21 Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Tested to comply with FCC (U.S. Federal Communications Commission)	
Mouse Scrolling Features Wheel Vertical Scrolling Life Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Country of Manufacture ISO 9001 Qualified Manufacturer ISO 14001 Qualified Manufacturer Restriction on Hazardous Substances	Standard vertical scrolling  • 100,000 revolutions (away from user)  • 300,000 revolutions (towards user)  -40 °F (-40 °C) to 140 °F (60 °C) at < 5% to 65% relative humidity (non-condensing)  32 °F (0 °C) to 104 °F (40 °C) at <5% to 80% relative humidity (non-condensing)  People's Republic of China (PRC)  Yes  This device complies with all applicable worldwide regulations and restrictions including, but not limited to: EU directive 2002/95/EC on the Restriction the Use of Certain Hazardous Substances in Electrical and Electronic Equipment and EU Registration Evaluation and Authorization of Chemicals (REACH) regulation regarding Substances of Very High Concern.  This Class B digital apparatus complies with Part 15 of the U.S. Federal Communications Commission (FCC) rules, Canadian ICES-003, and RSS-21 Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Tested to comply with FCC (U.S. Federal Communications Commission) Standards. For home or office use. The term "IC:" before the certification/registration number only signifies that the Industry Canada technical	
Mouse Scrolling Features Wheel Vertical Scrolling Life Storage Temperature & Humidity Operating Temperature & Humidity Pertification Information Country of Manufacture ISO 9001 Qualified Manufacturer ISO 14001 Qualified Manufacturer Restriction on Hazardous Substances	Standard vertical scrolling  • 100,000 revolutions (away from user)  • 300,000 revolutions (towards user)  -40 °F (-40 °C) to 140 °F (60 °C) at < 5% to 65% relative humidity (non-condensing)  32 °F (0 °C) to 104 °F (40 °C) at <5% to 80% relative humidity (non-condensing)  People's Republic of China (PRC)  Yes  Yes  This device complies with all applicable worldwide regulations and restrictions including, but not limited to: EU directive 2002/95/EC on the Restriction the Use of Certain Hazardous Substances in Electrical and Electronic Equipment and EU Registration Evaluation and Authorization of Chemicals (REACH) regulation regarding Substances of Very High Concern.  This Class B digital apparatus complies with Part 15 of the U.S. Federal Communications Commission (FCC) rules, Canadian ICES-003, and RSS-21 Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Tested to comply with FCC (U.S. Federal Communications Commission) Standards. For home or office use. The term "IC:" before the certification/registration number only signifies that the Industry Canada technical specifications were met. Model numbers: 1678 Designer Bluetooth Keyboard and 1679, Designer Bluetooth Mouse. FCC ID: C3K1678 and C3K1679.	
Mouse Scrolling Features Wheel Vertical Scrolling Life Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Country of Manufacture ISO 9001 Qualified Manufacturer ISO 14001 Qualified Manufacturer Restriction on Hazardous Substances  FCC/IC ID	Standard vertical scrolling  • 100,000 revolutions (away from user)  • 300,000 revolutions (towards user)  -40 °F (-40 °C) to 140 °F (60 °C) at < 5% to 65% relative humidity (non-condensing)  32 °F (0 °C) to 104 °F (40 °C) at < 5% to 80% relative humidity (non-condensing)  People's Republic of China (PRC)  Yes  Yes  This device complies with all applicable worldwide regulations and restrictions including, but not limited to: EU directive 2002/95/EC on the Restriction the Use of Certain Hazardous Substances in Electrical and Electronic Equipment and EU Registration Evaluation and Authorization of Chemicals (REACH) regulation regarding Substances of Very High Concern.  This Class B digital apparatus complies with Part 15 of the U.S. Federal Communications Commission (FCC) rules, Canadian ICES-003, and RSS-21 Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Tested to comply with FCC (U.S. Federal Communications Commission) Standards. For home or office use. The term "IC:" before the certification/registration number only signifies that the Industry Canada technical specifications were met. Model numbers: 1678 Designer Bluetooth Keyboard and 1679, Designer Bluetooth Mouse. FCC ID: C3K1678 and C3K1679. ID: 3048A-1678 and 3048A-1679.	
Mouse Scrolling Features Wheel Vertical Scrolling Life Storage Temperature & Humidity Operating Temperature & Humidity Certification Information Country of Manufacture ISO 9001 Qualified Manufacturer ISO 14001 Qualified Manufacturer Restriction on Hazardous Substances	Standard vertical scrolling  • 100,000 revolutions (away from user)  • 300,000 revolutions (towards user)  -40 °F (-40 °C) to 140 °F (60 °C) at < 5% to 65% relative humidity (non-condensing)  32 °F (0 °C) to 104 °F (40 °C) at <5% to 80% relative humidity (non-condensing)  People's Republic of China (PRC)  Yes  Yes  This device complies with all applicable worldwide regulations and restrictions including, but not limited to: EU directive 2002/95/EC on the Restriction the Use of Certain Hazardous Substances in Electrical and Electronic Equipment and EU Registration Evaluation and Authorization of Chemicals (REACH) regulation regarding Substances of Very High Concern.  This Class B digital apparatus complies with Part 15 of the U.S. Federal Communications Commission (FCC) rules, Canadian ICES-003, and RSS-21 Operation is subject to the following two conditions: (1) this device may not cause interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. Tested to comply with FCC (U.S. Federal Communications Commission) Standards. For home or office use. The term "IC:" before the certification/registration number only signifies that the Industry Canada technical specifications were met. Model numbers: 1678 Designer Bluetooth Keyboard and 1679, Designer Bluetooth Mouse. FCC ID: C3K1678 and C3K1679.	



## **Technical Data Sheet**

Certification Information			
Agency and Regulatory Marks	ACMA Declaration of Conformity (Australia and New Zealand) DWLFM Certificate (Bahrain) ANATEL Certificate (Bahrain) IC ID, RSS-210 Certificate of Acceptance (Canada) SUBTEL Certificate (Chile) EIP Pollution Control Mark, EPUP (China) CMIIT Certificate (China) NTRA Certificate (Egypt) RTT&E Declaration of Conformity (European Union) WEEE (European Union) POSTEL Certificate (Indonesia) MIC Certificate (Israel) VCCI and TELEC Certificates (Japan) TRC Certificate (Kenya) KCC Certificate (Korea) MOT Certificate (Korea) MOT Certificate (Kuwait)	SIRIM Certificate (Malaysia) ICTA Certificate (Mauritius) IFETEL Certificate (Morocco) ANRT Certificate (Morocco) TRA Certificate (Morocco) TRA Certificate (Peru) ICT Certificate (Peru) CTC Certificate (Qatar) EAC and FAC Certificates (Russia, Kazakhstan) TITC Letter (Kingdom of Saudi Arabia) IDA Approval (Singapore) ICASA Certificate (South Africa) NCC Certificates (Taiwan) NTC SDoC (Thailand) UNIIRT Certificate (Ukraine) TRA Certificate (Ukraine) TRA Certificate (United Arab Emirates) FCC ID, Grant of Equipment Authorization (USA)	
Windows Certification Kit (WCK)	Mouse ID: 1705706 (32-bit), 1705707 (64-bit) Microsoft Windows 8.1, and 1705708 Microsoft Windows 8.1 RT Keyboard ID: 1709884 (32-bit and 64-bit) and 1709888 Microsoft Windows 8.1 RT		