

ATX PSU
HYPER 80+ PRO Series

H3-450

H3-550

H3-650

H3-700



Specification

- ❑ Complies with ATX12 v2.4 & EPS12 v2.92
- ❑ Efficiency $\geq 85\%$ @ typical Load
- ❑ Active PFC ≥ 0.9
- ❑ Hold up time > 17ms @80% Load
- ❑ +12V Single-Rail Design
- ❑ +5V & 3.3V DC to DC Module Design
- ❑ 120mm Silent & long life Fan
- ❑ Complete Protections: OCP/OVP/OPP/SCP

Rating Information

- H3-450

AC INPUT 交流輸入	200-240V~ 4A 50-60Hz				
DC OUTPUT 直流輸出	+3.3V	+5V	+12V	-12V	+5V _{SB}
Max. Output Current 最大輸出電流	16A	16A	37.5A	0.3A	2.5A
Max. Combined Power 最大功率	85W		450W	3.6W	12.5W
Total Power 額定功率	450W				

● H3-550

AC INPUT 交流輸入	200-240V~ 4.5A 50-60Hz				
DC OUTPUT 直流輸出	+3.3V	+5V	+12V	-12V	+5V _{SB}
Max. Output Current 最大輸出電流	16A	16A	45.8A	0.3A	2.5A
Max. Combined Power 最大功率	85W		549.6W	3.6W	12.5W
Total Power 額定功率	550W				

● H3-650

AC INPUT 交流輸入	200-240V~ 5A 50-60Hz				
DC OUTPUT 直流輸出	+3.3V	+5V	+12V	-12V	+5V _{SB}
Max. Output Current 最大輸出電流	20A	20A	54.1A	0.3A	2.5A
Max. Combined Power 最大功率	100W		649.2W	3.6W	12.5W
Total Power 額定功率	650W				

● H3-700

AC INPUT 交流輸入	200-240V~ 5A 50-60Hz				
DC OUTPUT 直流輸出	+3.3V	+5V	+12V	-12V	+5V _{SB}
Max. Output Current 最大輸出電流	20A	20A	58A	0.3A	2.5A
Max. Combined Power 最大功率	100W		696W	3.6W	12.5W
Total Power 額定功率	700W				

Output Cable Information

Model	MB 20+4Pin	CPU 4+4Pin	PCI-e 6+2Pin	SATA	Molex	Floppy
450W	450 mm	550 mm	400+150 mm	S+S+S (400+150+150) S+S+P+P (400+150+100+100)		
	1	1	2	5	2	0
550W	450 mm	550 mm	400+150 mm	S+S+S (400+150+150) S+S+P+P (400+150+100+100)		
	1	1	2	5	2	0
650W	550 mm	600 +150mm	400+155 mm	S+S+S (400+150+150) S+S+P+P (400+150+100+100)		
	1	2	2	5	2	0
700W	550 mm	600 +150mm	400+150 mm*2	S+S+S (400+150+150) S+S+P+P (400+150+100+100)		
	1	2	4	5	2	0

