

3.5 HDD DATA SHEET

## Amazing Versatility and Trusted Dependability Meet Incredible Speed



Lightning-fast performance and titanic storage up to 12TB give your desktop or creative professional system the edge you need to be your very best. BarraCuda® Pro 3.5-inch drives are also backed by a 5-year limited warranty.



### Best-Fit Applications

- Creative pros systems
- Desktop or all-in-one PCs
- Home servers
- Entry-level direct-attached storage devices (DAS)



## Key Advantages

**Highest capacity.** Up to 12TB means you get the highest storage capacity available in the 3.5-inch PC class.

**Peace of mind.** A 5-year limited warranty and 300TB/year workload limit means this drive has your back.

**Incredible speed.** Delivers 7200-RPM spin speed along with sustained data rates up to 250MB/s and burst data rates of 6Gb/s.

**Energy efficient.** This drive is one of the lowest-power 3.5-inch drives on the market.

**Ultimate protection.** Bundled with Seagate® Rescue Data Recovery, this drive is protected for 2 years against any mechanical, accidental or natural disaster—with a 90% success rate for in-house recovery.<sup>1</sup>

**History of reliability.** For 20+ years, the Barracuda family has had a reputation for complete reliability.

**Optimized for creative pros.** Designed and tuned for creative applications, these drives feature higher random performance and drive reliability than typical PC compute drives.

<sup>1</sup> Registration required to activate.



Specifications	12TB	10TB	8TB
Standard Model Numbers	ST12000DM0007	ST10000DM0004	ST8000DM0004
Bytes per Sector	512	512	512
<b>Performance</b>			
Interface	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s
SATA Transfer Rates Supported (Gb/s)	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5
Max. Sustained Transfer Rate OD (MB/s)	250MB/s	220MB/s	220MB/s
Cache, Multisegmented (MB)	256	256	256
<b>Reliability/Data Integrity</b>			
Load/Unload Cycles	300,000	300,000	300,000
Nonrecoverable Read Errors per Bits Read, Max	1 per 10E15	1 per 10E15	1 per 10E15
Power-On Hours per Year (24x7)	8760	8760	8760
Data Recovery and Rescue Services	Yes	Yes	Yes
Workload Rate Limit (TB/year) <sup>1</sup>	300	300	300
Limited Warranty (years)	5	5	5
<b>Power Management</b>			
Startup Power (A)	1.8	1.8	1.8
Operating Mode, Typical (W)	7.8	7.8	6.8
Idle Average (W)	5.0W	5.0W	4.5W
Standby Mode/Sleep Mode, Typical (W)	0.80/0.80	0.80/0.80	0.80/0.80
<b>Environmental/Temperature</b>			
Operating (ambient, min)	0°C	0°C	0°C
Operating (drive case, max)	60°C	60°C	60°C
Nonoperating (ambient)	-40°C – 70°C	-40°C – 70°C	-40°C – 70°C
Halogen Free	Yes	Yes	Yes
RoHS Compliance	Yes	Yes	Yes
<b>Physical</b>			
Height (mm/in, max)	26.11mm/1.028in	26.11mm/1.028in	26.11mm/1.028in
Width (mm/in, max)	101.85mm/4.010in	101.85mm/4.010in	101.85mm/4.010in
Depth (mm/in, max)	146.99mm/5.787in	146.99mm/5.787in	146.99mm/5.787in
Weight (g/lb)	705g/1.55lb	705g/1.55lb	650g/1.43lb
Carton Unit Quantity	20	20	20
Cartons per Pallet/Cartons per Layer	40 / 8	40 / 8	40 / 8

<sup>1</sup> BarraCuda Pro drives are designed for always-on workloads of 300TB/year. For higher transaction workloads, see Seagate's enterprise-class drive offerings



Specifications	6TB	4TB	2TB
Standard Model Numbers	ST6000DM004	ST4000DM006	ST2000DM009
Bytes per Sector	512	512	512
<b>Performance</b>			
Interface	SATA 6Gb/s	SATA 6Gb/s	SATA 6Gb/s
SATA Transfer Rates Supported (Gb/s)	6.0/3.0/1.5	6.0/3.0/1.5	6.0/3.0/1.5
Max. Sustained Transfer Rate OD (MB/s)	220MB/s	220MB/s	195MB/s
Cache, Multisegmented (MB)	256	128	128
<b>Reliability/Data Integrity</b>			
Load/Unload Cycles	300,000	300,000	300,000
Nonrecoverable Read Errors per Bits Read, Max	1 per 10E15	1 per 10E15	1 per 10E15
Power-On Hours per Year (24x7)	8760	8760	8760
Data Recovery and Rescue Services	Yes	Yes	Yes
Workload Rate Limit (TB/year) <sup>1</sup>	300	300	300
Limited Warranty (years)	5	5	5
<b>Power Management</b>			
Startup Power (A)	2.0	2.0	2.0
Operating Mode, Typical (W)	9.0	6.7	6.7
Idle Average (W)	7.2W	6.0W	4.5W
Standby Mode/Sleep Mode, Typical (W)	0.6/0.6	0.6/0.6	0.8/0.8
<b>Environmental/Temperature</b>			
Operating (ambient, min)	0°C	0°C	0°C
Operating (drive case, max)	60°C	60°C	60°C
Nonoperating (ambient)	-40°C – 70°C	-40°C – 70°C	-40°C – 70°C
Halogen Free	Yes	Yes	Yes
RoHS Compliance	Yes	Yes	Yes
<b>Physical</b>			
Height (mm/in, max)	26.1mm/1.028in	26.1mm/1.028in	26.1mm/1.028in
Width (mm/in, max)	101.85mm/4.010in	101.85mm/4.010in	101.85mm/4.010in
Depth (mm/in, max)	146.99mm/5.787in	5.787mm/146.99in	146.99mm/5.787in
Weight (g/lb)	780g/1.72lb	680g/1.50lb	550g/1.21lb
Carton Unit Quantity	20	20	20
Cartons per Pallet/Cartons per Layer	40 / 8	40 / 8	40 / 8

<sup>1</sup> BarraCuda Pro drives are designed for always-on workloads of 300TB/year. For higher transaction workloads, see Seagate's enterprise-class drive offerings

seagate.com



AMERICAS Seagate Technology LLC 10200 South De Anza Boulevard, Cupertino, California 95014, United States, 408-658-1000  
 ASIA/PACIFIC Seagate Singapore International Headquarters Pte. Ltd. 7000 Ang Mo Kio Avenue 5, Singapore 569877, 65-6485-3888  
 EUROPE, MIDDLE EAST AND AFRICA Seagate Technology SAS 16-18, rue du Dôme, 92100 Boulogne-Billancourt, France, 33 1-4186 10 00

© 2017 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology and the Spiral logo are registered trademarks of Seagate Technology LLC in the United States and/or other countries. BarraCuda is either a trademark or registered trademark of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one trillion bytes. Your computer's operating system may use a different standard of measurement and report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions, and thus will not be available for data storage. Actual data rates may vary depending on operating environment and other factors. Seagate reserves the right to change, without notice, product offerings or specifications. DS1901.7-1707US July 2017