



[kingston.com/ssd](https://kingston.com/ssd)

## KINGSTON FURY RENEGADE SSD

# FOR GAMERS, ENTHUSIASTS, AND HIGH-POWER USERS

Kingston FURY™ Renegade PCIe 4.0 NVMe M.2 SSD provides cutting-edge performance in high capacities for gaming and hardware enthusiasts seeking extreme performance for PC builds and upgrades. By leveraging the latest Gen 4x4 NVMe controller and 3D TLC NAND, Kingston FURY Renegade SSD offers blazing speeds up to 7,300/7,000MB/s<sup>1</sup> read/write and up to 1,000,000 IOPS<sup>1</sup> for amazing consistency and exceptional gaming experience. From game and application loading times to streaming and capturing, give your system a boost in overall responsiveness.

With better heat management comes better stability during peak performance. The slim M.2 combined with a low profile, graphene aluminum heat spreader is optimized for intense usage in gaming laptops and desktops. The optional heatsink model delivers an additional layer of thermal dispersion so when the game heats up, your PS5™ console stays cool. Kingston FURY Renegade SSD matches the top-tier performance of the Kingston FURY Renegade memory line to produce the ultimate team that will keep you at the top of your game.

Available in capacities from 500GB–4TB<sup>2</sup> to store an extensive library of your favorite games and media.

- › Incredible PCIe Gen 4x4 NVMe performance
- › Available with heatsink or low-profile heat spreader
- › Slim M.2 2280 form factor
- › High capacities up to 4TB<sup>2</sup>
- › PS5™ Ready

more >>

**FEATURES / BENEFITS**

**Level up with PCIe 4.0 NVMe** — Dominate with cutting-edge Gen 4x4 intense speeds up to 7,300/7,000MB/s<sup>1</sup> read/write and up to 1,000,000 IOPS<sup>1</sup> performance.

**Maximize your motherboard** — Powerful slim M.2 form factor to enhance your gaming rig and laptop.

**More space to play** — Get all the latest titles and DLC available. Performance with high capacities up to 4TB<sup>2</sup> to store your favorite games and media.

**Low profile graphene aluminum heat spreader** — Advanced thermal dissipation keeps your drive cool during intense usage. Brings higher performance to the tightest of spaces in gaming laptops and motherboards.

**PS5™ Ready** — Game-changing storage designed to maximize your play. Optional integrated aluminum heatsink model provides an additional layer of thermal dispersion to cool the drive and maintain peak performance.

**SPECIFICATIONS**

**Form Factor**

M.2 2280

**Interface**

PCIe 4.0 x4 NVMe

**Capacities<sup>2</sup>**

500GB, 1TB, 2TB, 4TB

**Controller**

Phison E18

**NAND**

3D TLC

**Sequential Read/Write<sup>1</sup>**

500GB – 7,300/3,900MB/s      1TB – 7,300/6,000MB/s  
 2TB – 7,300/7,000MB/s      4TB – 7,300/7,000MB/s

**Random 4K Read/Write<sup>1</sup>**

500GB – up to 450,000/900,000 IOPS  
 1TB – up to 900,000/1,000,000 IOPS  
 2TB – up to 1,000,000/1,000,000 IOPS  
 4TB – up to 1,000,000/1,000,000 IOPS

**Total Bytes Written (TBW)<sup>3</sup>**

500GB – 500TB 1TB – 1.0PB 2TB – 2.0PB 4TB – 4.0PB

**Power Consumption**

500GB – 5mW Idle / 0.34W Avg / 2.7W (MAX) Read / 4.1W (MAX) Write  
 1TB – 5mW Idle / 0.33W Avg / 2.8W (MAX) Read / 6.3W (MAX) Write  
 2TB – 5mW Idle / 0.36W Avg / 2.8W (MAX) Read / 9.9W (MAX) Write  
 4TB – 5mW Idle / 0.36W Avg / 2.7W (MAX) Read / 10.2W (MAX) Write

**Storage Temperature**

-40°C~85°C

**Operating Temperature**

0°C~70°C

**Dimensions**

Heat spreader: 80mm x 22mm x 2.21mm (500GB-1TB)  
 80mm x 22mm x 3.5mm (2TB-4TB)  
 Heatsink: 80mm x 23.67mm x 10.5mm

**Weight**

Heat spreader: 500GB-1TB – 7g      2TB-4TB – 9.7g  
 Heatsink: 500GB-1TB – 32.1g      2TB-4TB – 34.9g

**Vibration Operating**

2.17G Peak (7-800Hz)

**Vibration Non-operating**

20G Peak (20-1000Hz)

**MTBF**

1,800,000 hours

**Warranty/Support<sup>4</sup>**

Limited 5-year warranty with free technical support



**PART NUMBERS**

Heat Spreader	Heatsink
SFYRS/500G	SFYRSK/500G
SFYRS/1000G	SFYRSK/1000G
SFYRD/2000G	SFYRDK/2000G
SFYRD/4000G	SFYRDK/4000G

The SSD is designed for use in desktop and notebook computer workloads and is not intended for Server environments.

- Based on "out-of-box performance" using a PCIe 4.0 motherboard. Speed may vary due to host hardware, software, and usage.
- Some of the listed capacity on a flash storage device is used for formatting and other functions and thus is not available for data storage. As such, the actual available capacity for data storage is less than what is listed on the products. For more information, go to Kingston's Flash Memory Guide at [kingston.com/flashguide](http://kingston.com/flashguide).
- Total Bytes Written (TBW) is derived from the JEDEC Client Workload (JESD219A).
- Limited warranty based on 5 years or "Percentage Used" which can be found using the Kingston SSD Manager (Kingston.com/SSDManager). For NVMe SSDs, a new unused product will show a Percentage Used value of 0, whereas a product that reaches its warranty limit will show a Percentage Used value of greater than or equal to one hundred (100). See [Kingston.com/wa](http://Kingston.com/wa) for details.



THIS DOCUMENT SUBJECT TO CHANGE WITHOUT NOTICE.

©2022 Kingston Technology Corporation, 17600 Newhope Street, Fountain Valley, CA 92708 USA. All rights reserved. Kingston FURY and the Kingston FURY logo are trademarks of Kingston Technology Corporation. All trademarks are the property of their respective owners. MKD-441.3 US

