



## SPECIFICATIONS

<b>Model Name</b>	GeForce RTX™ 4080 SUPER 16G GAMING X SLIM
<b>Cores</b>	10240 Units
<b>Memory</b>	16GB GDDR6X
<b>Standard sběrnice</b>	PCI Express® Gen 4
<b>Rozhraní paměti</b>	256-bit
<b>Takt jádra (MHz)</b>	Extreme Performance: 2625 MHz (MSI Center) Boost: 2610 MHz (GAMING & SILENT Mode)
<b>Takt paměti (MHz)</b>	23 Gbps
<b>Max připojených displejů</b>	4
<b>Output</b>	DisplayPort x 2 (v1.4a) HDMI™ x 2 (Supports 4K@120Hz HDR, 8K@60Hz HDR, and Variable Refresh Rate as specified in HDMI 2.1a)
<b>HDCP podpora</b>	Y
<b>Doporučený výkon zdroje (W)</b>	850 W (Min.750 W)
<b>Digital Maximum Resolution</b>	7680 x 4320
<b>Napájecí kabely</b>	16-pin x 1
<b>Podpora DirectX verze</b>	12 Ultimate
<b>Podpora OpenGL verze</b>	4.6
<b>Rozměry (mm)</b>	322 x 136 x 62 mm
<b>Váha (g)</b>	1628 g / 2327 g

## CONNECTIONS



1. DisplayPort
2. HDMI™

## FEATURES



### TRI FROZR 3

Stay cool and quiet. MSI's TRI FROZR 3 thermal design enhances heat dissipation all around the graphics card.



### TORX FAN 5.0

Fan blades linked by ring arcs and a fan cowl work together to stabilize and maintain high-pressure airflow.



### Copper Baseplate

Heat from the GPU and memory modules is captured by a copper baseplate and then rapidly transferred to Core Pipes.



### Core Pipe

Precision-machined heat pipes ensure max contact to the GPU and spread heat along the full length of the heatsink.



### Airflow Control

Sections of different heatsink fins disrupt unwanted airflow harmonics and reduce noise.



### Metal Backplate

A sturdy backplate helps to strengthen the graphics card while a flow-through design reduces trapped heat.



### Dual BIOS

Dual BIOS lets you set the priority to full performance in GAMING mode or low noise in SILENT mode.



### MSI Center

The exclusive MSI Center software lets you monitor, tweak and optimize MSI products in real-time.