

PHILIPS

Philips Unite LED
6000 Series All In One

LED Solutions

135"



135HDL6015IA/00



Philips Unite LED 6015 All In One

Enhanced mobility, safety, and energy efficiency

Maximise ROI with this ultimately flexible dvLED display. Mechanised to raise and lower, as well as folding to fit through doorways, this All In One display can be moved to suit, with the option for a flight case for easy movement, too.

Crystal-clear COB LED with nano coating

- 1.5mm pixel pitch for ultra-sharp visuals

Unique low power standby mode

- Using less than 0.5W in standby mode for best energy savings

Integrated electric lifting trolley

- Adjust the height of the display, effortlessly, safely, and smoothly

Smart foldable display construction

- Designed for easier transportation and space saving storage

Emergency stop function

- Immediate stop capability for motorised height adjustments

Anti pinch protection

- Prevents injuries during lifting or lowering operations

Integrated Android SoC – Philips Wave ready

- Control with remote or via remote device management

Simplified one-box installation

- Including built-in cabling and audio, all in one package

Highlights

Motorised height adjustment

Designed for professional flexibility and enhanced mobility, the Philips Unite LED 6015 All In One includes a motorised trolley enabling smooth and safe electric lifting. Adjust the display height easily with just the push of a button, ensuring perfect viewing in any setting. Ideal for dynamic spaces, this height adjusting feature also allows for simple transportation through doors between rooms, and in elevators between floors.

Foldable design for easy handling

Designed with a smart, foldable structure, setup, transportation, and storage are more convenient than ever. Seamless when set up, the screen folds neatly for compact transportation, protecting the display during moves and allowing easier access through standard doors and in elevators.

Emergency stop and anti-pinch

Safety comes first and with the motorised height adjustment on the Philips Unite LED 6015 All In One with special features including an emergency stop button and anti-pinch protection are integrated as standard. The emergency stop ensures quick response during lifting, while the anti-pinch function detects obstructions and halts movement to prevent injury or equipment damage.

Ultra-efficient standby mode

Maximise energy savings without compromising on quality or reliability. The Philips Unite LED 6015 All In One includes our ultra-low standby mode. Consuming less than 0.5 Watts, this unique feature helps to lower operational costs and support sustainability goals. Instant power-up via remote control ensures minimal downtime when you are ready to present.

Crystal clear visuals with COB LED technology

Experience superior picture quality with COB LED and a fine 1.5mm pixel pitch. Vibrant colours, deep blacks, and uniform brightness create an immersive visual experience, ideal for professional meeting rooms, auditoriums, and corporate settings.

Simple installation, everything included

The Philips Unite LED 6015 All In One will arrive with you ready to go, with all components pre-installed and configured. The motorised trolley, foldable screen, remote control, and Wi-Fi/Bluetooth module come included, simplifying installation and making deployment fast, easy, and efficient.

Integrated Android SoC

Incorporating the world-renowned reliability of Android 11. Optimised for native Android apps, the integrated System on Chip (SoC) enables you to install web apps and software directly onto the display, eliminating the need for an external media player.

Philips Wave ready

Philips Wave – the evolutionary remote device management platform – puts you fully in control. Simplified installation and setup, monitoring and control, firmware upgrades, managing playlists, and setting power schedules. Saving time, energy, and environmental impact.

Specifications

Picture/Display

Aspect ratio: 16:9
Brightness uniformity: $\geq 95\%$
Brightness Max: 500 cd/m²
Colour temperature adjust range (K): 6500 \pm 500
Contrast ratio (typical): 5000:1
Frame frequency (Hz): 50/60
Refresh rate (Hz): 3840
Electric Lifting: Yes
Screen Folding: Yes
Anti-Pinch: Yes
Emergency stop: Yes

Connectivity

Video input: DVI-I (x 1), DisplayPort 1.4 (x 1),
HDMI 2.0 (x 2), USB 3.0 (x 2)
Audio input: 3.5 mm mini jack (x 1)
Audio out: 3.5 mm headphone/line-out jack
Video output: DisplayPort 1.4 (x 1)
External control: RS232C (in/out) 2.5 mm jack,
RJ45, IR (in/out) 3.5 mm jack

Power

Mains power: AC 100~240
Max Power consumption (W): 1.650
Typical power cons. (W): 600

Operating conditions

Temperature range (operation): -20~45 °C
Temperature range (storage): -20~50 °C
Humidity range (operation)[RH]: 10~80%
Humidity range (storage) [RH]: 10~85%

Module

LED type: COB
Pixel constitution: 1R1G1B_Flip Chip
LED lifetime(Hrs): 100.000
Module resolution (WxH pixels): 96 x 108
Pixel pitch (mm): 1.5625
Module size (W x H in mm): 150 x 168.75

Feature

File management, Chromium, Browser, Media Player, Settings, Teamviewer, PDF Player, Interact as source

Accessories

Included accessories: Remote Control and AAA Batteries, Quick start guide, Speaker set, Wi-Fi module: CRD22 Wi-Fi USB module, incl 2 antennas

Miscellaneous

Warranty: 3 Years
Regulatory approvals: CE, FCC SDOC, Part 15, Class A, CB 62368, RoHS

Packaging Data

Packing Options: Wooden crate

