


BE Series



- Single +12V Output
- Smart Thermal Control to Balance Noise & Cooling
- 120mm Cooling Fan
- +5V & +3.3V DC-DC Design For B75E
- +3.3V DC-DC Design For B65E, B55E, B45E
- MTBF 100KHRs @ 25°C per MIL-STD-217D/F
- Operating Ambient 0°C Minimum to +40°C Maximum
- ErP Lot 6 Compliant
- Dimensions: 150(W) X 140(L) X 86(H) mm
- ATX12V V2.4 For B65E, B55E, B45E
- ATX12V V3.1 For B75E support 12V-2x6 Connector

Connector

Connector							
	20+4 Pin Main Power Connector	8 Pin +12V CPU Power Connector	4 Pin +12V CPU Power Connector	6+2 Pin PCIe Power Connector	16 Pin 12V-2x6 PCIe Power Connector	SATA Power Connector	Peripheral Power Connector
B75E	1	1	1	2	1 (320W)	6	3
B65E	1	1	1	2	N/A	6	3
B55E	1	1	1	2	N/A	6	3
B45E	1	1	1	2	N/A	6	3

Specifications

MODEL	Max. Output	AC Input	+12V	+5V	+3.3V	-12V	+5VSB	MAX1	MAX2
B75E	750W	220-230V	62.5A	20.0A	20.0A	0.3A	3.0A	100W	750W
B65E	650W	200-240V	50.0A	20.0A	20.0A	0.3A	3.0A	100W	600W
B55E	550W	200-240V	42.0A	20.0A	20.0A	0.3A	3.0A	100W	504W
B45E	450W	200-240V	36.0A	20.0A	20.0A	0.3A	3.0A	100W	432W

* MAX1: 5V & 3.3V Combined Output * MAX2: +12V Total Output

Safety

B65E, B55E, B45E



B75E

