



全漢企業股份有限公司

電氣規格書

料號 :
9PA300AV00 ,FMP,G.P,FSP300-40PFB,IPC,AT,300W,BALL,WO/IO,WO/SS,FSP,W/PFC(A),86H*150L*140W,FULL RANGE,STD,RAZ02,
9PA300AV01 ,G.P,SPT300PFB,(S03001),IPC,AT,300W,BALL,WO/IO,WO/SS,SPI,W/PFC(A),FULL RANGE,9PA300AV00,RAZ02,
9PA300AV02 KEEP201509,NPD,G.P,SPT300PFB,(S03002),IPC,AT,NON ErP,300W,BALL,WO/IO,WO/SS,SPI,W/PFC(A),OEM,FULL RANGE,9PA300AV01,RAZ02,
9PA300AV03 ,G.P,,FSP300-40PFB,(F04001),IPC,AT,,NON ErP,,300W,,SLEEVE,WO/IO,WO/SS,FSP,,,W/PFC(A),,ODM,,,FULL RANGE,F04,,9PA300AV00,,,RAZ02,,
版次 : 5
文件編號 : ESD07002184
附件版本 : 2
研發部門 : RAZ02
作者 : winnie/陳婉立
Model No/Type : FSP300-40PFB
機密 : N
發行日期 : 2017/1/6-17:29:53
備註 : 1.更新FSP LOGO(12/03/2007)
升版理由 : 1.增加延伸9PA300AV01(12/03/2007) 2.增加延伸9PA300AV02(02/04/2010) 3.修正版本標示(12/24/2010) 4.增加延伸9PA300AV03(01/06/2016)

單位	姓名	單位	姓名	單位	姓名
主管	Tj莊同榮				



全漢企業股份有限公司
FSP TECHNOLOGY INC.

台灣 桃園市建國東路 22 號

NO.22, Jianguo E. Rd., Taoyuan City, Taiwan, R.O.C.
TEL: +886-3-375-9888 FAX: +886-3-375-6966

SPECIFICATION

FSP300-40PFB

Main Feature:
Active PFC Circuit
Full Range Input

JUN 25, 2007

REV: 2



全漢企業股份有限公司
FSP TECHNOLOGY INC.

MODEL: FSP300-40PFB

Revision History

<u>Rev</u>	<u>Description</u>	<u>Date</u>	<u>Author</u>
2	Delete 2.2SAFETY 6.1. LEAKAGE CURRENT	2007.06.25	Winnie

1. GENERAL DESCRIPTION AND SCOPE

This is the specification of Model FSP300-40PFB; AC-line powered switching power supply with active PFC (Power Factor Correction) circuit, meet EN61000-3-2 and with Full Range Input features. Designed and manufactured by FSP GROUP.

The specification below is intended to describe as detailedly as possible the functions and performance of the subject power supply. Any comment or additional requirements to this specification from our customers will be highly appreciated and treated as a new target for us to approach.

2. REFERENCE DOCUMENTS

The subject power supply will meet the EMI requirements and obtain main safety approvals as following:

2.1 EMI REGULATORY

- FCC Part 15 Subpart J, Class 'B' 115 Vac operation.
- CISPR 22 Class 'B' 230 Vac operation.

3. PHYSICAL REQUIREMENTS

3.1 MECHANICAL SPECIFICATIONS

The mechanical drawing of the subject power supply, which indicate the form factor, location of the mounting holes, location, the length of the connectors, and other physical specifications of the subject power supply. Please refer to the attachment drawing.

4. ELECTRICAL REQUIREMENTS

4.1 OUTPUT ELECTRICAL REQUIREMENTS

The subject power supply will meet all electrical specifications below, over the full operation temperature range and dynamic load regulation.

4.1.1. OUTPUT RATING

Output	Nominal	Regulation	Ripple/Noise	Min	Max
1	+5V	±5%	50mV	2.0A	40.0 A
2	+12V	±5%	120mV	1A	15.0 A
3	-5V	±10%	50mV	0 A	0.3A
4	-12V	±10%	120mV	0 A	0.8 A

The +5V and +12V total output power shall not exceed 290W and the total output for this subject power supply is 300 watts. Ripple and noise measurements shall be made under all specified load conditions through a single pole low pass filter with 20MHz cutoff frequency. Outputs shall bypassed at the connector with a 0.1uF ceramic disk capacitor and a 10uF electrolytic capacitor to simulate system loading.

4.1.2. LOAD CAPACITY SPECIFICATIONS

The cross regulation defined as follows, the voltage regulation limits DC include DC Output ripple & noise.

LOAD	STM.	+5V	+12V	-5V	-12V
ALL MAX	HHHH	34.0A	10.0A	0.3A	0.7A
+5V MAX other MIN	HLLL	40.0 A	4.5A	0A	0A
+12V MAX other MIN	LHLL	2.0 A	15.0A	0A	0A
ALL MIN	LLLL	2.0A	0.1A	0A	0A

4.1.3. HOLD-UP TIME (@FULL LOAD)

115V / 60Hz : 17 mSec. Minimum.

230V / 50Hz : 17 mSec. Minimum.

The output voltage will remain within specification, in the event that the input power is removed or interrupted, for the duration of one cycle of the input frequency. The interruption may occur at any point in the AC voltage cycle. The power good signal shall remain high during this test.

4.1.4.OUTPUT RISE TIME

(10% TO 90% OF FINAL OUTPUT VALUE, @FULL LOAD)

115V-rms or 230V-rms + 5Vdc : 20ms Maximum

4.1.5.OVER VOLTAGE PROTECTION

Voltage Source	Protection Point
+5V _{dc}	5.5V-6.82V
+12V _{dc}	13.4V-15.6V

4.1.6.SHORT CIRCUIT PROTECTION

Output short circuit is defined to be a short circuit load of less than 0.1 ohm.

In the event of an output short circuit condition on +5V or +12V output, the power supply will shutdown and latch off without damage to the power supply. The power supply shall return to normal operation after the short circuit has been removed and the power switch has been turned off for no more than 2 seconds.

In the event of an output short circuit condition on -5V or -12V output, the power supply will not be damaged. The power supply shall return to normal operation as soon as the short circuit has been removed. and the power switch has been turned off for no more than 2 seconds.

4.1.7.OVERLOAD PROTECTION

Overload currents defined as a 5 amp/sec fault current ramp starting from full load, applied to the +5V output, shall not cause that output to exceed 60 amps before the output voltage drops below 0.5 volts and is latched off. The +12V output shall not exceed 30amps under the same ramp conditions starting at full load before it is latched off.

The overload protection must be such that the power supply is protected from damage by entering a shutdown condition.

4.1.8.POWER GOOD SIGNAL


The power good signal is a TTL compatible signal for the purpose of initiating an orderly star-up procedure under normal input operating conditions. This signal is asserted (low) until +5Vdc has reached 4.75 volts during power up. Characteristics:

TTL signal asserted (low state) : less than 0.5V while sinking 10mA.

TTL signal asserted (high state): greater than 4.75V while sourcing 500uA.

High state output impedance: less or equal to 1Kohm from output to common.

POWER GOOD @ 115/230V, FULL LOAD	100 –500mSec.
POWER FAIL @115/230V, FULL LOAD	1 mSec. minimum



4.2. OUTPUT TRANSIENT LOAD RESPONSE


+5V and +12V must be within specification for a step change in current as specified below. The outputs will be tested one section at a time with all other sections at maximum load. The test transition will be from IA to IB and IB to IA. The step current will have a nominal transition time of 0.5 amp per microsecond for +5V and 0.1 amp per microsecond for +12V.

+5Vdc:

IA:	40 amps
IB:	30 amps
Volts variation:	400 mV max (p-p)
Setting time:	10 ms max

+12Vdc:

IA:	15.0 amps
IB:	12.0 amps
Volts variation:	450 mV max (p-p)
Setting time:	10 ms max



4.3. INPUT ELECTRICAL SPECIFICATIONS

4.3.1. INPUT RATING: FULL RANGE INPUT

PARAMETER		UNITS
V-in Range	90 - 264	V-rms

4.3.2. INPUT FREQUENCY

NOMINAL FREQUENCY	
115V	60Hz
230V	50Hz

4.3.3. INRUSH CURRENT

(Cold start – 25 deg. C)

115V	80 Amps - peak
230V	120 Amps - peak

4.3.4. INPUT LINE CURRENT

115V	7.0 Amps – rms maximum
230V	3.0 Amps – rms maximum

4.4. EFFICIENCY

115 VAC @Full Load	75% minimum
230 VAC @Full Load	75% minimum

5. ENVIRONMENTAL REQUIREMENTS

The power supply will be compliant with each item in this specification for the following Environmental conditions.

5.1. TEMPERATURE RANGE

Operating	0 to +50 deg. C
Storage	-20 to +80 deg. C

5.2. HUMIDITY

Operating	5 –95% RH, Non-condensing
Storage	5 –95% RH, Non-condensing

5.3. VIBRATION

The subject power supply will withstand the following imposed conditions without experiencing non-recoverable failure or deviation from specified output characteristics.

Vibration Operating – Sine wave excited, 0.25 G maximum acceleration, 10-250 Hz swept at one octave / min. Fifteen minute dwell at all resonant points, where resonance is defined as those exciting frequencies at which the device under test experiences excursions two times large than non-resonant excursions.

Plane of vibration to be along three mutually perpendicular axes.

5.4. SHOCK

The subject power supply will withstand the following imposed conditions without experiencing non-recoverable failure or deviation from specified output characteristics.

Storage 40G, 11 mSec. half-sine wave pulse in both directions on three mutually perpendicular axes.

Operating 10G, 11mSec. half-sine wave pulse in both directions on three mutually Perpendicular axes.

5.5 COOLING SPECIFICATIONS

5.5.1. The subject power supply is cooled by a self-contained, 80mm, 12VDC fan.

6. SAFETY

6.1. LEAKAGE CURRENT

The leakage current from AC to safety ground will not exceed 3.5 mA-rms at 264Vac, 50 Hz.

7. ELECTROMAGNETIC COMPATIBILITY

7.1 LINE CONDUCTED EMI

The subject power supply will meet FCC and VFG class B requirements under full load conditions.

7.2. RADIATED EMI

The subject power supply will meet FCC and CISPR 22 requirements under normal load conditions.

8. LABELLING

Label marking will be permanent, legible and complied with all agency requirements.

8.1. MODEL NUMBER LABEL

Labels will be affixed to the sides of the power supply showing the following:

- Manufacturer's name and logo.
- Model no., serial no., revision level, location of manufacturer.
- The total power output and the maximum load for each output.
- AC input rating.

8.2 DC OUTPUT IDENTIFICATION

Each output connector will be labeled.

9. RELIABILITY

9.1. MTBF

The power supply have a minimum predicted MTBF(MIL-HDBK-217) of 100,000 hours of continuous operation at 25°C, maximum-output load, and nominal AC input voltage.