

電氣規格書



ESD17002726-R1

FSP350-70PFL(SK)

Released Date:2021/01/15-05:12:37



全漢企業股份有限公司
FSP TECHNOLOGY INC.

台灣 桃園市建國東路 22 號

NO.22, Jianguo E. Rd., Taoyuan City, Taiwan, R.O.C.

TEL: +886-3-275-0888

SPECIFICATION

FSP350-70PFL(SK)

**Main Feature:
Active PFC Circuit
Full Range Input**

SEP 10,2019

REV: 1.4



全漢企業股份有限公司
FSP TECHNOLOGY INC.

MODEL: FSP350-70PFL(SK)

Revision History

Rev	Description	Date	Author
1.1	Update 4.5. Standby Power Consumption (5Vsb) & 5.3.VIBRATION	8.4.2017	Karl
1.2	Add 5.5 +5Vsb Mode (PS-ON/OFF) Acoustic Noise	8.25.2017	Karl
1.3	4.1.1. OUTPUT RATING & 4.1.2. LOAD CAPACITY SPECIFICATIONS <ul style="list-style-type: none"> ● CHANGE +5V MIN load from 0A to 0.2A ● CHANGE +12V1 MIN load from 0.1A to 0.05A ● CHANGE +12V2 MIN load from 0.1A to 0A 	4.3.2018	Winnie
1.4	ADD 5.6. Altitude	09.10.2019	Winnie



CONTENTS

1. GENERAL DESCRIPTION AND SCOPE	5
2. REFERENCE DOCUMENTS	5
2.1 EMI REGULATORY	5
3. PHYSICAL REQUIREMENTS.....	5
3.1 MECHANICAL SPECIFICATIONS.....	5
4. ELECTRICAL REQUIREMENTS	5
4.1 OUTPUT ELECTRICAL REQUIREMENTS	5
4.1.1. OUTPUT RATING	6
4.1.2. LOAD CAPACITY SPECIFICATIONS	6
4.1.3. HOLD-UP TIME (@FULL LOAD)	6
4.1.4.OUTPUT RISE TIME	7
4.1.5.OVER VOLTAGE PROTECTION.....	7
4.1.6.SHORT CIRCUIT PROTECTION	7
4.1.7.OVER CURRENT PROTECTION.....	7
4.1.8.POWER GOOD SIGNAL	8
4.2. OUTPUT TRANSIENT LOAD RESPONSE	8
4.2.1 Transient Load Requirement	9
4.3. INPUT ELECTRICAL SPECIFICATIONS	9
4.3.1. VOLTAGE RANGE	9
4.3.2. INPUT FREQUENCY	9
4.3.3. INRUSH CURRENT.....	10
4.3.4. INPUT LINE CURRENT.....	10
4.4. EFFICIENCY	10
4.5. Standby Power Consumption (5Vsb):	10

5. ENVIRONMENTAL REQUIREMENTS.....	11
5.1. TEMPERATURE RANGE	11
5.2. HUMIDITY	11
5.3. VIBRATION	11
5.4. SHOCK.....	11
5.5. +5Vsb Mode (PS-ON/OFF) Acoustic Noise	12
5.6. Altitude	12
6. SAFETY.....	12
6.1. LEAKAGE CURRENT.....	12
7. ELECTROMAGNETIC COMPATIBILITY	12
7.1. RADIATED EMI	12
8. LABELLING.....	12
8.1. MODEL NUMBER LABEL	12
8.2. DC OUTPUT IDENTIFICATION	13
9. RELIABILITY	13
9.1. MTBF	13

1. GENERAL DESCRIPTION AND SCOPE

This is the specification of Model FSP350-70PFL(SK); AC-line powered switching power supply with active PFC (Power Factor Correction) circuit, meet EN61000-3-2 and with Full Range Input features. Designed and manufactured by FSP GROUP.

The specification below is intended to describe as detailedly as possible the functions and performance of the subject power supply. Any comment or additional requirements to this specification from our customers will be highly appreciated and treated as a new target for us to approach.

2. REFERENCE DOCUMENTS

The subject power supply will meet the EMI requirements and obtain main safety approvals as following:

2.1 EMI REGULATORY

- FCC Part 15 Subpart J, Class 'B' 115 Vac operation.
- CISPR 22 Class 'B' 230 Vac operation.

3. PHYSICAL REQUIREMENTS

3.1 MECHANICAL SPECIFICATIONS

The mechanical drawing of the subject power supply, which indicate the form factor, location of the mounting holes, location, the length of the connectors, and other physical specifications of the subject power supply. Please refer to the attachment drawing.

4. ELECTRICAL REQUIREMENTS

4.1 OUTPUT ELECTRICAL REQUIREMENTS

The subject power supply will meet all electrical specifications below, over the full operation temperature range and dynamic load regulation.

4.1.1. OUTPUT RATING

Output	Nominal	Regulation	Ripple/Noise	Min	Max
1	+3.3V	±5%	50mV	0A	21.0 A
2	+5V	±5%	50mV	0.2A	16.0 A
3	+12V1	±5%	120mV	0.05A	17.0 A
4	+12V2	±5%	120mV	0A	17.0 A
5	-12V	±10%	120mV	0 A	0.5 A
6	+5VSB	±5%	50mV	0 A	3A

7	-5V	±10%	100mV	0 A	0.1A
---	-----	------	-------	-----	------

*-5V Option, +5vsb peak <= 10ms.

(1) The +3.3V and +5V total output shall not exceed 105watts.

(2)total output for this subject power supply is 350 watts.

(3)Ripple and noise measurements shall be made under all specified load conditions through a single pole low pass filter with 20MHz cutoff frequency. Outputs shall bypassed at the connector with a 0.1uF ceramic disk capacitor and a 10uF electrolytic capacitor to simulate system loading.

4.1.2. LOAD CAPACITY SPECIFICATIONS

The cross regulation defined as follows, the voltage regulation limits DC include DC Output ripple & noise.

	+12V1	+12V2	+5V	+3.3V	-12V	+5Vsb	-5V
1	11.14A	11.14A	7.38A	9.68A	0.33A	1.97A	0.1A
2	1A	1A	1A	21.0A	0.1A	3A	0.05A
3	17.0A	0.1A	3A	0.5A	0.5A	0.1A	0
4	4A	4A	16.0A	0.5A	0.05A	0.1A	0.1A
5	5.57A	5.57A	3.69A	4.84A	0.16A	0.98A	0
6	8.0A	9.0A	3A	0.5A	0.05A	0.1A	0.1A
7	0.5A	17.0A	3A	0.5A	0.5A	0.1A	0
8	0.5A	0.5A	3A	0.5A	0.05A	3A	0
9	2.23A	2.23A	1.48A	1.94A	0.07A	0.39A	0
10	0.05A	0A	0.2A	0A	0A	0A	0

4.1.3. HOLD-UP TIME (@FULL LOAD)

115V / 60Hz : 12mSec. Minimum.

230V / 50Hz : 12mSec. Minimum.

4.1.4.OUTPUT RISE TIME

(10% TO 90% OF FINAL OUTPUT VALUE, @FULL LOAD)

115V-rms or 230V-rms + 5Vdc : 20ms Maximum

4.1.5.OVER VOLTAGE PROTECTION

Voltage Source	Protection Point
+ 3.3 V _{dc}	3.7V-4.8V
+5V _{dc}	5.7V-7.0V
+12Vdc AND +12Vdc	13.3V – 16V

4.1.6.SHORT CIRCUIT PROTECTION

Output short circuit is defined to be a short circuit load of less than 0.1 ohm.

In the event of an output short circuit condition on +3.3V, +5V or +12V or output, the power supply will shutdown and latch off without damage to the power supply. The power supply shall return to normal operation after the short circuit has been removed and the power switch has been turned off for no more than 2 seconds.

In the event of an output short circuit condition on -12Vand -5V output, the power supply will not be damaged. The power supply shall return to normal operation as soon as the short circuit has been removed. and the power switch has been turned off for no more than 2 seconds.

4.1.7.OVER CURRENT PROTECTION

	O.C.P
+5V	25A~45A
+3.3V	25A~50A
+12V1,+12V2	20A~28A

4.1.8. POWER GOOD SIGNAL


The power good signal is a TTL compatible signal for the purpose of initiating an orderly start-up procedure under normal input operating conditions. This signal is asserted (low) until +5Vdc has reached 4.75 volts during power up. Characteristics:

TTL signal asserted (low state) : less than 0.5V while sinking 10mA.

TTL signal asserted (high state): greater than 4.75V while sourcing 500uA.

High state output impedance: less or equal to 1Kohm from output to common.

POWER GOOD @ 115/230V, FULL LOAD	100 –500mSec.
POWER FAIL @ 115/230V, FULL LOAD	1 mSec. minimum



4.2. OUTPUT TRANSIENT LOAD RESPONSE

+5V and +12V must be within specification for a step change in current as specified below. The outputs will be tested one section at a time with all other sections at maximum load. The test transition will be from IA to IB and IB to IA. The step current will have a nominal transition time of 0.5 amp per microsecond for +5V and 1.0 amp per microsecond for +12V.

+5Vdc:


IA:	16.0 amps
IB:	11.0 amps
Volts variation:	400 mV max (p-p)
Setting time:	10 ms max

+12V1dc, +12V2dc,

IA: 17.0 amps
 IB: 11.9 amps
 Volts variation: 550 mV max (p-p)
 Setting time: 10 ms max

+3.3Vdc:

IA: 21.0 amps
 IB: 14.7 amps
 Volts variation: 400 mV max (p-p)
 Setting time: 10 ms max



4.2.1 Transient Load Requirement

Output	Δ Step Load Size	Load Slew Rate	Capacitive Load
+3.3V	30% of max load	0.5 A/ μ s	6000 μ F
+5V	30% of max load	0.5 A/ μ s	6000 μ F
+12V1,+12V2	30% of max load	1.0 A/ μ s	4700 μ F

4.3. INPUT ELECTRICAL SPECIFICATIONS

4.3.1. VOLTAGE RANGE

PARAMETER		UNITS
V-in Range	90 - 264	V-rms

4.3.2. INPUT FREQUENCY

INPUT FREQUENCY	47-63Hz
-----------------	---------

4.3.3. INRUSH CURRENT

(Cold start – 25 deg. C)

115V	50A
230V	100A

(No damage)

4.3.4. INPUT LINE CURRENT

115V	7 Amps – rms maximum
230V	3.5Amps – rms maximum

4.4. EFFICIENCY

	Full load (100%)	Typical load (50%)	Light load (20%)
115VAC	82%	85%	82%

(loading shown in Amps)

Loading	+12V1	+12V2		+5V	+3.3V	-12V	+5Vsb
Full (100%)	11.14	11.14		7.38	9.68	0.33	1.97
Typical (50%)	5.57	5.57		3.69	4.84	0.16	0.98
Light (20%)	2.23	2.23		1.48	1.94	0.07	0.39

4.5. Standby Power Consumption (5Vsb):

Efficiency > 45% @ 5Vsb/45mA & 230Vac input (2013 Lot 6)

Efficiency > 55% @ 5Vsb/550mA & 230Vac input

Efficiency > 70% @ 5Vsb/1A & 230Vac input

Efficiency > 70% @ 5Vsb/3A & 230Vac input

4.6. PS_ON#

PS_ON# is an active-low, TTL-compatible signal that allows a motherboard to remotely control the power supply in conjunction with features such as soft on/off, Wake on LAN+, or wake-on-modem.

When PS_ON# is pulled to TTL low, the power supply should turn on the five main DC output rails: +12VDC, +5VDC, +3.3VDC, -5VDC, and -12VDC. When PS_ON# is pulled to TTL high or open-circuited, the DC output rails should not deliver current and should be held at zero potential with respect to ground. PS_ON# has no effect on the +5VSB output, which is always enabled whenever the AC power is present. Table 15 lists PS_ON# signal characteristics.

The power supply shall provide an internal pull-up to TTL high. The power supply shall also provide debounce circuitry on PS_ON# to prevent it from oscillating on/off at startup when activated by a mechanical switch. The DC output enable circuitry must be SELV-compliant.

Table 15. PS_ON# Signal Characteristics

	Min.	Max.
V _{IL} , Input Low Voltage	0.0V	0.8V
I _{IL} , Input Low Current (V _{in} = 0.4V)		-1.6mA
V _{IH} , Input High Voltage (I _{in} = -200 μ A)	2.0V	
V _{IH} OPEN circuit, I _{in} = 0		5.25V

5. ENVIRONMENTAL REQUIREMENTS

The power supply will be compliant with each item in this specification for the following Environmental conditions.

5.1. TEMPERATURE RANGE

Operating	350W	0 to +50 deg. C
Storage		-20 to +80 deg. C

5.2. HUMIDITY

Operating	5 –85% RH, Non-condensing
Storage	5 –95% RH, Non-condensing

5.3. VIBRATION

Random Vibration

0.01g²/ Hz at 5 Hz, sloping to 0.02g²/ Hz at 20 Hz, and maintaining 0.02g²/ Hz from 20Hz to 500Hz. The area under the PSD curve is 3.13gRMS.

The duration shall be 20 minutes per axis for all three axes on all samples.

5.4. SHOCK

The subject power supply will withstand the following imposed conditions without experiencing non-recoverable failure or deviation from specified output characteristics.

- Storage 40G, 9 mSec. half-sine wave pulse in both directions on three mutually perpendicular axes.
- Operating 10G, 11mSec. half-sine wave pulse in both directions on three mutually Perpendicular axes.

5.5. +5Vsb Mode (PS-ON/OFF) Acoustic Noise

(1) Position the microphone 30 centimeters above the x-y center of the EUT (2) Input voltage:110Vac/60Hz 220Vac/50Hz	The EUT < 25dB
----------------------------------------------------------------------------------------------------------------------------	----------------

5.6. Altitude

The power supply is applied for tropical climates and use at altitudes not exceeding 5000m above Sea level

6. SAFETY

6.1. LEAKAGE CURRENT

In addition to the UL,CSA safety requirements,the leakage current from AC to safety ground will not exceed 3.5mA-rms at 264Vac,63Hz

7. ELECTROMAGNETIC COMPATIBILITY

7.1. RADIATED EMI

The subject power supply will meet FCC and CISPR 22 requirements under normal load conditions.

8. LABELLING

Label marking will be permanent, legible and complied with all agency requirements.

8.1. MODEL NUMBER LABEL

Labels will be affixed to the sides of the power supply showing the following:

- Manufacturer's name and logo.
- Model no., serial no., revision level, location of manufacturer.
- The total power output and the maximum load for each output.
- AC input rating.

8.2. DC OUTPUT IDENTIFICATION

Each output connector will be labeled.

9. RELIABILITY

9.1. MTBF

The power supply have a minimum predicted MTBF(MIL-HDBK-217) of 100,000 hours of continuous operation at 25°C, maximum-output load, and nominal AC input voltage.