

HYDRO PT Series

550W / 650W / 750W



Introduction

FSP new PSU-Hydro PT series has 80 PLUS® Platinum certification, and features DC-DC module design. It offers good overall performance and thanks to its FDB fan and Japanese electrolytic capacitors its reliability should be excellent as well. It is the ultimate design for gaming enthusiast and overclocker ever!

Features



DC - DC Module Design

Provide supreme efficiency and voltage stability



100% Japan-made E-cap

Reliable power and prolonged life span



Ribbon Cable

Give any systems a neat and polished look (Black-sleeved cable for 24 pin)


- Unique product ID with changeable side stickers for DIY enthusiasts and gamers
- · Intelligent fan speed control circuit design
- · Advanced thermal layout design
- Complies with newest ATX12 v2.4 & EPS12 v2.92 standards
- · High efficiency ≥ 92%
- · Active PFC ≥ 99%
- · High Wattages with 80PLUS® Platinum Certification
- · Powerful +12V single rail design
- · Ribbon cables for the need of enthusiasts and gamers
- · Full Japan-made electrolytic capacitors
- · Support 6+2 pin PCI-Express Connectors
- · Quiet and Long-Lasting 135mm FDB Fan
- · Complete Protections: OCP, OVP, SCP, OPP, UVP, OTP
- · Global Safety Approved



HYDRO PT Series

550W / 650W / 750W

Product Overview



Special heat sink design for 12V switching circuit

A new heat dissipation design that conducts heat through a thermal pad on the bottom of the power supply, transforming the whole PSU chassis into a heat-sink and cooled by system airflow.


DC - DC Module Design


Both of +3.3V and +5V DC-DC module combined +12V SR circuit offers supreme efficiency, voltage stability, and high system compatibility especially in cross regulation (unbalance load) mode.





Changeable stylish side stickersFor DIY enthusiasts and gamers.


Performance
















HYDRO PT Series

550W / 650W / 750W

Rating

550W

AC Input	100-240Vac~ 8-4A 60-50Hz				
DC Output	+3.3V	+5V	+12V	-12V	+5Vsb
Max Output Current	20A	20A	45.84A	0.3A	2.5A
Max Combined Power	120W		550W	3.6W	12.5W
Total Power	550W				

650W

AC Input	100-240Vac~ 10-5A 50-60Hz				
DC Output	+3.3V	+5V	+12V	-12V	+5Vsb
Max Output Current	20A	20A	54.17A	0.3A	2.5A
Max Combined Power	120W		650W	3.6W	12.5W
Total Power	650W				

750W

AC Input	100-240Vac~ 10-5A 50-60Hz				
DC Output	+3.3V	+5V	+12V	-12V	+5Vsb
Max Output Current	20A	20A	62.5A	0.3A	2.5A
Max Combined Power	120W		750W	3.6W	12.5W
Total Power	750W				



FSP HYDRO PT Series

550W / 650W / 750W

Specifications

			The state of the s
Model	HPT550	HPT650	HPT750
Туре	ATX	ATX	ATX
PFC	Active PFC	Active PFC	Active PFC
Input Voltage	100-240Vac	100-240Vac	100-240Vac
Input Current	8-4A	10-5A	10-5A
Input Frequency	60/50Hz	60/50Hz	60/50Hz
Output Capacity	550W	650W	750W
Max. Output Power	550W	650W	750W
Fan Type	FDB Fan, 135mm	FDB Fan, 135mm	FDB Fan, 135mm
Efficiency	>92%	>92%	>92%
MTBF	100,000 Hrs	100,000 Hrs	100,000 Hrs
Protection	OCP, OVP, SCP,	OCP, OVP, SCP,	OCP, OVP, SCP,
	OPP, UVP, OTP	OPP, UVP, OTP	OPP, UVP, OTP
Weight	2.17kg	2.17kg	2.17kg
Dimension(L×W×H)	150 x 170 x 86 mm	150 x 170 x 86 mm	150 x 170 x 86 mm



FSP HYDRO PT Series

Connectors


	550W	650W	750W
	1	1	1
24 PIN			
	1	1	2
4+4 PIN			
	4	4	4
6+2 PIN			
	10	10	10
SATA			
	2	2	2
MOLEX			
	1	1	1
FLOPPY			


Cable Length


550W / 650W














Cable Length

750W









FSP HYDRO PT Series

Package Information

Model	HPT550	HPT650	HPT750	
EAN Code	4713224520402	4713224520419	4713224520426	
UPC Code	845685008947	845685008954	845685008961	
Shipping Dimensions (L×W×H)	298 × 218 × 99 mm			
Shipping Weights				
Master Pack Dimension (L×W×H)	539 × 250 × 323 mm			
Master Pack Quantity	5 retail boxes per master package			
Master Pack Weight				
Pallet Quantity	200 (5 retail boxes × 40 master boxes)			
Country of Origin	China			
Warranty	10 Years			
Additional Information				