

HDMI splitter, 2 ports

DSP-2PH4-03

PERFECT CONNECTION

- Sends a single HDMI signal to 2 displays
- Signal amplifier Improves signal quality
- Perfect for home theatres, classand conference rooms



Features

- Sends a single HDMI signal to 2 separate monitors, projectors or TV's
- The digital amplifier increases the transmission distance and also improves signal quality
- Supports 3D video

Packaging

Q'ty in crtn, pcs	45
Crtn volume, CUM	0.02738
Crtn weight, kgs	3.79
Individual package size LxWxH:	120x25x180 mm
Carton size LxWxH:	370x370x200 mm
Country of origin	CN
Barcode	8716309091442
Customs code	8543709099

Package contents

Splitter
USB power cable
User manual

Specifications

Ports: one input receptacle, 2 output HDMI output receptacles, 19 pin (A)
Interface standard: HDMI + HDCP v.1.4 (compatible with all HDMI versions)
Video formats: HDMI (480p/576i/576p/720p/1080i/1080P)
Maximal single-link range: 1920x1080 pixels, 1080p
Dual-link range: up to 3840x2160 at 30 Hz; color 30bit, 36bit

Supports Blue-Ray: 24/50/60fs/HD-DVD/xvYCC, audio DTS-HD/Dolby-trueHD/DTS/Dolby-AC3/DSD/HD(HBR)
Signal retiming support
Working distance: up to 20 m at AWG26 HDMI cable (at 4K resolution 8 m input max, up to 12 m output)

Certificates

