

HP LaserJet Enterprise M806 Printer series

Ideal for boosting productivity and efficiency across your business. Equip your teams to handle even the biggest print jobs quickly with HP's top-of-the line A3 printer – and print while on the go. Your investment is protected with easy upgrades.





Boost productivity: give workgroups the speed they need.

- Print big jobs fast at up to 56 ppm A4, and easily thanks to the extra-large input capacity of up to 4,600 pages3. Versatile paper handling options include a stapler/stacker/hole punch and booklet maker4.
- Simplify tasks with the right touch equip users to fly through tasks with the large 10.9 cm (4.3-inch) colour touchscreen
- Simplicity all around make it easy for all to print with one common drivers.
- Don't wait, just print right away and save energy with Instant-on Technology.



- Keep a close watch, even from afar monitor and control printers centrally with HP Web Jetadmin⁶.
- Apply fleet-wide policies to protect all your HP devices with the HP Imaging and Printing Center.
- Safeguard your printers right away with HP Instant-on Security8, and protect the sensitive data sent to your printer with the HP High-Performance Secure Hard Disk9.
- Prints with a positive ID authenticate users at the device to help secure print jobs.



- Mobile printing is simple with wireless direct printing, and enable touch-to-print convenience from a mobile
- Let employees print from mobile devices with built-in print capability or HP ePrint app and software 10.
- Printing made Apple® simple let users print wirelessly from an iPad®, iPhone®, or iPod touch®11.





connected to the same network as your 05 X or i05 device. Wireless performance is dependent on physical environment and distance from the access point. 05 X, iPad, iPhone, and iPod touch are trademarks of Apple® Inc., registered in the United States and other countries. AirPrint™ and the AirPrint logo are trademarks of Apple Inc.









¹ Wireless direct printing is standard in the HP LaserJet Enterprise M806x+ D7P69A, and may be added as an option to the HP LaserJet Enterprise M806dn and M806x+ CZ245A. Mobile device may require an app or driver. Wireless performance is dependent on physical environment and distance from the printer. For details, see hp.com/go/wirelessprinting.

² Touch-to-print capability is standard in the HP LaserJet Enterprise M806x+ D7P69A model, and may be added as an option to the HP LaserJet Enterprise M806dn and M806x+ CZ245A. Mobile device must support near field communications-enabled

Maximum paper capacity of 4,600 sheets is standard in the HP LaserJet Enterprise M806x+ D7P69A and M806x+ CZ245A and available in the HP LaserJet Enterprise M806dn model with the optional 3,500-sheet high-capacity input tray

⁴ 2 bin stapler/stacker, 2 bin stapler/stacker/hole punch and booklet maker are optional accessories. Please purchase separately The HP Universal Print Driver is free and available for download at hp.com/go/upd.

⁶ HP Web Jetadmin is free and available for download at hp.com/go/webjetadmin.

⁷ HP Imaging and Printing Security Center must be purchased separately.
⁸ HP Instant-on Security is part of HP Imaging and Printing Security Center, which must be purchased separately

⁹ HP High-Performance Secure Hard Drive is not available on the HP LaserJet Enterprise M806dn and can't be purchased separately.

10 Local printing requires mobile device and printer to be on the same network or have a direct wireless connection to printer. Wireless performance is dependent upon physical environment and distance from access point. Wireless operations are compatible with 2.4 GHz operations only. Remote printing requires an Internet connection to an HP Web-connected printer. App or software and HP ePrint account registration may also be required. Wireless broadband use requires separately purchased service contract for mobile devices. Check with service provider for coverage and availability in your area. See hp.com/go/mobileprinting for more details.

11 Supports OS X® Lion, OS X Mountain Lion, and the following devices running iOS 4.2 or later: iPad® (all models), iPhone® (3GS or later), and iPod touch® (third generation or later). Works with HP's AirPrint-enabled printers and requires the printer be

Product walkaround

- 1. Intuitive 10.9 cm (4.3 in) colortouchscreen control panel
- 2. 500-page output bin
- 3. Hardware integration pocket (HIP) for solution integration
- 4. 100-sheet face-up straight-through output bin
- 5. Easy front-door access to HP all-in-one toner cartridge
- 6. Built-in automatic two-sided printing
- 7. Two 500-sheet input trays support media up to A3 (11 x 17 in)
- 8. 3,500-sheet high-capacity input tray supports A4/letter media
- 9. Easy-access USB port to print files directly
- 10. 100-sheet multipurpose tray handles media up to 220 g/m2 (53 lb
- 11. Right-side doors provide access for clearing jams
- 12. 800 MHz processor, 1 GB standard memory
- 13. HP High-Performance Secure Hard Disk
- 14. Access port for optional Kensington-style lock
- 15. USB port (for connecting third-party devices)
- 16. Hi-Speed USB 2.0 printing port
- 17. HP Jetdirect Gigabit Ethernet print server
- 18. Foreign interface harness (for connecting third-party devices)





Series at a glance



HP LaserJet Enterprise M806dn Printer

- print speed A4 black: up to 56 ppm (duplex: up to 56
- print speed A3 black: up to 28 ppm
- up to 1200 x 1200 dpi (HP FastRes 1200)
- 1 GB RAM expandable to 1.5 GB
- 800 MHz processor
- 2 Hi-Speed USB 2.0 Host
- 1 Hi-Speed USB 2.0 Device
- 1 Gigabit Ethernet 10/100/1000T network
- 1 Foreign Interface
- 1 Hardware Integration Pocket
- 2 Internal USB Host
- Two 500-sheet input trays
- 100-sheet multi-purpose tray



HP LaserJet Enterprise M806x+ NFC/Wireless Direct HP LaserJet Enterprise M806x+ Printer

Printer

- as HP LaserJet Enterprise M806dn with:
- Near Field Communications (NFC) Module for wireless direct printing
- 320 GB HP High-Performance Secure Hard Disk
- 3,500 sheet High-capacity tray (tray 4: 1500 sheets A4 or letter only, tray 5: 2000 sheets A4 or letter



- as HP LaserJet Enterprise M806dn with:
- 320 GB HP High-Performance Secure Hard Disk
- 3,500 sheet High-capacity tray (tray 4: 1500 sheets A4 or letter only, tray 5: 2000 sheets A4 or letter

Recommended accessories



C3F79A HP LaserJet 3500-sheet High-capacity Input Tray

Support the productivity of growing work groups with this high-performance, robust input feeder and stand. The additional 3,500-sheet paper capacity allows users to spend more time focusing on business and less time reloading paper.



CZ285A HP LaserJet Booklet Maker/Finisher

The HP LaserJet Booklet Maker/Finisher provides the ability to create more complex finished documents in-house without the time and expense of going to an outside service.



CZ994A

HP LaserJet Stapler/Stacker

The HP LaserJet Stapler/Stacker provides automatic stapling and stacking for improved efficiency and increased output capacity.



CZ996A

HP LaserJet Stapler/Stacker with 2/4 hole punch

The HP LaserJet Stapler/Stacker with 2/4 hole punch provides automatic stapling and stacking for improved efficiency and increased output capacity.

Ordering information



HP LaserJet Enterprise M806dn Printer (CZ244A)

HP LaserJet M806dn Printer; HP Black LaserJet Toner Cartridge (~34.5K pages); Hardware Install Guide, Support flyer, Warranty card; Printer documentation and driver on CD-ROM; power cord



HP LaserJet Enterprise M806x+ NFC/Wireless Direct Printer (D7P69A)

HP LaserJet M806x+ Printer; HP Black LaserJet Toner Cartridge (~34.5K pages); Hardware Install Guide, Support flyer, Warranty card; Printer documentation and driver on CD-ROM; power cord; NFC module



HP LaserJet Enterprise M806x+ Printer (CZ245A)

HP LaserJet M806x+ Printer; HP Black LaserJet Toner Cartridge (~34.5K pages); Hardware Install Guide, Support flyer, Warranty card; Printer documentation and driver on CD-ROM; power cord

Accessories, Supplies and Support

Accessories

C3F79A	HP LaserJet 3500-sheet High-capacity Input Tray
CZ285A	HP LaserJet Booklet Maker/Finisher
CZ994A	HP LaserJet Stapler/Stacker
CZ996A	HP LaserJet Stapler/Stacker with 2/4 hole punch
C8091A	HP Staple Cartridge Refill
CC383A	HP 2-pack 2000-staple Cartridge

Connectivity

J8026A HP Jetdirect 2700w USB Wireless Print Server J8029A HP Jetdirect 2800w NFC/Wireless Direct Accessory

Supplies	
C2H57A	HP LaserJet 220V Maintenance/Fuser Kit
CF325X	HP 25X High Yield Black Original LaserJet Toner

Service & support

U8C50E - HP 3 year Next Business Day LaserJet Enterprise M806 Hardware Support

U8C53E - HP 3 year 4 hour 9x5 LaserJet Enterprise M806 Hardware Support

U8C51E - HP 4 year Next Business Day LaserJet Enterprise M806 Hardware Support

U8C52E - HP 5 year Next Business Day LaserJet Enterprise M806 Hardware Support

U8C71PE - HP 1 year Post Warranty Next Business Day Laser Jet Enterprise M806 Hardware Support

U8C72PE - HP 2 year Post Warranty Next Business Day LaserJet Enterprise M806 Hardware Support

U8C73PE - HP 1 year Post Warrant 4 hour 9x5 9x5 LaserJet Enterprise M806 Hardware Support

For a complete list of supplies, accessories and services, please refer to http://www.hp.com

For workflow, device management and other solutions, please visit the Global Solutions catalog: www.hp.com/go/gsc

Declared yield value in accordance with ISO/IEC 19752. Actual yields vary considerably based on images printed and other factors. For more information, visit hp.com/go/learnaboutsupplies. Actual yields vary considerably based on images printed and other factors. For more information, visit hp.com/go/learnaboutsupplies. Actual yields vary considerably based on images printed and other factors. For more information, visit hp.com/go/learnaboutsupplies. Actual yields vary considerably based on images printed and other factors. For more information, visit hp.com/go/learnaboutsupplies.

Technical specifications

Print technology	Laser						
Print speed	First page out black (A4): As fast as 8.5 sec						
	A4 black: Up to 56 ppm (duplex: up to 56 ipm); A3 black: Up to 28 ppm						
	Measured using ISO/IEC 24734, excludes first set of test documents. For more information see hp.com/go/printerclaims. Exact speed varies depending on the system configuration, software application,						
_	drive; and document complexity.						
Processor	800 MHz						
Memory	1 GB. Expandable to 1.5 GB through 1 GB industry-standard DIMM						
Hard disk	320 GB HP High-Performance Secure Hard Disk (only on D7P69A and CZ245A)						
Print	Quality HP FastRes 1200 (1200 dpi quality), 600 x 600 dpi with HP Resolution Enhancement technology						
	Resolution Black: Up to 1200 x 1200 dpi Printer languages HP PCL 6, HP PCL 5e, HP Postscript Level 3 emulation, native PDF printing (v 1.4)						
	Printer languages HPPCL 5, HPPCL 5e, HPPCL 5e, HPPCL 5e armuation, native PUP printing (v. 1.4) Typefaces/finits 105 internal True Tipye forits calable in HPPCL, 3e internal scalable forits in HPP obstscript Level 3 emulation (Euro symbol built-in); 1 internal Unicode Fonts (Andale						
	Mono WorldType): 2 Internal Windows Vista 8 Fonts (Calibri, Cambria): additional font solutions available via third-party flash memory cards; HP LaserJet Fonts and IP						
	Emulation available at hp.com/go/laserjetfonts						
	Duty cycle (monthly, A4) Up to 300,000 pages						
	Recommended monthly page volu		. 3.0				
	Print margins (mm)	Top: 2.0 mm. Left: 2.0 mm. Right: 2.0 mm. Bottom		<u></u>			
Media handling	Input:	Capacity	Weight 60 to 220 q/m²	Size			
	Tray 1	sheets: 100; envelopes: 100; labels: 100	60 to 220 g/III-	A3, A4, A5, RA3, B4, B5, post cards (JIS double); envelopes (DL, C5, B5); 98 x 191 to 312 x 470 mm			
	Tray 2, 3	sheets: 500; labels: small quantities	60 to 199 g/m ²	A3; A4; A5; B4; B5; 148 x 210 to 297 x 431.8 mm			
	Tray 4, 5	CZ244A: optional High-capacity Input tray, tray 4:	60 to 199 g/m²	CZ244A: Optional High-capacity Input, Tray 4/5: A4,			
		sheets: 1500 (A4 only), tray 5: sheets: 2000 (A4	3	210 to 297 mm; D7P69A: High-capacity Input, Tray			
		only); D7P69A: High-capacity Input tray, tray 4:		4/5: A4, 210 to 297 mm; CZ245A: as D7P69A			
		sheets: 1500 (A4 only), tray 5: sheets: 2000 (A4		product;			
		only); CZ245A: as D7P69A product;					
	Output:	Sheets: Up to 600 sheets. Transparencies: Up to 100	sheets				
	Duplex printing: Automatic (standard)						
Media types	Paper (bond, colour, letterhead, pl	ain, preprinted, prepunched, recycled, rough), labels, car	dstock, transparencies				
Interface and connectivity	Standard: CZ244A: 2 Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Foreign Interface; 1 Hardware Integration Pocket; 2 Internal USB Host; D7P69A: 2						
	Hi-Speed USB 2.0 Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 NFC/Wireless (accessory included); 1 Foreign Interface; 2 Internal USB Host; CZ245A: 2 Hi-Speed USB 2.0						
	Host; 1 Hi-Speed USB 2.0 Device; 1 Gigabit Ethernet 10/100/1000T network; 1 Foreign Interface; 1 Hardware Integration Pocket; 2 Internal USB Host;						
Operating systems compatibility				, Windows Server 2012 (64-bit), Windows Server 2008 (32-bit/64-bit),			
				.8 Mountain Lion. For the latest operating system support see: AirPrint™			
				re Driver (hp.com/go/eprintsoftware); Linux (hplip.net); Novell			
	(novell.com/iprint); SAP device types (hp.com/go/sap/drivers); SAP Print (hp.com/go/sap/print); UNIX (hp.com/go/unix); UNIX JetDirect (hp.com/go/jetdirectunix_software). LaserJet driver information and support available at: hp.com/support/lijM806; hp.com/go/hpsc; hp.com/support						
Notwork operating systems compatibility			in Lion: Windows 2000: MDE iV: Citriv®	MetaFrame Server; Novell® 5.1 or higher; RED HAT Linux 7.x or higher;			
Network operating systems compatibility							
	Solaris® 2.5 or higher (SPARC® systems only); SUSE Linux 8.x or higher; Windows 2003 SP2+ 64-bit; Windows Server 2003 SP2+; Windows Terminal Services; Windows Vista (32-bit and 64-bit); Windows Vista Ready; Windows XP SP3+ 64-bit; Windows XP SP3+ Home; Windows XP SP3+ Home; Windows XP SP3+ Professional; Windows XP SP3+ Professional and Windows Vista; Windows 7 SP1 or greater						
	(32-bit and 64-bit), Windows 8 (32-bit and 64-bit), Windows Server 2008 (32-bit and 64-bit), Windows Server 2012 (64-bit), Win						
		e, Windows XP Professional and Windows Vista)		,			
	Windows 8, Windows 7 SP1+, Windows Vista, Windows Server 2003 (SP1+), Windows Server 2008, Windows Server 2008 R2 (64 bit), Windows Server 2012 (64-bit), Windows XP (SP2+); CD-ROM or DVD						
Minimum system requirements	Windows 8, Windows 7 SP1+, Win	drive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0), or network connection; 200 MB available hard disk space; Operating system compatible hardware system requirements see					
Minimum system requirements	drive, or Internet connection; Dedi	cated universal serial bus (USB 1.1 or 2.0), or network of		pace; Operating system compatible hardware system requirements see			
Minimum system requirements	drive, or Internet connection; Dedi- microsoft.com. Mac OS X v10.6.8,	cated universal serial bus (USB 1.1 or 2.0), or network o OS X 10.7.5 Lion, OS X 10.8 Mountain Lion; 1 GB of avai	lable hard-disk space; CD-ROM or DVD d	pace; Operating system compatible hardware system requirements see			
	drive, or Internet connection; Dedi microsoft.com. Mac OS X v10.6.8, or network connection (Operating	cated universal serial bus (USB 1.1 or 2.0), or network o OS X 10.7.5 Lion, OS X 10.8 Mountain Lion; 1 GB of avai system compatible hardware system requirements see	lable hard-disk space; CD-ROM or DVD d				
	drive, or Internet connection; Dedi microsoft.com. Mac OS X v10.6.8, or network connection (Operating	cated universal serial bus (USB 1.1 or 2.0), or network o OS X 10.7.5 Lion, OS X 10.8 Mountain Lion; 1 GB of avai	lable hard-disk space; CD-ROM or DVD d	pace; Operating system compatible hardware system requirements see			
Standard software	drive, or Internet connection, Dedi microsoft.com. Mac OS X v10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M	cated universal serial bus (USB 1.1 or 2.0), or network or OS X 10.7.5 Lion, OS X 10.8 Mountain Lion; 1 GB of avai system compatible hardware system requirements see lac SW Link to Web (Mac Installer), Windows Installer	lable hard-disk space; CD-ROM or DVD d apple.com)	pace; Operating system compatible hardware system requirements see			
Standard software Control panel	drive, or Internet connection, Dedi microsoft.com. Mac OS X v10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M	cated universal serial bus (USB 1.1 or 2.0), or network o OS X 10.7.5 Lion, OS X 10.8 Mountain Lion; 1 Eb of avai system compatible hardware system requirements see ac SW Link to Web (Mac Installer), Windows Installer touchscreen; rotating (adjustable angle) display; illumina	lable hard-disk space; CD-ROM or DVD d apple.com)	oace; Operating system compatible hardware system requirements see rive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0)			
Standard software Control panel Power	drive, or Internet connection; Dedi microsoft.com. Mac OS X v10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M 10.9 cm colour LCD with resistive t Requirements: Input Voltage: 220	cated universal serial bus (USB 1.1 or 2.0), or network of 05 X 10.7.5 Lion, 05 X 10.8 Mountain Lion; 1 GB of avai system compatible hardware system requirements see lac SW Link to Web (Mac Installer), Windows Installer touchscreen; rotating (adjustable angle) display; illumina to 240 VAC, 50/60 Hz, 5.5 A	lable hard-disk space; CD-ROM or DVD d apple.com) sted capacitive Home button (for quick re	oace; Operating system compatible hardware system requirements see rive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0)			
Standard software Control panel Power	drive, or Internet connection; Dedi microsoft.com. Mac 0 S X v10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M 10.9 cm colour LCD with resistive I Requirements: Input Voltage: 220 Out of package: CZ244A: 1095 x	cated universal serial bus (USB 1.1 or 2.0), or network of 0 S x 10.7.5 Lion, 0S x 10.8 Mountain Lion; 1 GB of avai system compatible hardware system requirements see lac SW Link to Web (Mac Installer), Windows Installer touchscreen; rotating (adjustable angle) display; illumina to 240 VAC, 50/60 Hz, 5.5 A 648 x 635 mm; D7P69A: 1095 x 715 x 1040 mm; CZ2	lable hard-disk space; CD-ROM or DVD d apple.com) ated capacitive Home button (for quick ro 45A: 1095 x 715 x 1040 mm;	oace; Operating system compatible hardware system requirements see rive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0)			
Standard software Control panel Power Dimensions (w x d x h)	drive, or Internet connection; Dedi microsoft.com. Mac OS X v10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M 10.9 cm colour LCD with resistive I Requirements: Input Voltage: 220 Out of package: CZ244A: 1095 x Packaged: CZ244A: 856 x 760 x 5	cated universal serial bus (USB 1.1 or 2.0), or network of OS X 10.7.5 Lion, OS X 10.8 Mountain Lion; 1 GB of avai system compatible hardware system requirements see lac SW Link to Web (Mac Installer), Windows Installer touchscreen; rotating (adjustable angle) display; illumina to 240 VAC, 50/60 Hz, 5.5 A 648 x 635 mm; D7P69A : 1095 x 715 x 1040 mm; CZ2 978 mm; D7P69A : 856 x 790 x 1368 mm; CZ245A : 85	lable hard-disk space; CD-ROM or DVD d apple.com) ated capacitive Home button (for quick ro 45A: 1095 x 715 x 1040 mm;	oace; Operating system compatible hardware system requirements see rive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0)			
Standard software Control panel Power Dimensions (w x d x h)	drive, or Internet connection; Dedi microsoft.com. Mac OS X v10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M 10.9 cm colour LCD with resistive I Requirements: Input Voltage: 20 Out of package: CZ244A: 1095 x Packaged: CZ244A: 856 x760 x Out of package: CZ244A: 76.1 kg	cated universal serial bus (USB 1.1 or 2.0), or network of 0S X 10.7.5 Lion, 0S X 10.8 Mountain Lion; 1 GB of avai system compatible hardware system requirements see lac SW Link to Web (Mac Installer), Windows Installer touchscreen; rotating (adjustable angle) display; illumina to 240 VAC, 50/60 Hz, 5.5 A 648 x 635 mm; D7P69A: 1095 x 715 x 1040 mm; CZ2 778 mm; D7P69A: 856 x 790 x 1368 mm; CZ245A: 8!; D7P69A: 108.4 kg; CZ245A: 108.4 kg;	lable hard-disk space; CD-ROM or DVD d apple.com) ated capacitive Home button (for quick ro 45A: 1095 x 715 x 1040 mm;	oace; Operating system compatible hardware system requirements see rive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0)			
Standard software Control panel Power Dimensions (w x d x h) Weight	drive, or Internet connection; Dedi microsoft.com. Mac OS X v10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M 10.9 cm colour LCD with resistive I Requirements: Input Voltage: 220 Out of package: CZ244A: 1095 x Packaged: CZ244A: 856 x 760 x Out of package: CZ244A: 76.1 kg Packaged: CZ244A: 88.84 kg; D7	cated universal serial bus (USB 1.1 or 2.0), or network of 05 X 10.7.5 Lion, 05 X 10.8 Mountain Lion; 1 GB of avail system compatible hardware system requirements see lac SW Link to Web (Mac Installer), Windows Installer touchscreen; rotating (adjustable angle) display; illumina to 240 VAC, 50/60 Hz, 5.5 A 648 x 635 mm; D7P69A : 1095 x 715 x 1040 mm; CZ2 978 mm; D7P69A : 856 x 790 x 1368 mm; CZ245A : 8! D7P69A : 108.4 kg; CZ245A : 108.4 kg; P69A : 130.87 kg; CZ245A : 130.67 kg;	lable hard-disk space; CD-ROM or DVD d apple.com) ated capacitive Home button (for quick ro 45A: 1095 x 715 x 1040 mm;	oace; Operating system compatible hardware system requirements see rive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0)			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management	drive, or Internet connection; Dedi microsoft.com. Mac OS X v10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M 10.9 cm colour LCD with resistive I Requirements: Input Voltage: 220 Out of package: CZ244A: 1095 x Packaged: CZ244A: 856 x 760 x Out of package: CZ244A: 76.1 kg Packaged: CZ244A: 88.84 kg; D7 HP Web Jetadmin; HP Utility (Mac)	cated universal serial bus (USB 1.1 or 2.0), or network of 05 X 10.7.5 Lion, 05 X 10.8 Mountain Lion; 1 GB of avail system compatible hardware system requirements see lac SW Link to Web (Mac Installer), Windows Installer touchscreen; rotating (adjustable angle) display; illumina to 240 VAC, 50/60 Hz, 5.5 A 648 x 635 mm; D7P69A: 1095 x 715 x 1040 mm; CZZ 978 mm; D7P69A: 856 x 790 x 1368 mm; CZZ45A: 85 ; D7P69A: 108.4 kg; CZZ45A: 108.4 kg; P69A: 130.87 kg; CZZ45A: 130.67 kg;	lable hard-disk space; CD-ROM or DVD d apple.com) sted capacitive Home button (for quick re 45A: 1095 x 715 x 1040 mm; 36 x 790 x 1368 mm;	Dace; Operating system compatible hardware system requirements see frive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0). eturn to the Home menu); Easy Access USB; Hardware Integration Pocket			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management	drive, or Internet connection; Dedi microsoft.com. Mac OS X v10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M 10.9 cm colour LCD with resistive I Requirements: Input Voltage: 220 Out of package: CZ244A: 1095 x Packaged: CZ244A: 856 x 760 x Out of package: CZ244A: 76.1 kg Packaged: CZ244A: 88.8 kg; D7 HP Web Jetadmin; HP Utility (Mac) CZ244A: Identity Management: K	cated universal serial bus (USB 1.1 or 2.0), or network of OS X 10.7.5 Lion, OS X 10.8 Mountain Lion; 1 GB of avai system compatible hardware system requirements see lac SW Link to Web (Mac Installer), Windows Installer touchscreen; rotating (adjustable angle) display; illumina to 240 VAC, 50/60 Hz, 5.5 A 648 x 635 mm; D7P69A : 1095 x 715 x 1040 mm; CZ2 978 mm; D7P69A : 856 x 790 x 1368 mm; CZ245A : 8: D7P69A : 130.87 kg; CZ245A : 130.67 kg; erberos authentication, LDAP authentication, 1000 uses	lable hard-disk space; CD-ROM or DVD d apple.com) sted capacitive Home button (for quick re 145A: 1095 x 715 x 1040 mm; 56 x 790 x 1368 mm; PIN codes, optional HP Access Control a	pace; Operating system compatible hardware system requirements see rive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0 eturn to the Home menu); Easy Access USB; Hardware Integration Pocket			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management	drive, or Internet connection; Dedi microsoft.com. Mac OS X v10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M 10.9 cm colour LCD with resistive I Requirements: Input Voltage: 220 Out of package: CZ244A: 856 x760 x Packaged: CZ244A: 856 x760 x Out of package: CZ244A: 88.84 kg; D7 HP Web Jetadmin; HP Utility (Mac) CZ244A: Identity Management: K Network: IPSec/firewall with Certif	cated universal serial bus (USB 1.1 or 2.0), or network of 0S X 10.7.5 Lion, 0S X 10.8 Mountain Lion; 1 GB of avai system compatible hardware system requirements see lac SW Link to Web (Mac Installer), Windows Installer touchscreen; rotating (adjustable angle) display; illumina to 240 VAC, 50/60 Hz, 5.5 A 648 x 635 mm; D7P69A : 1095 x 715 x 1040 mm; CZ2 978 mm; D7P69A : 856 x 790 x 1368 mm; CZ245A : 8!; D7P69A : 108.4 kg; CZ245A : 108.4 kg; P69A : 130.87 kg; CZ245A : 130.67 kg; erberos authentication, LDAP authentication, 1000 user icate, Pre-Shared Key, and Kerberos authentication, Sup	lable hard-disk space; CD-ROM or DVD d apple.com) sted capacitive Home button (for quick re 45A: 1095 x 715 x 1040 mm; 56 x 790 x 1368 mm; PIN codes, optional HP Access Control & sports WJA-10 IPsec configuration Plug-	pace; Operating system compatible hardware system requirements see rive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0 eturn to the Home menu); Easy Access USB; Hardware Integration Pocket and 3rd party advanced authentication solutions (e.g., badge readers); in, 802.1X authentication (EAP-PEAR EAP-TLS), SNMPv3, HTTPS,			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management	drive, or Internet connection; Dedi microsoft.com. Mac OS X v10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M 10.9 cm colour LCD with resistive I Requirements: Input Voltage: 220 Out of package: CZ244A: 1095 x Packaged: CZ244A: 760 x Out of package: CZ244A: 76.1 kg Packaged: CZ244A: 88.84 kg; D7 HP Web Jetadmin; HP Utility (Mac) CZ244A: Identity Management: K Network: IPSec/firewall with Certificates, Access Control List; Da	cated universal serial bus (USB 1.1 or 2.0), or network of 05 X 10.7.5 Lion, 05 X 10.8 Mountain Lion; 1 GB of avail system compatible hardware system requirements see lac SW Link to Web (Mac Installer), Windows Installer touchscreen; rotating (adjustable angle) display; illumina to 240 VAC, 50/60 Hz, 5.5 A 648 x 635 mm; D7P69A: 1095 x 715 x 1040 mm; CZ2 978 mm; D7P69A: 856 x 790 x 1368 mm; CZ245A: 8! D7P69A: 130.87 kg; CZ245A: 130.67 kg; erberos authentication, LDAP authentication, 1000 usei ficate, Pre-Shared Key, and Kerberos authentication, Sug- lats: Storage Encryption, SSL/TLS, Encrypted Credentials Storage Encryption, SSL/TLS, Encrypted Credentials	lable hard-disk space; CD-ROM or DVD d apple.com) sted capacitive Home button (for quick re- sted capacitive Home button (for quick re- sted capacitive Home button (for quick re- sted capacitive Home State Re- sted capacitive Home State Re- prorts WJA-10 IPsec configuration Plug- poports WJA-10 IPsec configuration Plug- ; Device: Security lock slot, USB port disk	pace; Operating system compatible hardware system requirements see rive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0 eturn to the Home menu); Easy Access USB; Hardware Integration Pocket and 3rd party advanced authentication solutions (e.g., badge readers); in, 802.1X authentication (EAP-PEAP, EAP-TLS), SNMPv3, HTTPS, ablement, Hardware Integration Pocket for security solutions; Security			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management	drive, or Internet connection; Dedi microsoft.com. Mac OS X v10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M 10.9 cm colour LCD with resistive I Requirements: Input Voltage: 220 Out of package: CZ244A: 1095 x Packaged: CZ244A: 856 x 760 x 9 Packaged: CZ244A: 856 x 760 x 9 Packaged: CZ244A: 84 (p. DT HP Web Jetadmin; HP Utility (Mac) CZ244A: Identity Management: K Network: IPSec/firewall with Certificates, Access Control List; Dic Management: Compatible with HP	cated universal serial bus (USB 1.1 or 2.0), or network of OS X 10.7.5 Lion, OS X 10.8 Mountain Lion; 1 GB of avai system compatible hardware system requirements see lac SW Link to Web (Mac Installer), Windows Installer touchscreen; rotating (adjustable angle) display; illumina to 240 VAC, 50/60 Hz, 5.5 A 648 x 635 mm; D7P69A : 1095 x 715 x 1040 mm; CZ2 978 mm; D7P69A : 856 x 790 x 1368 mm; CZ245A : 8: D7P69A : 108.4 kg; CZ245A : 108.4 kg; P69A : 130.87 kg; CZ245A : 130.67 kg; erberos authentication, LDAP authentication, 1000 usei icate, Pre-Shared Key, and Kerberos authentication, Sug ata: Storage Encryption, SSL/TLS, Encrypted Credentials Imaging & Printing Security Center; D7P69A : Identity I	lable hard-disk space; CD-ROM or DVD dapple.com) sted capacitive Home button (for quick residual capacitive Home button) 145A: 1095 x 715 x 1040 mm; 165 x 790 x 1368 mm; PIN codes, optional HP Access Control apports WIA-10 IPsec configuration Pluggions (in the property lock) sol, USB port disk danagement: Kerberos authentication, Liberoper Suthernication, Liberoper Suthernica	pace; Operating system compatible hardware system requirements see rive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0 eturn to the Home menu); Easy Access USB; Hardware Integration Pocket and 3rd party advanced authentication solutions (e.g., badge readers); in, 802.1X authentication (EAP-PEAP EAP-TLS), SNMPV3, HTTPS, ablement, Hardware Integration Pocket for security solutions; Security .DAP authentication, 1000 user PIN codes, optional HP Access Control and			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management	drive, or Internet connection; Dedi microsoft.com. Mac OS X v10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M 10.9 cm colour LCD with resistive Requirements: Input Voltage: 220 Out of package: CZ244A: 1095 x Packaged: CZ244A: 856 x 760 x 9 Packaged: CZ244A: 88.84 kg: DT HP Web Jetadmir, HP Utility (Mac) CZ244A: Identity Management: K Network: IPSec/firewall with Certificates, Access Control List; Dx Management: Compatible with HP 3rd party advanced authentication	cated universal serial bus (USB 1.1 or 2.0), or network or OS x 10.7.5 Lion, OS X 10.8 Mountain Lion; 1 GB of avail system compatible hardware system requirements see lac SW Link to Web (Mac Installer), Windows Installer touchscreen; rotating (adjustable angle) display; illumina to 240 VAC, 50/66 Hz, 5.5 A GB at 36.8 A GB mm; D7P69A: 1095 x 715 x 1040 mm; CZ2 478 mm; D7P69A: 856 x 790 x 1368 mm; CZ245A: 81; D7P69A: 108.4 kg; CZ245A: 130.67 kg; erberos authentication, LDAP authentication, 1000 usel icate, Pre-Shared Key, and Kerberos authentication, Sup ata: Storage Encryption, SSL/TLS, Encrypted Credentials (Imaging & Printing Security Center; D7P69A: Identity 1 solutions (e.g., badge readers); Network: IPSec/firewall systems (e.g., e.g., e.	lable hard-disk space; CD-ROM or DVD d apple.com) sted capacitive Home button (for quick re 45A: 1095 x 715 x 1040 mm; 56 x 790 x 1368 mm; PIN codes, optional HP Access Control a ports WJA-10 IPsec configuration Plug- ; Device: Security lock slot, USB port disk danagement: Kerberos authentication, L i. with Certificate, Pre-Shared Key, and Ke	pace; Operating system compatible hardware system requirements see rive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0) eturn to the Home menu); Easy Access USB; Hardware Integration Pocket and 3rd party advanced authentication solutions (e.g., badge readers); in, 802.1X authentication (EAP-PEAP, EAP-TLS), SNMPv3, HTTPS, ablement, Hardware Integration Pocket for security solutions; Security DAP authentication, 1000 user PIN codes, optional HP Access Control and arberos authentication, Supports WJA-10 IPsec configuration Plug-in,			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management	drive, or Internet connection; Dedi microsoft.com. Mac OS X v10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M 10.9 cm colour LCD with resistive to Requirements: Input Voltage: 220 Out of package: CZ244A: 1095 x Packaged: CZ244A: 760 x 9 Packaged: CZ244A: 856 x 760 x 9 Packaged: CZ244A: 88.84 kg; D7 HP Web Jetadmin; HP Utility (Mac) CZ244A: Identity Management: Kompatible with HP 3rd party advanced authentication 802.1X authentication (EAP-PEAP.	cated universal serial bus (USB 1.1 or 2.0), or network of 05 X 10.7.5 Lion, 05 X 10.8 Mountain Lion; 1 GB of avail system compatible hardware system requirements see lac SW Link to Web (Mac Installer), Windows Installer touchscreen; rotating (adjustable angle) display; illumina to 240 VAC, 50/60 Hz, 5.5 A 648 x 635 mm; D7P69A: 1095 x 715 x 1040 mm; CZ2 978 mm; D7P69A: 856 x 790 x 1368 mm; CZ245A: 8: D7P69A: 130.87 kg; CZ245A: 108.4 kg; P69A: 130.87 kg; CZ245A: 108.6 kg; erberos authentication, LDAP authentication, 1000 uses iicate, Pre-Shared Key, and Kerberos authentication, Sug- ata: Storage Encryption, SSL/TLS, Encrypted Credentials Imaging & Printing Security Center; D7P69A: Identity In solutions (e.g., badge readers); Network: IPSec/firewall LEAP-TLS), SNMPv3, HTTPS, Certificates, Access Control	lable hard-disk space; CD-ROM or DVD d apple.com) sted capacitive Home button (for quick re- sted capacitive Home button (for quick re- sted capacitive Home button (for quick re- sted capacitive Home; 1990 x 1368 mm; PIN codes, optional HP Access Control a- sports WJA-10 IPsec configuration Plug- poports WJA-10 IPsec configuration Plug- ; Device: Security lock slot, USB port disk danagement: Kerberos authentication, I, uith Certificate, Pre-Shared Key, and Ke List; Data: Storage Encryption, Secure E	pace; Operating system compatible hardware system requirements see frive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0 eturn to the Home menu); Easy Access USB; Hardware Integration Pocket and 3rd party advanced authentication solutions (e.g., badge readers); in, 802.1X authentication (EAP-PEAR EAP-TLS), SNMPv3, HTTPS, ablement, Hardware Integration Pocket for security solutions; Security .DAP authentication, 1000 user PIN codes, optional HP Access Control and arberos authentication, Supports WJA-10 IPsec configuration Plug-in, rase, SSL/TLS, Encrypted Credentials; Device: Security lock slot, USB port			
Standard software Control panet Power Dimensions (w x d x h) Weight Printer management Security management	drive, or Internet connection; Dedi microsoft.com. Mac OS X v10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M 10.9 cm colour LCD with resistive IR equirements: Input Voltage: 220 Out of package: CZ244A: 1095 x Packaged: CZ244A: 856 x 760 x 90 Out of package: CZ244A: 856 x 760 x 90 Colour Care Annual C	cated universal serial bus (USB 1.1 or 2.0), or network of SX 10.7.5 Lion, 05 X 10.8 Mountain Lion; 1 GB of avai system compatible hardware system requirements see lac SW Link to Web (Mac Installer), Windows Installer touchscreen; rotating (adjustable angle) display; illumina to 240 VAC, 50/60 Hz, 5.5 A 688 × 635 mm; D7P69A: 1095 × 715 × 1040 mm; CZ2 978 mm; D7P69A: 856 × 790 × 1368 mm; CZ245A: 8: D7P69A: 108.4 kg; CZ245A: 130.67 kg; P69A: 130.87 kg; CZ245A: 130.67 kg; erberos authentication, LDAP authentication, 1000 usericate, Pre-Shared Key, and Kerberos authentication, Sugata: Storage Encryption, SSL/TLS, Encrypted Credentisty Insaging & Printing Security Center; D7P69A: Identity in solutions (e.g., badge readers): Network: IPSec/firewall EAP-TLS), SNMPV3, HTTPS, Certificates, Access Control n Pocket for security solutions; Security Management: C	lable hard-disk space; CD-ROM or DVD diapple.com) ated capacitive Home button (for quick related capacitive Home button (for quick related capacitive Home button (for quick related capacitive Home) 45A: 1095 x 715 x 1040 mm; 56 x 790 x 1368 mm; PIN codes, optional HP Access Control approach to the configuration Pluggore Configuration Pluggore Configuration Pluggore Service: Security lock slot, USB port disadnagement: Kerberos authentication, Liwith Certificate, Pre-Shared Key, and Ke List; Data: Storage Encryption, Secure Ecompatible with HP Imaging & Printing Sec	pace; Operating system compatible hardware system requirements see rive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0) eturn to the Home menu); Easy Access USB; Hardware Integration Pocket and 3rd party advanced authentication solutions (e.g., badge readers); in, 802.1X authentication (EAP-PEAP, EAP-TLS), SNMPv3, HTTPS, ablement, Hardware Integration Pocket for security solutions; Security DAP authentication, 1000 user PIN codes, optional HP Access Control and erberos authentication, Supports WIA-10 IPsec configuration Plug-in, rase, SSL/TLS, Encrypted Credentials; Device: Security lock slot, USB port security Center; CZ245A: as D7P69A product;			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management	drive, or Internet connection; Dedi microsoft.com. Mac OS X v10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M 10.9 cm colour LCD with resistive IR equirements: Input Voltage: 220 Out of package: CZ244A: 1095 x Packaged: CZ244A: 856 x 760 x 90 Out of package: CZ244A: 856 x 760 x 90 Colour Care Annual C	cated universal serial bus (USB 1.1 or 2.0), or network of OS X 10.7.5 Lion, OS X 10.8 Mountain Lion; 1 GB of avail system compatible hardware system requirements see lac SW Link to Web (Mac Installer), Windows Installer touchscreen; rotating (adjustable angle) display; illumina to 240 VAC, 50/60 Hz, 5.5 A 648 × 635 mm; D7P69A: 1095 × 715 × 1040 mm; CZ245A: 85; D7P69A: 108.4 kg; CZ245A: 108.4 kg; P69A: 108.4 kg; CZ245A: 130.67	lable hard-disk space; CD-ROM or DVD diapple.com) ated capacitive Home button (for quick related capacitive Home button (for quick related capacitive Home button (for quick related capacitive Home) 45A: 1095 x 715 x 1040 mm; 56 x 790 x 1368 mm; PIN codes, optional HP Access Control approach to the configuration Pluggore Configuration Pluggore Configuration Pluggore Service: Security lock slot, USB port disadnagement: Kerberos authentication, Liwith Certificate, Pre-Shared Key, and Ke List; Data: Storage Encryption, Secure Ecompatible with HP Imaging & Printing Sec	pace; Operating system compatible hardware system requirements see rive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0 et universal serial bus (USB), Hardware Integration Pocket for security solutions; Security (DAP authentication, 1000 user PIN codes, optional HP Access Control and erberos authentication, Supports WJA-10 IPsec configuration Plug-in, rase, SSL/TLS, Encrypted Credentials; Device: Security lock slot, USB port security Center; CZ245A: as D7P69A product;			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management	drive, or Internet connection; Dedi microsoft.com. Mac OS X v10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M 10.9 cm colour LCD with resistive Requirements: Input Voltage: 220 Out of package: CZ244A: 1095 x Packaged: CZ244A: 88.84 kg; D7 HP Web Jetadmin; HP Utility (Mac) CZ24A: Identity Management: K Network: IPSec/firewall with Certificates, Access Control List; D. Management: Compatible with HP 3rd party advanced authentication 802.1X authentication (EAP-PEAP, disablement, Hardware Integration Operating temperature: 10 to 32.5	cated universal serial bus (USB 1.1 or 2.0), or network or OS X 10.7.5 Lion, OS X 10.8 Mountain Lion; 1 GB of avair system compatible hardware system requirements see lac SW Link to Web (Mac Installer), Windows Installer touchscreen; rotating (adjustable angle) display; illumina to 240 VAC, 50/60 Hz, 5.5 A 648 x 635 mm; D7P69A: 1095 x 715 x 1040 mm; CZ2 978 mm; D7P69A: 856 x 790 x 1368 mm; CZ245A: 85; D7P69A: 108.4 kg; CZ245A: 108.4 kg; P69A: 130.87 kg; CZ245A: 130.67 kg; erberos authentication, LDAP authentication, 1000 user icate, Pre-Shared Key, and Kerberos authentication, Supata: Storage Encryption, SSL/TLS, Encrypted Credentials Lamaging & Printing Security Center; D7P69A: Identity 1 solutions (e.g., badge readers); Network: IPSec/firewall EAP-TLS), SNMPv3, HTTPS, Certificates, Access Control nPcCket for security solutions, Security Management: C 3°C. Recommended operating temperature: 10 to 32.5° 30% RH	lable hard-disk space; CD-ROM or DVD diapple.com) ated capacitive Home button (for quick related capacitive Home button (for quick related capacitive Home button (for quick related capacitive Home) 45A: 1095 x 715 x 1040 mm; 56 x 790 x 1368 mm; PIN codes, optional HP Access Control approach to the configuration Pluggore Configuration Pluggore Configuration Pluggore Service: Security lock slot, USB port disadnagement: Kerberos authentication, Liwith Certificate, Pre-Shared Key, and Ke List; Data: Storage Encryption, Secure Ecompatible with HP Imaging & Printing Sec	pace; Operating system compatible hardware system requirements see rive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0) eturn to the Home menu); Easy Access USB; Hardware Integration Pocket and 3rd party advanced authentication solutions (e.g., badge readers); in, 802.1X authentication (EAP-PEAP, EAP-TLS), SNMPv3, HTTPS, ablement, Hardware Integration Pocket for security solutions; Security DAP authentication, 1000 user PIN codes, optional HP Access Control and erberos authentication, Supports WIA-10 IPsec configuration Plug-in, rase, SSL/TLS, Encrypted Credentials; Device: Security lock slot, USB port security Center; CZ245A: as D7P69A product;			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management	drive, or Internet connection; Dedi microsoft.com. Mac OS X v10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M 10.9 cm colour LCD with resistive Requirements: Input Voltage: 220 Out of package: CZ244A: 185 x 760 x 9 Packaged: CZ244A: 856 x 760 x 9 Packaged: CZ244A: 88.84 kg; DT HP Web Jetadmin; HP Utility (Mac) CZ244A: Identity Management: K Network: IPSec/firewall with Certif Certificates, Access Control List; D Management: Compatible with HP 3rd party advanced authentication 802.1X authentication (EAP-PEAP, disablement, Hardware Integration Operating temperature: 10 to 3.25 to 40°C. Storage humidity: 10 to 5	cated universal serial bus (USB 1.1 or 2.0), or network of OS X 10.7.5 Lion, OS X 10.8 Mountain Lion; 1 GB of avai system compatible hardware system requirements see lac SW Link to Web (Mac Installer), Windows Installer touchscreen; rotating (adjustable angle) display; illumina to 240 VAC, 50/60 Hz, 5.5 A 648 x 635 mm; D7P69A : 1095 x 715 x 1040 mm; CZ2 978 mm; D7P69A : 856 x 790 x 1368 mm; CZ245A : 89; D7P69A : 108.4 kg; CZ245A : 108.4 kg; P69A : 130.87 kg; CZ245A : 130.67 kg; erberos authentication, LDAP authentication, 1000 usei (cate, Pre-Shared Key, and Kerberos authentication, Sup ata: Storage Encryption, SSL/TLS, Encrypted Credentisty Imaging & Printing Security Center; D7P69A : Identity 1 solutions (e.g., badge readers); Network: IPSec/firewal EAP-TLS), SNMP2, HTTPS, Certificates, Access Control 1 Pocket for security solutions; Security Management: C 376°C. Recommended operating temperature: 10 to 32.59 30% RH	lable hard-disk space; CD-ROM or DVD diapple.com) ated capacitive Home button (for quick related capacitive Home button (for quick related capacitive Home button (for quick related capacitive Home) 45A: 1095 x 715 x 1040 mm; 56 x 790 x 1368 mm; PIN codes, optional HP Access Control approach to the configuration Pluggore Configuration Pluggore Configuration Pluggore Service: Security lock slot, USB port disadnagement: Kerberos authentication, Liwith Certificate, Pre-Shared Key, and Ke List; Data: Storage Encryption, Secure Ecompatible with HP Imaging & Printing Sec	pace; Operating system compatible hardware system requirements see rive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0 et universal serial bus (USB), Hardware Integration Pocket for security solutions; Security (DAP authentication, 1000 user PIN codes, optional HP Access Control and erberos authentication, Supports WJA-10 IPsec configuration Plug-in, rase, SSL/TLS, Encrypted Credentials; Device: Security lock slot, USB port security Center; CZ245A: as D7P69A product;			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management Operating environment Acoustics	drive, or Internet connection; Dedi microsoft.com. Mac OS X v10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M 10.9 cm colour LCD with resistive Requirements: Input Voltage: 220 Out of package: CZ244A: 1095 x Packaged: CZ244A: 856 x 760 x 40 Out of package: CZ244A: 856 x 760 x 40 Packaged: CZ244A: 88.84 kg; DT HP Web Jetadmin; HP Utility (Mac) CZ244A: Identity Management: K Network: IPSec/firewall with Certif Certificates, Access Control List; DW Management: Compatible with HP 3rd party advanced authentication 802.1X authentication (EAP-PEAP disablement, Hardware Integration Operating temperature: 10 to 32.5 to 40°C. Storage humidity: 10 to 9 Acoustic Pressure Emissions: 7.2 B(Acoustic Pressure Emissions: 55 d CISPR 22:22008 / EN 55022:2010 (cated universal serial bus (USB 1.1 or 2.0), or network or OS X 10.7.5 Lion, OS X 10.8 Mountain Lion; 1 GB of avai system compatible hardware system requirements see lac SW Link to Web (Mac Installer), Windows Installer touchscreen; rotating (adjustable angle) display; illumina to 240 VAC, 50/60 Hz, 5.5 A 648 x 635 mm; D7P69A: 1095 x 715 x 1040 mm; CZ2 7978 mm; D7P69A: 856 x 790 x 1368 mm; CZ245A: 85; D7P69A: 108.4 kg; CZ245A: 130.67 kg; erberos authentication, LDAP authentication, 1000 usei icate, Pre-Shared Key, and Kerberos authentication, Supata: Storage Encryption, SSL/TLS, Encrypted Credentials Imaging & Printing Security Center; D7P69A: Identity 1 asolutions (e.g., badge readers); Network: IPSec/firewall EAP-TLS), SNMPV3, HTTPS, Certificates, Access Control on Pocket for security solutions; Security Management: C 3°C. Recommended operating temperature: 10 to 32.5° 300 K RH (Class A), EN 61000-3-2:2006 +A1:2009 +A2:2009; EN	lable hard-disk space; CD-ROM or DVD dapple.com) sted capacitive Home button (for quick researched apple.com) 45A: 1095 x 715 x 1040 mm; 66 x 790 x 1368 mm; PIN codes, optional HP Access Control apports WIA-10 IPsec configuration Pluggions; Device: Security lock slot, USB port disk danagement: Kerberos authentication, Liwith Certificate, Pre-Shared Key, and Ke List; Data: Storage Encryption, Secure Eompatible with HP Imaging & Printing St. C. Operating humidity: 10 to 80% RH. C. (1900-3-3:2008; EN 55024:2010; EMI	pace; Operating system compatible hardware system requirements see rive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0) and 3rd party advanced authentication solutions (e.g., badge readers); in, 802.1X authentication (EAP-PEAP, EAP-TLS), SNMPv3, HTTPS, ablement, Hardware Integration Pocket for security solutions; Security DAP authentication, 1000 user PIN codes, optional HP Access Control and arberos authentication, 50pports WJA-10 IPsec configuration Plug-in, rase, SSL/TLS, Encrypted Credentials; Device: Security lock slot, USB port security Center; CZ245A: as D7P69A product; Operating humidity recommended: 10 to 80% RH. Storage temperature: 0			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management Operating environment Acoustics	drive, or Internet connection; Dedi microsoft.com. Mac OS X v10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M 10.9 cm colour LCD with resistive IR equirements: Input Voltage: 220 Out of package: CZ244A: 1095 x Packaged: CZ244A: 856 x 760 x 9 Out of package: CZ244A: 856 x 760 x 9 Packaged: CZ244A: 84 g. D7 HP Web Jetadmin; HP Utility (Mac) CZ244A: Identity Management: K Network: IPSec/firewall with Certificates, Access Control List; D: Management: Compatible with HP 3rd party advanced authentication 80.2 1 X authentication (EAP-PEAP disablement, Hardware Integration Operating temperature: 10 to 32.5 cm 40 of C. Storage humidity: 10 to 5 Acoustic Pressure Emissions: 7.2 B(Acoustic Pressure Emissions: 5.2 CISPR 22:2008 / EN 55022:2010 required by individual countries.	cated universal serial bus (USB 1.1 or 2.0), or network of SX 10.7.5 Lion, 05 X 10.8 Mountain Lion; 1 GB of avai system compatible hardware system requirements see lac SW Link to Web (Mac Installer), Windows Installer touchscreen; rotating (adjustable angle) display; illumina to 240 VAC, 50/60 Hz, 5.5 A GAB X 635 mm; D7P69A: 1095 x 715 x 1040 mm; CZ2 978 mm; D7P69A: 856 x 790 x 1368 mm; CZ245A: 8: 07P69A: 108.4 kg; CZ245A: 108.4 kg; P69A: 130.87 kg; CZ245A: 130.67	lable hard-disk space; CD-ROM or DVD diapple.com) ated capacitive Home button (for quick residual capacitive Home) ated capacitive Home button (for quick residual capacitive Home) ated Capa	pace; Operating system compatible hardware system requirements see rive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0 et universal serial bus (USB ; Hardware Integration Pocket for security solutions; Security DAP authentication, 1000 user PIN codes, optional HP Access Control and erberos authentication, Supports WIA-10 IPsec configuration Plug-in, rase, SSL/TLS, Encrypted Credentials; Device: Security lock slot, USB port security Center; CZ245A: as D7P69A product; Derating humidity recommended: 10 to 80% RH . Storage temperature: 0			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management	drive, or Internet connection; Dedi microsoft.com. Mac OS X v10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M 10.9 cm colour LCD with resistive IR equirements: Input Voltage: 220 Out of package: CZ244A: 1095 x Packaged: CZ244A: 38.56 x 760 x 9 Out of package: CZ244A: 38.84 kg; DT HP Web Jetadmin; HP Utility (Mac) CZ244A: Identity Management: K Network: IPSec/firewall with Certificates, Access Control List. Management: Compatible with HP 3rd party advanced authentication 802.1X authentication (EAP-PEAR disablement, Hardware Integration Operating temperature: 10 to 32.5 to 40°C. Storage humidity: 10 to 5 CISPR 22:2008 / EN \$5022:2010 (CISPR 22:2008 / EN \$5022:2010 (required by individual countries. R (Class 1 Laser/LED Product): 6S Ce	cated universal serial bus (USB 1.1 or 2.0), or network of SX 10.7.5 Lion, 0S X 10.8 Mountain Lion; 1 GB of avail system compatible hardware system requirements see lac SW Link to Web (Mac Installer), Windows Installer touchscreen; rotating (adjustable angle) display; illuminato 240 VAC, 50/60 Hz, 5.5 A 648 × 635 mm; D7P69A: 1095 × 715 × 1040 mm; CZ2478 mm; D7P69A: 856 × 790 × 1368 mm; CZ245A: 85; D7P69A: 108.4 kg; CZ245A: 108.4 kg; P69A: 130.87 kg; CZ245A: 130.67 kg; erberos authentication, LDAP authentication, 1000 uses ficate, Pre-Shared Key, and Kerberos authentication, Suptata: Storage Encryption, SSL/TLS, Encrypted Credentials Imaging & Printing Security Center; D7P69A: Identity in solutions (e.g., badge readers); Network: IPSec/firewall EAP-TLS), SNMPv3, HTTPS, Certificates, Access Control n Pocket for security solutions; Security Management Cost Cost Control no Pocket for security solutions; Security Management Cost Cost Cost Cost Cost Cost Cost Cos	lable hard-disk space; CD-ROM or DVD diapple.com) ated capacitive Home button (for quick residual capacitive Home) ated capacitive Home button (for quick residual capacitive Home) ated Capa	pace; Operating system compatible hardware system requirements see rive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0) and 3rd party advanced authentication solutions (e.g., badge readers); in, 802.1X authentication (EAP-PEAP, EAP-TLS), SNMPv3, HTTPS, ablement, Hardware Integration Pocket for security solutions; Security DAP authentication, 1000 user PIN codes, optional HP Access Control and erberos authentication, 500 services (SLTLS, Encrypted Credentials; Device: Security lock slot, USB port security Center; CZ245A: as D7P69A product; Operating humidity recommended: 10 to 80% RH. Storage temperature: 0			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management Operating environment Acoustics	drive, or Internet connection; Dedi microsoft.com. Mac OS X v10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M 10.9 cm colour LCD with resistive Requirements: Input Voltage: 220 Out of package: CZ244A: 1095 x Packaged: CZ244A: 856 x 760 x 9 Packaged: CZ244A: 856 x 760 x 9 Packaged: CZ244A: 188.84 kg; DT HP Web Jetadmir, HP utility (Mac) CZ244A: Identity Management: K Network: IPSec/firewall with Certificates, Access Control List; Dr. Management: Compatible with HP 3rd party advanced authentication 802.1X authentication (EAP-PEAP disablement, Hardware Integration Operating temperature: 10 to 32.5 to 40°C. Storage humidity: 10 to 5 Acoustic Power Emissions: 7.2 B/d. Acoustic Pressure Emissions: 55 d CISPR 22:2008 / EN 55022:2010 required by individual countries. R. (Class 1 Laser/LED Product): GS Ce individual countries. R.	cated universal serial bus (USB 1.1 or 2.0), or network or OS X 10.7.5 Lion, OS X 10.8 Mountain Lion; 1 GB of avail system compatible hardware system requirements see lac SW Link to Web (Mac Installer), Windows Installer touchscreen; rotating (adjustable angle) display; illumina to 240 VAC, 50/60 Hz, 5.5 A G88 X 635 mm; D7P69A: 1095 x 715 x 1040 mm; CZ2478 mm; D7P69A: 856 x 790 x 1368 mm; CZ245A: 85; D7P69A: 108.4 kg; CZ245A: 108.4 kg; P69A: 130.87 kg; CZ245A: 130.67 kg; erberos authentication, LDAP authentication, 1000 usel icate, Pre-Shared Key, and Kerberos authentication, Supata: Storage Encryption, SSL/TLS, Encrypted Credentials (LaParlis), SMMPv3, HTTPS, Certificates, Access Control in Pocket for security solutions; Security Management: C 5°C. Recommended operating temperature: 10 to 32.5° 2006 RH) B(A) (Class A), EN 61000-3-2:2006 +A1:2009 +A2:2009; EN egulatory standards: IEC 60950-1:2005 +A1; EN60950-1:1616 (Germany, Europe); IEC 62479:2010; EN 62479; EN 62479	lable hard-disk space; CD-ROM or DVD dapple.com) sted capacitive Home button (for quick researched to the complex of the comp	pace; Operating system compatible hardware system requirements see rive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0) and 3rd party advanced authentication solutions (e.g., badge readers); in, 802.1X authentication (EAP-PEAP, EAP-TLS), SNMPv3, HTTPS, ablement, Hardware Integration Pocket for security solutions; Security DAP authentication, 1000 user PIN codes, optional HP Access Control and arberos authentication, 500 user PIN codes, optional HP Access Control and arberos authentication, 50pports WJA-10 IPsec configuration Plug-in, rase, SSL/TLS, Encrypted Credentials; Device: Security lock slot, USB port ecurity Center; CZ245A: as D7P69A product; Operating humidity recommended: 10 to 80% RH. Storage temperature: 0 CDirective 2004/108/EC with CE Marking (Europe); other EMC approvals as 11; IEC 60825-1:2007 (Class 1 Laser/Led Product); EN 60825-1:2007 EC with CE Marking (Europe); other safety approvals as required by			
Standard software Control panel Power Dimensions (w x d x h) Weight Printer management Security management Operating environment Acoustics	drive, or Internet connection; Dedi microsoft.com. Mac OS X v10.6.8, or network connection (Operating HP PCL 6 Discrete Printer Driver, M 10.9 cm colour LCD with resistive Requirements: Input Voltage: 220 Out of package: CZ244A: 1095 x Packaged: CZ244A: 856 x 760 x 9 Packaged: CZ244A: 856 x 760 x 9 Packaged: CZ244A: 188.84 kg; DT HP Web Jetadmir, HP utility (Mac) CZ244A: Identity Management: K Network: IPSec/firewall with Certificates, Access Control List; Dr. Management: Compatible with HP 3rd party advanced authentication 802.1X authentication (EAP-PEAP disablement, Hardware Integration Operating temperature: 10 to 32.5 to 40°C. Storage humidity: 10 to 5 Acoustic Power Emissions: 7.2 B/d. Acoustic Pressure Emissions: 55 d CISPR 22:2008 / EN 55022:2010 required by individual countries. R. (Class 1 Laser/LED Product): GS Ce individual countries. R.	cated universal serial bus (USB 1.1 or 2.0), or network of SX 10.7.5 Lion, 05 X 10.8 Mountain Lion; 1 GB of avai system compatible hardware system requirements see lac SW Link to Web (Mac Installer), Windows Installer touchscreen; rotating (adjustable angle) display; illumina to 240 VAC, 50/60 Hz, 5.5 A 648 x 635 mm; D7P69A: 1095 x 715 x 1040 mm; CZ2 978 mm; D7P69A: 856 x 790 x 1368 mm; CZ245A: 85; D7P69A: 108.4 kg; CZ245A: 108.4 kg; P69A: 130.87 kg; CZ245A: 130.67 kg; erberos authentication, LDAP authentication, 1000 usericate, Pre-Shared Key, and Kerberos authentication, Sug ata: Storage Encryption, SSL/TLS, Encrypted Credentials; Imaging & Printing Security Center; D7P69A: Identity In solutions (e.g., badge readers); Network: IPSec/firewal EAP-TLS), ShMPA9, HTTPS, Certificates, Access Control on Pocket for security solutions; Security Management: C 37C. Recommended operating temperature: 10 to 32.59 (Class A), EN 61000-3-2:2006 +A1:2009 +A2:2009; EN egulatory standards: IEC 60950-1:2005 +A1; EN60950-trificate (Germany, Europe); IEC 62479:2010; EN 62475; Yes	lable hard-disk space; CD-ROM or DVD dapple.com) sted capacitive Home button (for quick researched to the complex of the comp	pace; Operating system compatible hardware system requirements see rive, or Internet connection; Dedicated universal serial bus (USB 1.1 or 2.0 et universal serial bus (USB ; Hardware Integration Pocket for security solutions; Security LoAP authentication, 1000 user PIN codes, optional HP Access Control and erberos authentication, Supports WJA-10 IPsec configuration Plug-in, rase, SSL/TLS, Encrypted Credentials; Device: Security lock slot, USB port ecurity Center; CZ245A: as D7P69A product; Derating humidity recommended: 10 to 80% RH . Storage temperature: 0			



