

MikroTik IoT Updates:

Reliable LoRa® Solutions at an Even Better Price



wAP LR8G kit

A **compact, weatherproof outdoor gateway** for LoRa® technology. The updated **868MHz LoRa® module** delivers enhanced **Rx sensitivity**, extending your range and improving reliability—even in rough conditions. This versatile device also includes:

- Built-in **GPS**.
- A **2.4 GHz WiFi interface** and Ethernet port for seamless integration.
- Durable design, tested to perform in various weather conditions.



LtAP LR8G LTE6 kit

A **rugged all-in-one device** for IoT connectivity, ideal for industrial or public use. Perfect for **transportation projects** or **logistics**, the LtAP LR8G LTE6 Kit combines:



- **LoRa® connectivity**, LTE, and GPS for maximum versatility.
- Dual-chain **2.4 GHz WiFi** for added flexibility.
- A tough, robust enclosure built for industrial and mobile setups.
- Mini SIM slot and a built-in modern LTE6 modem for fast and responsive mobile connectivity
- Enhanced **868MHz Rx sensitivity** for effective long-range communication.
- Many powering options, including automotive.

R11e-LR8G card

The simplest way to add **LoRa® connectivity** to any MikroTik device with a mini PCIe slot. Perfect for tight budgets without compromising performance, this card features:

- Exceptional **Rx sensitivity** up to **-141 dBm** for 868MHz, ensuring reliable long-range communication.
- Compact, efficient design for easy integration into existing setups.
- Cost-effective performance for IoT projects of any scale.
- Integrated GPS chip for LoRa packet timestamps in various setups.



The Things Network

Our products for LoRa® are ready to work with “The Things Network” - the famous open source infrastructure that provides free LoRa® network coverage and has tons of apps for your needs. With the help of “The Things Network” you can get started with the Internet-of-things within a day. And it is easily upgradable to enterprise-grade network “The Things Industries”.

The setup is so easy - anyone can learn it. No need to reinvent the wheel – join “The Things Network” to save time and energy with smart solutions!

• wAP LR8G kit specifications

Product code	RBwAPR-2nD&R11e-LR8G
CPU	Single-core QCA9531 600 MHz
CPU architecture	MIPSBE
Size of RAM	64 MB
RAM type	DDR2
Storage	16 MB, NAND
Number of 100M Ethernet ports	1
Wireless	2.4 GHz
Protocols	802.11b/g/n
Wireless interface model	QCA9531
Antenna gain	2 dBi
Antenna beam width	360°
Dimensions	185 x 85 x 30 mm
Operating system	RouterOS v7, License level 4
Operating temperature	-40°C to +60°C

• wAP LR8G kit powering

Number of DC inputs	3 (PoE-In, Automotive, DC jack)
PoE-In input Voltage	9-28 V
Automotive input Voltage	12-30 V
DC jack input Voltage	9-28 V
Power adapter nominal voltage	24 V
Power adapter nominal current	0.8 A
PoE-In	Passive PoE
Max power consumption	7 W

• wAP LR8G kit wireless specifications

Rate (2.4 GHz)	Tx (dBm)	Receive Sensitivity
1MBit/s	22	-96
11MBit/s	22	-89
6MBit/s	20	-93
54MBit/s	18	-74
MCS0	20	-93
MCS7	16	-71

• wAP LR8G kit included parts



24 V 0.8 A power adapter



Gigabit PoE injector




Fastening set



Desktop stand



Outdoor case bracket



Ceiling mount base



Hose clamp

• LtAP LR8G LTE6 kit Specifications

Product code	LtAP-2HnD&FG621-EA&LR8G
CPU	Dual-core MT7621AT 880 MHz
CPU architecture	MMIPS
Size of RAM	128 MB
RAM type	DDR3
Storage	16 MB, Flash
Number of 1G Ethernet ports	1
SIM slots	3 Mini SIM
Wireless interface model	AR9342
Wireless	2.4 GHz 802.11b/g/n dual-chain
Antenna gain	2.5 dBi
LoRa band	868MHz
GNSS interface model	MT3337V
LTE modem	R11eL-FG621-EA
TAC	86335904
LTE Category	6 (300Mbit/s Downlink, 50Mbit/s Uplink)
MIMO DL	2x2
MIMO UL	1x1
LTE FDD bands	1 (2100 MHz) / 3 (1800 MHz) / 5 (850 MHz) / 7 (2600 MHz) / 8 (900 MHz) / 20 (800 MHz) / 28 (700 MHz)
LTE TDD bands	38 (2600MHz) / 40 (2300MHz) / 41 (2500MHz)
3G Category	R8 (42.2Mbps Downlink, 11.2Mbps Uplink)
3G bands	1 (2100MHz) / 3 (1800MHz) / 5 (850MHz) / 8 (900MHz)
Dimensions	170 x 162 x 40 mm
Operating system	RouterOS v7 only
Operating temperature	-40°C to +70°C

• LtAP LR8G LTE6 kit Certification & Approvals

Certification	CE, FCC, IC, E-MARK, EAC, ROHS
IP	IP54

• LtAP LR8G LTE6 kit Powering

Number of DC inputs	3 (PoE-In, Automotive, DC jack)
PoE-In input Voltage	12-30 V
Automotive input Voltage	12-27 V
DC jack input Voltage	12-30 V
Power adapter nominal voltage	24 V
Power adapter nominal current	1.2 A
PoE-In	Passive PoE
Max power consumption (without attachments)	12 W
Max power consumption	24 W

• LtAP LR8G LTE6 kit Wireless specifications

Rate (2.4 GHz)	Tx (dBm)	Receive Sensitivity
1MBit/s	25	-100
11MBit/s	25	-94
6MBit/s	26	-96
54MBit/s	23	-78
MCS0	26	-96
MCS7	22	-73

• LtAP LR8G LTE6 kit Included parts



24 V 1.2 A
power adapter



Screw set



Automotive cable

• R11e-LR8G Specifications

Product code	R11e-LR8G
Interface	Mini-PCle
Baseband chip	SX1302
Listen before talk	Yes
Support class	A and C
Frequency	863-870 MHz (EU863-870, RU864-870, IN865-867)
RF Output power	863-870 MHz 27 dBm
Receive max sensitivity	-141 dBm
GPS receiver	Yes
Range	Up to 15 km in rural environment and up to 2 km in urban environment when using MikroTik LoRa® 6.5 dBi antenna kit
Operating temperature	-40°C to +70°C
Max power consumption	1.3 W