


UISP Cable

Datasheet
UISP-Cable-Pro/Carrier



UISP Cable Pro/Carrier

Protect your networks from harmful outdoor environments with Ubiquiti's industrial-grade shielded Ethernet cable, UISP Cable.

A Category 5e, outdoor, carrier-class shielded cable features an integrated ESD drain wire.



Specifications

Box Dimensions	UISP-Cable-Pro: 330 x 330 x 340 mm (13 x 13 x 13.4") UISP-Cable-Carrier: 330 x 425 x 340 mm (13 x 16.7 x 13.4")
Box Weight	UISP-Cable-Pro: 12 kg (26.5 lb) UISP-Cable-Carrier: 16 kg (35.3 lb)
Cable Length	305 m (1000 ft)
Cable Color	Black
Cable Type	CAT5e, Shielded
Ethernet Support	Up to 1 Gbps
Conductor Wire Gauge	24 AWG
Conductor	Solid Bare Copper
Conductor Type	Solid Bare Copper
Conductor Diameter	0.500 ± 0.005 mm
Insulation Type	Solid Polyethylene
Insulation Thickness	UISP-Cable-Pro: Avg. 0.26 mm (Min. 0.25 mm) UISP-Cable-Carrier: Avg. 0.295 mm (Min. 0.29 mm)
Insulation Diameter	UISP-Cable-Pro: 1.04 ± 0.03 mm UISP-Cable-Carrier: 1.16 ± 0.02 mm
Separation (Polyester Wrapping)	Thick: 0.025 mm, Extent: 20 mm
Anti-Crosstalk Divider	UISP-Cable-Pro: None UISP-Cable-Carrier: LDPE: 4.2*0.3 mm
Cable Shield (Aluminum Foil)	UISP-Cable-Pro: Thick: 0.060 mm, Extent: 18 mm UISP-Cable-Carrier: Thick: 0.060 mm, Extent: 20 mm
ESD Drain Wire	UISP-Cable-Pro: 0.4 CCS UISP-Cable-Carrier: 0.4 TC
Rip Cord	Yes
Jacket Material	Polyethylene
Jacket Thickness	UISP-Cable-Pro: Avg. 0.50 mm (Min. 0.46 mm) UISP-Cable-Carrier: Avg. 0.52 mm (Min. 0.46 mm)
Jacket Diameter	UISP-Cable-Pro: 6.0 ± 0.30 mm UISP-Cable-Carrier: 6.8 ± 0.30 mm
Storage Temperature	-30 to 75°C (-22 to 167°F)
Installation Temperature	-20 to 60°C (-4 to 140°F)
Operation Temperature	-40 to 80°C (-40 to 176°F)
Standards	ANSI/TIA-568-C.2 (2009) ISO/IEC 11801 (Edition 2.2)

Performance



UIISP Cable Pro

Frequency (MHz)	RL (dB) min.	Attenuation (dB/100 m)	NEXT/PSNEXT (dB)	ACR (dB)	ELFEXT/PSELFEXT (dB/100 m)
1	17.0	2.03	62.30	6.30	60.75
4	18.8	4.04	53.26	49.20	48.71
8	19.7	5.76	48.75	43.00	42.69
10	20.0	6.46	47.30	40.80	40.75
16	20.0	8.24	44.30	36.10	36.67
20	20.0	9.26	42.78	33.50	34.73
25	19.3	10.41	41.33	30.90	32.79
31.25	18.6	11.72	39.87	28.20	30.86
62.5	16.5	16.99	35.36	18.40	24.83
100	15.1	21.97	32.29	10.30	20.75
150	13.80	23.40	18.60/30.30	8.30	17.60/18.50

UIISP Cable Carrier

Frequency (MHz)	RL (dB) min.	Attenuation (dB/100 m)	NEXT/PSNEXT (dB)	ACR (dB)	ELFEXT/PSELFEXT (dB/100 m)
1	18.0	1.93	65.30	60.30	61.00
4	19.9	3.90	56.27	49.20	48.96
8	20.7	5.50	51.75	43.00	42.94
10	21.0	6.30	50.30	40.80	41.00
16	21.0	8.00	47.24	36.10	36.92
20	21.0	9.00	45.78	33.50	34.98
25	20.3	10.20	44.33	30.90	33.04
31.25	19.5	11.50	42.88	28.20	31.10
62.5	19.0	16.70	38.36	18.40	25.08
100	18.3	21.70	35.30	10.30	21.00
200	16.5	32.20	30.78/27.78	7.60	17.78/14.98



Specifications are subject to change. Ubiquiti products are sold with a limited warranty described at www.ui.com/support/warranty

©2021 Ubiquiti Inc. All rights reserved. Ubiquiti, Ubiquiti Networks, the Ubiquiti U logo, the Ubiquiti beam logo, UniFi, and UniFi Network are trademarks or registered trademarks of Ubiquiti Inc. in the United States and in other countries. All other trademarks are the property of their respective owners.