

Portable Charger - 2x USB-A, USB-C with PD Charging, 20,100mAh Power Bank, Lithium-Ion, USB-IF, Black

MODEL NUMBER: UPB-20K0-2U1C











Compact 20,100mAh power bank charges up to 3 smartphones, tablets, e-readers and other mobile devices without using an AC power outlet.

Features

20,100mAh Lithium-Ion Battery Charges Your Mobile Devices without an AC Power OutletNo more frantic searching for an outlet when your mobile device's battery power is getting low. Small and lightweight, this high-capacity power bank dishes out 20,100mAh of battery capacity for charging up to three mobile devices at the same time, including smartphones, tablets, e-readers and handheld gaming devices. Lithium-ion lasts longer than lead-acid batteries and save you money in the end. The UPB-20K0-2U1C is compatible with Android, Apple and Windows devices.

3 USB Ports Allow You to Keep Your Phone and Other Essential Devices Ready for UseDual USB-A ports provide 5V 2.4A (12W) of total power per port. The ports support 1.5A of fast-charging power for Apple devices. The USB-C port supports PD charging up to 5V 3A (15W), 9V 3A (27W), 12V 3A (36W), 15V 3A (45W) and 20V 2.25A (45W). All three ports provide a maximum of 57W of charging power simultaneously.

Protects Your Expensive Devices During ChargingComprehensive safety features ensure worry-free charging of mobile devices. The power bank provides short circuit, overvoltage, overcurrent, overcharge and overdischarge protection.

Easy to Recharge for the Next Time You Leave Home A lithium-ion battery with 20,100mAh of capacity provides charging at maximum power draw for hours, making your devices ready when you need them. Status LEDs let you know how much battery capacity is left. When it's time to charge the internal battery, use the included USB-C cable to connect the power bank's USB-C port to a USB-C port on a computer or wall charger.

USB-IF Certification Ensures Rigorous Testing and Top-of-the-Line PerformanceThis power bank meets the high standards of USB-IF (USB Implementers Forum, Inc.), a non-profit organization consisting of companies that developed the USB specification. Receiving USB-IF certification means the UPB-20K0-2U1C meets the industry's highest environmental, mechanical and electrical standards. It operates with your USB devices, adapters and cables with top efficiency and safety.

Compact Housing Packs in a Pocket for On-the-Go Charging An ideal power solution when you're on

Highlights

- Ideal for road trips, hikes, blackouts and other applications without AC power
- USB-A and USB-C ports provide 57W maximum charging power simultaneously
- 20,100mAh of lithium-ion battery capacity is plenty for hours of maximum power draw
- Certified by USB-IF to ensure highest-grade construction and performance
- LED indicators show remaining power bank battery capacity at a glance

Applications

- Charge tablets and other mobile devices while away from home or office
- Maintain your smartphones' battery capacities while camping or hiking
- Keep your mobile devices working during a utility power outage

Package Includes

- UPB-20K0-2U1C 20,100mAh 3-Port Mobile Power Bank USB Battery Charger
- USB-C cable (M/M), 3 ft.
- Owner's manual



the road or stuck somewhere without convenient electricity, the portable battery charger weighs less than one pound. It fits comfortably in your purse, pocket or backpack to keep your phone, tablet, e-reader, MP3 player, digital camera or other handheld device operating when you need it.

Specifications

avenuew.		
OVERVIEW		
UPC Code	037332214218	
Product Type	Portable Charger	
Charging Form Factor	Portable	
Device Compatibility	Phone; Tablet; Amazon Kindle	
Country/Region	Global	
INPUT		
Input Plug Type	USB-C (FEMALE)	
Input Plug Type Details	USB-A to USB-C cable provided	
ОИТРИТ		
Output Capacity (Watts)	57	
Continuous Output Capacity (Watts)	57	
Overload Protection	Yes	
BATTERY		
Battery Charging (5V/1.5A Port)	Yes	
Capacity (Ah)	20.1	
POWER		
Power Consumption (Watts)	57	
USB Power Delivery (PD) Charging Support	Yes	
USB Power Delivery (PD) Charging Specification	3.0	
USER INTERFACE, ALERTS & CONTROLS		
LED Indicators	LED's will illuminate to indicate USB Device Charging Status as well as Power Bank Charging Status. See manual for LED information.	
CHARGING		
Number of Charging Ports	2	
Total Charging Amps	4.65A	



Total Charging Wets 57 Charging Method USB Charging Method Detail 20.100 mAh Charging Ports (2) USB A (FEMALE): USB C (FEMALE) Charging Ports (2) 2.4A Quick Charge Charging Ports J Amps (1) 2.25x, (2) 2.4A Charging Ports / Amps (1) 2.25x, (2) 2.4A Mangerist Charging No Wireless Charging No Overcharge Protection Yes Compatible Devices Smartphone: Tablet: Video Game Console PHYSICAL Color Black Material of Construction ABS Total Number of Ports 3 Shipping Dimensions (hwd / cm) 1.81 x 9.25 x 4.65 Shipping Dimensions (hwd / cm) 4.60 x 23.50 x 11.81 Shipping Weight (fbs.) 1.32 Shipping Weight (fg) 0.60 Unit Dimensions (hwd / m) 1.000 x 3.200 x 6.400 Unit Dimensions (hwd / cm) 2.2 x 8 x 16.24 Unit Weight (bs.) 0.8 Unit Weight (bs.) 0.8 Unit Weight (kg) 0.36			
Charging Method Detail 20,100 mAh Charging Port Type (2) USB A (FEMALE): USB C (FEMALE) Charging Ports (2) 2.4A Quick Charge Charging Ports (2) 2.4A Quick Charge Charging Ports Details USB-C; SV/3A, 9.9/3A, 12V/3A, 15V/3A, 20V/2.25AUSB-A; SV/2.4A Charging Ports / Amps (1) 2.25A; (2) 2.4A Charging Ports / Amps (1) 2.25A; (2) 2.4A Charging Ports / Amps (3) 2.5A; (2) 2.4A (3) 2.4A (3) 2.5A; (3) 2.4A (3) 2.5A; (3) 2.4A (3) 2.5A (3) 2.	Total Charging Watts	57	
Charging Port Type (2) USB A (FEMALE); USB C (FEMALE)		USB	
Charging Ports (2) 2.4A Quick Charge Charging Ports Details USB-C: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/2.25AUSB-A: 5V/2.4A Charging Ports / Amps (1) 2.25A; (2) 2.4A Magnetic Charging No Wireless Charging No Overcharge Protection Yes Compatible Devices Smartphone; Tablet; Video Game Console PHYSICAL Color Black Material of Construction ABS Total Number of Ports 3 Shipping Dimensions (hwd / in.) 1.81 x 9.25 x 4.65 Shipping Weight (lbs.) 1.32 Shipping Weight (lbs.) 1.32 Shipping Weight (lbs.) 1.32 Shipping Weight (lbs.) 0.60 Unit Dimensions (hwd / in.) 1.000 x 3.200 x 6.400 Unit Dimensions (hwd / in.) 2.2 x 8 x 16.24 Unit Weight (lbs.) 0.8 Unit Weight (lbs.) 0.8 Unit Weight (kg) 0.36 ENVIRONMENTAL Operating Temperature Range 4" to 140°F (20° to 40°C) Storage Humidity Range 20% to 50% RH, Non	Charging Method Detail	20,100 mAh	
Charging Ports Details USB-C: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/2.25AUSB-A: 5V/2.4A Charging Ports / Amps (1) 2.25A; (2) 2.4A Magnetic Charging No Overcharge Protection Yes Compatible Devices Smartphone; Tablet; Video Game Console PHYSICAL Color Black Material of Construction ABS Total Number of Ports 3 Shipping Dimensions (hwd / in.) 1.81 x 9.25 x 4.65 Shipping Dimensions (hwd / cm) 4.60 x 23.50 x 11.81 Shipping Weight (lbs.) 1.32 Shipping Weight (kg) 0.60 Unit Dimensions (hwd / in.) 1.00 x 3.200 x 6.400 Unit Dimensions (hwd / in.) 2.2 x 8 x 16.24 Unit Packaging Type Box Unit Weight (lbs.) 0.8 Unit Weight (lbs.) 0.8 Unit Weight (kg) 0.36 ENVIRONMENTAL Operating Temperature Range 4° to 140°F (-20° to 60°C) Operating Temperature Range 4° to 140°F (-20° to 60°C) Operating Humidity Range 20% to 50% RH, Non-Condensing	Charging Port Type	(2) USB A (FEMALE); USB C (FEMALE)	
Charging Ports / Amps (1) 2.25A; (2) 2.4A Magnetic Charging No Wireless Charging No Corpatible Devices Smartphone; Tablet; Video Game Console PHYSICAL Color Black Material of Construction ABS Total Number of Ports 3 Shipping Dimensions (twd /in.) 1.81 x 9.25 x 4.65 Shipping Weight (kg) 4.60 x 23.50 x 11.81 Shipping Weight (kg) 0.60 Unit Dimensions (twd / in.) 1.000 x 3.200 x 6.400 Unit Dimensions (twd / in.) 2.2 x 8 x 16.24 Unit Weight (kg) 0.8 Unit Weight (kg) 0.36 ENVIRONMENTAL Operating Temperature Range Storage Temperature Range 32° to 104°F (°° to 40°C) Storage Temperature Range 20% to 90% RH, Non-Condensing Storage Humidity Range 5% to 45% RH, Non-Condensing CONNECTIONS Number of Ports 3 Side A - Connector 1 USB C (FEMALE)	Charging Ports	(2) 2.4A Quick Charge	
Magnetic Charging No Overcharge Protection Yes Compatible Devices Smartphone; Tablet; Video Game Console PHYSICAL Color Black Material of Construction ABS Total Number of Ports 3 Shipping Dimensions (Iwd / in.) 1.81 x 9.25 x 4.65 Shipping Dimensions (Iwd / cm) 4.60 x 23.50 x 11.81 Shipping Weight (Ibs.) 1.32 Shipping Weight (kg) 0.60 Unit Dimensions (Iwd / in.) 1.000 x 3.200 x 6.400 Unit Packaging Type Box Unit Weight (Ibs.) 0.8 Unit Weight (Ibs.) 0.8 Unit Weight (Ikg) 0.36 ENVIRONMENTAL Operating Temperature Range 32° to 104°F (°° to 40°C) Storage Temperature Range 4° to 140°F (-20° to 60°C) Operating Humidity Range 20% to 90% RH, Non-Condensing Storage Humidity Range 5% to 45% RH, Non-Condensing CONNECTIONS Number of Ports 3 Side A - Connector 1 USB C (FEMALE)	Charging Ports Details	USB-C: 5V/3A. 9V/3A, 12V/3A, 15V/3A, 20V/2.25AUSB-A: 5V/2.4A	
Wireless Charging No Overcharge Protection Yes Compatible Devices Smartphone; Tablet; Video Game Console PHYSICAL Color Black Material of Construction ABS Total Number of Ports 3 Shipping Dimensions (hwd / in.) 1.81 x 9.25 x 4.65 Shipping Dimensions (hwd / cm) 4.60 x 23.50 x 11.81 Shipping Weight (lbs.) 1.32 Shipping Weight (kg) 0.60 Unit Dimensions (hwd / in.) 1.000 x 3.200 x 6.400 Unit Packaging Type Box Unit Weight (lbs.) 0.8 Coperating Temperature Range 32* to 104*F (0* to 40*C) Storage Temperature Range 4* to 140*F (-20* to 60*C) Operating Humidity Range	Charging Ports / Amps	(1) 2.25A; (2) 2.4A	
Overcharge Protection Yes Compatible Devices Smartphone; Tablet; Video Game Console PHYSICAL Color Black Material of Construction ABS Total Number of Ports 3 Shipping Dimensions (hwd / in.) 1.81 x 9.25 x 4.65 Shipping Dimensions (hwd / cm) 4.60 x 23.50 x 11.81 Shipping Weight (lbs.) 1.32 Shipping Weight (kg) 0.60 Unit Dimensions (hwd / cm) 2.2 x 8 x 16.24 Unit Dimensions (hwd / cm) 2.2 x 8 x 16.24 Unit Weight (lbs.) 0.8 Unit Weight (kg) 0.36 ENVIRONMENTAL Operating Temperature Range 32° to 104°F (0° to 40°C) Storage Temperature Range 32° to 104°F (-20° to 60°C) Operating Humidity Range 20% to 90% RH, Non-Condensing CONNECTIONS Number of Ports 3 Side A - Connector 1 USB C (FEMALE)	Magnetic Charging	No	
Compatible Devices Smartphone; Tablet; Video Game Console	Wireless Charging	No	
PHYSICAL Color Black Material of Construction ABS Total Number of Ports 3 Shipping Dimensions (hwd / in.) 1.81 x 9.25 x 4.65 Shipping Dimensions (hwd / cm) 4.60 x 23.50 x 11.81 Shipping Weight (lbs.) 1.32 Shipping Weight (kg) 0.60 Unit Dimensions (hwd / cm) 1.000 x 3.200 x 6.400 Unit Dimensions (hwd / cm) 2.2 x 8 x 16.24 Unit Weight (lbs.) 0.8 Unit Weight (kg) 0.36 ENVIRONMENTAL Operating Temperature Range 32° to 104°F (°° to 40°C) Storage Temperature Range 4° to 140°F (°20° to 60°C) Operating Humidity Range 20% to 90% RH, Non-Condensing Storage Humidity Range 5% to 45% RH, Non-Condensing CONNECTIONS Number of Ports 3 Side A - Connector 1 USB C (FEMALE)	Overcharge Protection	Yes	
Color Black Material of Construction ABS Total Number of Ports 3 Shipping Dimensions (hwd / in.) 1.81 x 9.25 x 4.65 Shipping Dimensions (hwd / cm) 4.60 x 23.50 x 11.81 Shipping Weight (lbs.) 1.32 Shipping Weight (kg) 0.60 Unit Dimensions (hwd / cm) 1.000 x 3.200 x 6.400 Unit Dimensions (hwd / cm) 2.2 x 8 x 16.24 Unit Packaging Type Box Unit Weight (lbs.) 0.8 Unit Weight (kg) 0.36 ENVIRONMENTAL Operating Temperature Range 32° to 104°F (0° to 40°C) Storage Temperature Range 20% to 90% RH, Non-Condensing Storage Humidity Range 20% to 45% RH, Non-Condensing Storage Humidity Range 5% to 45% RH, Non-Condensing CONNECTIONS Number of Ports 3 Side A - Connector 1 USB C (FEMALE)	Compatible Devices	Smartphone; Tablet; Video Game Console	
Color Black Material of Construction ABS Total Number of Ports 3 Shipping Dimensions (hwd / in.) 1.81 x 9.25 x 4.65 Shipping Dimensions (hwd / cm) 4.60 x 23.50 x 11.81 Shipping Weight (lbs.) 1.32 Shipping Weight (kg) 0.60 Unit Dimensions (hwd / cm) 1.000 x 3.200 x 6.400 Unit Dimensions (hwd / cm) 2.2 x 8 x 16.24 Unit Packaging Type Box Unit Weight (lbs.) 0.8 Unit Weight (kg) 0.36 ENVIRONMENTAL Operating Temperature Range 32° to 104°F (0° to 40°C) Storage Temperature Range 20% to 90% RH, Non-Condensing Storage Humidity Range 20% to 45% RH, Non-Condensing Storage Humidity Range 5% to 45% RH, Non-Condensing CONNECTIONS Number of Ports 3 Side A - Connector 1 USB C (FEMALE)	PUVOIOAI		
Material of Construction ABS Total Number of Ports 3 Shipping Dimensions (hwd / in.) 1.81 x 9.25 x 4.65 Shipping Dimensions (hwd / cm) 4.60 x 23.50 x 11.81 Shipping Weight (lbs.) 1.32 Shipping Weight (kg) 0.60 Unit Dimensions (hwd / in.) 1.000 x 3.200 x 6.400 Unit Dimensions (hwd / cm) 2.2 x 8 x 16.24 Unit Weight (lbs.) 0.8 Unit Weight (kg) 0.36 ENVIRONMENTAL Operating Temperature Range 32° to 104°F (0° to 40°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 20% to 90% RH, Non-Condensing Storage Humidity Range 5% to 45% RH, Non-Condensing CONNECTIONS Number of Ports 3 Side A - Connector 1 USB C (FEMALE)			
Total Number of Ports 3			
Shipping Dimensions (hwd / in.) 1.81 x 9.25 x 4.65 Shipping Dimensions (hwd / cm) 4.60 x 23.50 x 11.81 Shipping Weight (lbs.) 1.32 Shipping Weight (kg) 0.60 Unit Dimensions (hwd / in.) 1.000 x 3.200 x 6.400 Unit Dimensions (hwd / cm) 2.2 x 8 x 16.24 Unit Weight (lbs.) 0.8 Unit Weight (kg) 0.36 ENVIRONMENTAL Operating Temperature Range 32° to 104°F (0° to 40°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 20% to 90% RH, Non-Condensing Storage Humidity Range 5% to 45% RH, Non-Condensing CONNECTIONS Number of Ports 3 Side A - Connector 1 USB C (FEMALE)			
Shipping Dimensions (hwd / cm) 4.60 x 23.50 x 11.81 Shipping Weight (lbs.) 1.32 Shipping Weight (kg) 0.60 Unit Dimensions (hwd / in.) 1.000 x 3.200 x 6.400 Unit Dimensions (hwd / cm) 2.2 x 8 x 16.24 Unit Packaging Type Box Unit Weight (lbs.) 0.8 Unit Weight (kg) 0.36 ENVIRONMENTAL Operating Temperature Range Storage Temperature Range 32° to 104°F (0° to 40°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 20% to 90% RH, Non-Condensing Storage Humidity Range 5% to 45% RH, Non-Condensing CONNECTIONS Number of Ports 3 Side A - Connector 1 USB C (FEMALE)			
Shipping Weight (lbs.) 1.32 Shipping Weight (kg) 0.60 Unit Dimensions (hwd / in.) 1.000 x 3.200 x 6.400 Unit Dimensions (hwd / cm) 2.2 x 8 x 16.24 Unit Packaging Type Box Unit Weight (lbs.) 0.8 Unit Weight (kg) 0.36 ENVIRONMENTAL Operating Temperature Range 32° to 104°F (0° to 40°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 20% to 90% RH, Non-Condensing Storage Humidity Range 5% to 45% RH, Non-Condensing CONNECTIONS Number of Ports 3 Side A - Connector 1 USB C (FEMALE)		1.81 x 9.25 x 4.65	
Shipping Weight (kg) 0.60	Shipping Dimensions (hwd / cm)	4.60 x 23.50 x 11.81	
Unit Dimensions (hwd / in.) Unit Dimensions (hwd / cm) 2.2 x 8 x 16.24 Unit Packaging Type Box Unit Weight (lbs.) 0.8 Unit Weight (kg) 0.36 ENVIRONMENTAL Operating Temperature Range 32° to 104°F (0° to 40°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 20% to 90% RH, Non-Condensing Storage Humidity Range 5% to 45% RH, Non-Condensing CONNECTIONS Number of Ports 3 Side A - Connector 1 USB C (FEMALE)	Shipping Weight (lbs.)	1.32	
Unit Dimensions (hwd / cm) 2.2 x 8 x 16.24 Unit Packaging Type Box Unit Weight (lbs.) 0.8 Unit Weight (kg) 0.36 ENVIRONMENTAL Operating Temperature Range 32° to 104°F (0° to 40°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 20% to 90% RH, Non-Condensing Storage Humidity Range 5% to 45% RH, Non-Condensing CONNECTIONS Number of Ports 3 Side A - Connector 1 USB C (FEMALE)	Shipping Weight (kg)	0.60	
Unit Packaging Type Box Unit Weight (lbs.) 0.8 Unit Weight (kg) 0.36 ENVIRONMENTAL Operating Temperature Range 32° to 104°F (0° to 40°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 20% to 90% RH, Non-Condensing Storage Humidity Range 5% to 45% RH, Non-Condensing CONNECTIONS Number of Ports 3 Side A - Connector 1 USB C (FEMALE)	Unit Dimensions (hwd / in.)	1.000 x 3.200 x 6.400	
Unit Weight (lbs.) Unit Weight (kg) 0.36 ENVIRONMENTAL Operating Temperature Range 32° to 104°F (0° to 40°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 20% to 90% RH, Non-Condensing Storage Humidity Range 5% to 45% RH, Non-Condensing CONNECTIONS Number of Ports 3 Side A - Connector 1 USB C (FEMALE)	Unit Dimensions (hwd / cm)	2.2 x 8 x 16.24	
Unit Weight (kg) ENVIRONMENTAL Operating Temperature Range 32° to 104°F (0° to 40°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 20% to 90% RH, Non-Condensing Storage Humidity Range 5% to 45% RH, Non-Condensing CONNECTIONS Number of Ports 3 Side A - Connector 1 USB C (FEMALE)	Unit Packaging Type	Вох	
ENVIRONMENTAL Operating Temperature Range 32° to 104°F (0° to 40°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 20% to 90% RH, Non-Condensing Storage Humidity Range 5% to 45% RH, Non-Condensing CONNECTIONS Number of Ports 3 Side A - Connector 1 USB C (FEMALE)	Unit Weight (lbs.)	0.8	
Operating Temperature Range 32° to 104°F (0° to 40°C) Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 20% to 90% RH, Non-Condensing Storage Humidity Range 5% to 45% RH, Non-Condensing CONNECTIONS Number of Ports 3 Side A - Connector 1 USB C (FEMALE)	Unit Weight (kg)	0.36	
Storage Temperature Range -4° to 140°F (-20° to 60°C) Operating Humidity Range 20% to 90% RH, Non-Condensing Storage Humidity Range 5% to 45% RH, Non-Condensing CONNECTIONS Number of Ports 3 Side A - Connector 1 USB C (FEMALE)	ENVIRONMENTAL		
Operating Humidity Range 20% to 90% RH, Non-Condensing Storage Humidity Range 5% to 45% RH, Non-Condensing CONNECTIONS Number of Ports 3 Side A - Connector 1 USB C (FEMALE)	Operating Temperature Range	32° to 104°F (0° to 40°C)	
Storage Humidity Range 5% to 45% RH, Non-Condensing CONNECTIONS Number of Ports 3 Side A - Connector 1 USB C (FEMALE)	Storage Temperature Range	-4° to 140°F (-20° to 60°C)	
CONNECTIONS Number of Ports 3 Side A - Connector 1 USB C (FEMALE)	Operating Humidity Range	20% to 90% RH, Non-Condensing	
Number of Ports 3 Side A - Connector 1 USB C (FEMALE)	Storage Humidity Range	5% to 45% RH, Non-Condensing	
Side A - Connector 1 USB C (FEMALE)	CONNECTIONS		
	Number of Ports	3	
Side B - Connector 1 (2) USB A (FEMALE)	Side A - Connector 1	USB C (FEMALE)	
	Side B - Connector 1	(2) USB A (FEMALE)	



Connector Plating	Nickel	
Contact Plating	Nickel	
Connector Style	Straight	
FEATURES & SPECIFICATIONS		
GaN Technology	No	
Overcurrent Protection	Yes	
Overvoltage Protection	Yes	
Over Current Protection	Yes	
Quick Charge Compliant	No	
Number of USB Hub Ports	0	
Driver Required	No	
STANDARDS & COMPLIANCE		
Product Certifications	USB-IF	
Product Compliance	RoHS; CE (Europe); REACH; FCC (USA)	
WARRANTY & SUPPORT		
Product Warranty Period (Worldwide)	1-year limited warranty	



© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark. All other trademarks are the property of their respective owners.