TRIPP-LITE

Heavy-Duty USB-C to Lightning Sync/Charge Cable, MFi Certified - M/M, USB 2.0, 10 ft. (3.05 m)

MODEL NUMBER: M102-010-HD



USB/Lightning cable connects your Apple iPhone, iPad or iPod to the USB-C port on your MacBook, laptop or wall/car charger.

Features

10-ft. (3.05 m) USB-C Cable Charges and Syncs Your Latest-Generation iPhone, iPad and iPodThis USB-C sync/charge cable (M/M) connects your iPhone, iPad or iPod to the USB-C port on your MacBook Pro, Windows laptop, car charger or wall charger. It allows you to charge and power your Apple device, while simultaneously syncing and transferring image files and other personal data at USB 2.0 speeds up to 480 Mbps. The cable is backward compatible with previous USB generations, allowing you to use it with older equipment.

Heavy-Duty Aramid Fiber Construction Designed to Endure the Stress of Everyday UseThe M102-010-HD is tested to withstand over 150,000 bends without failing, thanks to its advanced bulletproof Aramid fiber construction. Its double-braided nylon exterior is also built to withstand wear and tear over a long period. The nylon braiding also resists tangles. Integral strain relief gives the cable extra flexibility, reduces stress and helps the cable move freely without cracking or breaking loose from the connectors.

Reversible C94 Lightning and USB Type-C Plugs Connect in Either DirectionThe reversible connectors plug into their respective ports in either direction for an instant connection every time. While the cable is compatible with all USB-C ports, the C94 Lightning connector is designed for optimal charging performance with Apple's 18W USB-C power adapter.

MFi-Certified for Broad Device CompatibilityThe 20V 3A (60W) Lightning cable is MFi-certified for use with the latest generation of iPhone, iPad and iPod devices.

Highlights

- Bulletproof Aramid fiber allows cable to bend over 150,000 times without failing
- MFi-certified to operate with a wide range of iPhones, iPads and iPods
- C94 Lightning connector is compatible with Apple 18W USB-C power adapter
- Durable double-braided exterior resists tangles and withstands long-term wear and tear
- Reversible plugs connect in either direction for immediate no-fuss use

Applications

- Charge and sync your Apple iPhone, iPad or iPod using the USB-C port on your computer or a wall charger up to 10 ft. away
- Transfer photos and other important files between an external hard drive and your Apple device
- Pair with an Apple 18W power adapter for optimal charging performance with an iPad Pro, iPad Air or iPhone 8 or later

System Requirements

- Computer, laptop or charger with USB-C port
- Most current iPhone, iPad and iPod devices

Package Includes

• M102-010-HD Heavy-Duty USB-C to Lightning Cable (M/M), 10 ft.

Specifications

| OVERVIEW | | |
|------------|---------------------------------|--|
| UPC Code | 037332252616 | |
| Technology | Lightning; USB 2.0 (High Speed) | |
| Cable Type | Passive | |

TRIPP-LITE

| INPUT | | |
|--|------------------------------|--|
| Maximum Input Amps | 3 | |
| POWER | | |
| USB Power Delivery (PD) Charging Support | Yes | |
| CHARGING | | |
| Total Charging Watts | 20 | |
| PHYSICAL | | |
| Material of Construction | TPE, Aramid Fiber | |
| Cable Jacket Color | Black; White | |
| Cable Jacket Material | ТРЕ | |
| Cable Jacket Rating | VW-1 | |
| Cable Outer Diameter (OD) | 5.0mm | |
| Wire Gauge (AWG) | 24/19 | |
| Cable Length (ft.) | 10 | |
| Cable Length (m) | 3.05 | |
| Cable Length (in.) | 120 | |
| Shipping Dimensions (hwd / in.) | 1.18 x 4.92 x 2.56 | |
| Shipping Weight (kg) | 0.02 | |
| Unit Packaging Type | Box | |
| ENVIRONMENTAL | | |
| Operating Temperature Range | -4° to 140°F (-20° to 60°C) | |
| Storage Temperature Range | -4° to 176°F (-20° to 80°C) | |
| Operating Humidity Range | 0% to 90% RH, Non-Condensing | |
| Storage Humidity Range | 0% to 90% RH, Non-Condensing | |
| Power Provided to Connected Device(s) | 60W (20V/3A) | |
| CONNECTIONS | | |
| Side A - Connector 1 | USB C (MALE) | |
| Side B - Connector 1 | LIGHTNING (MALE) | |
| Connector Plating | Nickel | |
| Contact Plating | Gold | |
| Connector Style | Straight | |



| FEATURES & SPECIFICATIONS | | |
|--|--------------------------|--|
| USB Specification | USB 2.0 (up to 480 Mbps) | |
| Data Transfer Rate | 480 Mbps | |
| Angled Plug | No | |
| | | |
| STANDARDS & COMPLIANCE | | |
| Product Certifications | MFi | |
| Product Compliance | RoHS; REACH; UKCA | |
| | | |
| WARRANTY & SUPPORT | | |
| Product Warranty Period (Worldwide) | 2-year limited warranty | |



© 2023 Eaton. All Rights Reserved. Eaton is a registered trademark. All other trademarks are the property of their respective owners.