

ALIENWARE 500HZ GAMING MONITOR AW2524HF



THE WORLD'S FASTEST IPS GAMING MONITOR*— NOW WITH AMD FREESYNC™ PREMIUM

ENGINEERED FOR SPEED

The AW2524HF's 500Hz (OC) / 480Hz (native) refresh rate delivers a new category of speed and motion clarity on a Fast IPS panel, making even fast-paced games look supremely fluid, giving players a competitive edge.

The display's Fast IPS panel enables a 0.5ms** GtG (gray-to-gray) response time, virtually eliminating ghosting and blurring for a clear image, even in the fastest-paced games.

And with AMD FreeSync™ Premium technology and VESA AdaptiveSync Display certification, players will experience tear- and stutter-free gaming at high speed, on any modern GPU.

QUALITY FRONT-OF-SCREEN EXPERIENCE

This speed is achieved on a Fast IPS panel that offers wider viewing angles than competing TN panels, and sRGB 99% color coverage for consistent, accurate colors.

Meanwhile, the TUV-certified ComfortView Plus Low Blue Light hardware solution reduces harmful blue light while maintaining true-to-life colors, so even marathon gaming sessions are easy on the eyes.

GAMER-CENTRIC DESIGN

The esports-inspired design features a hexagonal base for a smaller desk footprint, and a fully-adjustable stand helps players arrange their PC gaming setup for ultimate comfort and convenience.

And the ingenious retractable headset hanger keeps your gear out of the way when not in use, to achieve that appealing desk aesthetic.



*Based on internal analysis, June 2023.

** 0.5ms (GtG min), 1ms (GtG most observed) in Extreme mode.



FEATURES AND TECHNICAL SPECIFICATIONS

ALIENWARE 500HZ GAMING MONITOR AW2524HF

| | |
|--|---|
| Diagonal Viewing Size: | 62.20 cm 24.5 Inches |
| Preset Display Area (H x V) | 543.74 mm x 302.62 mm 21.40" x 11.91" 164545.63 mm² (255.04 inches²) |
| Panel Type: | Fast IPS |
| Display Screen Coating | Antiglare with 3H hardness, Haze 25% |
| Maximum Preset Resolution | 1920 X 1080 at 480Hz (Native with DP) / at 500Hz (OC with DP) 1920 X 1080 at 255Hz (Native with HDMI) |
| Viewing Angle | 178° vertical / 178° horizontal |
| Pixel Pitch | 0.2832 mm x 0.2802mm |
| Pixel Per Inch (PPI) | 90 |
| Contrast Ratio | 1000: 1 (typical) |
| Aspect Ratio | (16:9) |
| Backlight Technology | White LED edgelight system |
| Brightness | 400 cd/m² (typical) |
| Response Time(typical) | 0.5 ms (gray-to-gray min), 1ms (gray to gray most observed, in Extreme Mode) |
| Connectivity | 2 x DP 1.4 (HDCP 1.4)(Supports up to FHD 1920 x 1080 500 Hz, HDR, VRR) 1 x HDMI 2.1 (HDCP 1.4)(Supports up to FHD 1920 x 1080 255 Hz TMDs, HDR, VRR as per specified in HDMI 2.1) 1 x USB 3.2 Gen1 (5 Gbps) upstream port (Rear) 2 x USB 3.2 Gen1 (5 Gbps) Downstream port (Rear) 2 x USB 3.2 Gen1 (5 Gbps) Downstream port [including one port which supports BC1.2 power-charging] (Bottom) |
| NVIDIA® Reflex Latency Analyzer | No |
| NVIDIA® G-SYNC® | No |
| Ambient Light Sensor | No |
| AlienFX™ Lighting | No |
| Adjustability | Height adjustable stand (110 mm) and Height-markers Tilt (-5° to 21°) Swivel (-20° to 20°) Pivot (-90° to 90°) Built in cable-management |
| Low Blue Light | Yes, ComfortView Plus (TÜV Rheinland - Hardware Solution) |
| Flicker-free | Yes |
| ID color variant | Dark Side of the Moon |
| Specifications - Service / Support Details | 3-Year Advanced Exchange Service and Premium Panel Exchange |
| HDR Support | HDR 10 |
| Calibration Accuracy | Not applicable |
| Color Support | Color Gamut (typical): sRGB 99% Color Depth: 1.07 Billion colors |
| Height with stand (Compressed ~ Extended) | 390.51 mm ~500.51 mm 15.37 inches~19.71 inches |
| Width | 555.14 mm 21.86" |
| Depth | 243.71 mm 9.60 inches |
| Height without stand | 328.86 mm 12.95" |
| Width without stand | 555.14mm 21.86" |
| Depth without stand | 84.0 mm 3.31" |
| Weight (panel only - for VESA mount) | 3.65 kg 8.05 lb |
| Weight (with packaging) | 9.10 kg 20.06 lb |
| Built-in Devices | NA |
| Compliant Standards | Product Safety, EMC and Environmental Datasheets, Dell Regulatory Compliance Home Page, Dell and the Environment |
| Flat Panel Mount Interface | VESA (100 x 100 mm) |
| Temperature Range | Operating: 0° to 40°C (32° to 104°F) Non-operating: -20° to 60°C (-4° to 140° F) |
| Humidity Range | Operating: 10% to 80% (non-condensing) Non-Operating:5% to 90% (non-condensing, storage/shipping) |
| Altitude | Operating: 5,000 m (16,404 ft) max Non-Operating: 12,192 m (40,000 ft) max |
| Voltage Required | 100 VAC to 240 VAC / 50 Hz or 60 Hz + 3 Hz /1.2 A (typical) |
| Power Consumption | 0.3 W (Off Mode) 0.5 W (Standby Mode) 18.5 W (On Mode) 74 W (Max) 18 W (Pon) 58 kWh (TEC) |
| Audio Output | No |
| What's Included | Monitor, Stand riser, Stand base, Power cable (varies by country), 1 x DisplayPort to DisplayPort 1.4 cable (1.80 meters), 1 x USB-C to Display Port 1.4 cable (1.0 meter), 1 x USB 3.2 Gen1(5 Gbps) upstream cable (1.80 meters), Quick start guide, Safety, Environmental, and Regulatory Information, Alienware Sticker |

¹ComfortView Plus feature reduces blue light emission and optimizes eye comfort without compromising color accuracy. ²Advanced Exchange Service: Replacement part/unit dispatched, if needed, following completion of phone/online diagnosis. Fee charged for failure to return defective unit. Availability varies. Other conditions apply.³For a copy of the Limited Hardware Warranty, write Dell USA LP, Attn: Warranties, One Dell Way, Round Rock, TX 78682 or see Dell.com/warranty.

Copyright 2022 Dell Inc. All rights reserved. Other trademarks or trade names may be used in this document to refer to either the entities claiming the marks and names or their products. Dell disclaims proprietary interest in the marks and names of others. Reproduction in any manner whatsoever without express written permission from Dell Inc. is strictly forbidden.