

DELL 86 4K INTERACTIVE TOUCH MONITOR | C8621QT

A touch above the rest.



REAL TIME TEAMWORK

Vast 85.6" 4K display with responsive technology improves collaboration. Features up to 20-point touch, dual-tip stylus and integrated speakers.



CONVENIENT CONNECTIVITY, SETUP AND MANAGEMENT

Comprehensive connectivity options including USB-C, easy installation and network manageability.



EXCLUSIVE TO DELL. INCLUSIVE FOR ALL.

Exclusive Dell Screen Drop feature, designed to improve reachability for users working from different heights.



TRUSTED RELIABILITY

Dell monitors — World's number 1 monitor company*, backed by renown reliability.

A touch above the rest.



BRILLIANT PERFORMANCE

Captivate audiences: Experience brilliant presentations on this impressive 85.6" screen with 4K UHD resolution. Expect consistent image quality from virtually anywhere in the room, thanks to the wide viewing angle enabled by In-Plane Switching (IPS) technology. Plus, built in 2x20W speakers deliver great sound for video and audio playback.

Striking clarity: Dell monitor technology optimizes fonts so visuals appear sharp and text is crisp while anti-glare and anti-smudge coatings reduce distracting reflections and fingerprints.

Easy on the eyes: Dell ComfortView reduces blue light emission to optimize eye comfort.



REAL TIME TEAMWORK

Instant engagement: With InGlass™ 20-point touch capability, multiple users can interact with the screen at the same time.

Natural touch: Annotate with your fingers, write with a stylus, or even erase written content with the palm of your hand — with virtually zero lag.

Improved stylus: Mimicking a more natural writing tool, the included stylus has an ergonomic, easy-grip design, a fine writing tip and a precise eraser.¹ It also magnetically attaches to the side of the display for safekeeping.

Co-create content: Touch functionality is compatible with most industry-standard software, such as included FlatFrog Board collaboration software.



INCLUSIVE FOR ALL

Exclusive Dell Screen Drop: Improve reachability for users of different heights using Dell Screen Drop, the world's first accessibility feature**. Buttons at the side of the panel enable users to lower the displayed images to 3 different height settings so it's within easy reach.



SEAMLESS DESIGN

The power of USB-C: Get up to 90W of power delivery so you can charge your connected laptop and enjoy uninterrupted productivity.

All-in-one convenience: Seamlessly integrate an optional Dell OptiPlex Micro PC into the back panel and easily upload your preferred corporate image for a display solution that adheres to your company's security and service standards.

Simplify IT management: IT can solve issues and manage the display remotely thanks to a range of tools, including RS232, RJ45, HDMI CEC ports and the TCP/IP command set.



TRUSTED RELIABILITY

Minimize downtime: Your monitor comes with a 3-year Advanced Exchange Service² so that if a replacement becomes necessary, it will be shipped to you the next business day during your 3-year Limited Hardware Warranty.³ You can also extend your coverage up to 5 years.


Get a higher level of support: Upgrade to 24x7, in-region technical phone support from qualified engineers with the ProSupport option.⁴

Features & Technical Specifications

Monitor	Dell 86 4K Interactive Touch Monitor – C8621QT	What's in the box? Components <ul style="list-style-type: none">• Monitor• 1 x Remote control with holder• 2 x Dual-tip passive styluses• 2 x Passive stylus nibs (2.8mm writing tips)• 3 x Cable clips• 1 x OptiPlex Micro Holder• 2 x AAA Batteries Software <ul style="list-style-type: none">• FlatFrog software Cables <ul style="list-style-type: none">• 1 x Power cord (varies by country)• 1 x Power cable for connecting an optional OptiPlex system to the display (1 meter)• 1 x USB 3.1 upstream cable (3 meter)• 1 x DP cable (DP to DP) (3 meter)• 1 x HDMI cable (3 meter)• 1 x USB Type-C cable (1.8 meter) Documentation <ul style="list-style-type: none">• FlatFrog software download instruction• Safety, Environmental and Regulatory Information• Quick Setup Guide
Diagonal Viewing Size	217.4 cm (85.6 inch)	
Maximum Resolution	3840 x 2160 at 60 Hz	
Aspect Ratio	16:9	
Pixel Pitch	0.4935 mm x 0.4935 mm	
Brightness	350 cd/m ² (typical)	
Color Support	Color Gamut (typical): NTSC 72% (CIE 1931) Color Depth: 1.07 billion colors	
Contrast Ratio	1200:1 (typical)	
Viewing Angle (Vertical/Horizontal)	178°/178°	
Response Time	8 ms typical (Gray to Gray)	
Touch Technology	FlatFrog InGlass™	
Panel Technology	IPS	
Backlight Technology	LED light bar system (edge light system)	
Surface Treatment	Anti-Smudge, Anti-Glare	
Dell Display Manager Compatibility	Yes; includes Easy Arrange and Auto Restore features	
ComfortView	Yes	
Connectivity		
Connectors	1 x DP 1.2 1 x USB Type-C (Alternate mode with DisplayPort 1.2, Power Delivery PD up to 90 W) 4 x HDMI 2.0 3 x USB 3.1 downstream port 1 x USB BC1.2 charging port at 2A (max) 3 x USB 3.1 upstream port 1 x Analog 2.0 audio line out (3.5 mm jack) 1 x RJ45 1 x RS232	
Remote Asset Management	1 x RS232 1 x RJ45 (TCP-IP Command Set, Crestron Roomview Express Certified)	
Design features		
Security	Lock Mode for menu and power settings Security lock slot for OptiPlex Micro Holder (security lock and OptiPlex Micro not included)	
Speakers	Integrated speakers (20W x 2)	
VESA Mounting Support	600 x 400 mm	
Power		
AC input voltage/frequency/current	100-240 VAC / 50 or 60 Hz ± 3 Hz / 7.0 A (max)	
Power Consumption (typical to maximum)	175W - 430W	
Duty Cycle	12/7 (typical)	
Dimensions		
Height	1156.63 mm (45.54 inches)	
Width	1982.64 mm (78.06 inches)	
Depth	82.8 mm (3.26 inches)	
Weight		
Weight (panel only)	86.5 kg (190.7 lb)	
Shipping Weight	114.5 kg (252.43 lb)	
Standard Service Plan	3 Years Advanced Exchange Service ³ & Limited Hardware Warranty ⁴ ; optional ProSupport	
Environmental Compliance	ENERGY STAR®, UL certified, China Energy Label (CEL), WEEE, ErP (EuP) Standards, Mercury-free for the panel only	

Connectivity and Accessories

DELL 86 4K INTERACTIVE TOUCH MONITOR | C8621QT



- | | | |
|-------------------------------|-------------------------------|---|
| 1 HDMI 2.0 x 4 | 5 USB 3.1 Upstream x 3 | 9 RJ45 |
| 2 DisplayPort 1.2 | 6 USB 3.1 Downstream x 3 | 10 OptiPlex Micro Holder (OptiPlex not included) |
| 3 USB Type-C | 7 USB Dedicated Charging Port | 11 Security lock slot for the OptiPlex Micro Holder |
| 4 Audio line-out ⁵ | 8 RS232 | |

RECOMMENDED ACCESSORIES



DELL OPTIPLEX 7070 MICRO PC WITH OPTIONAL INTEL UNITE[®]



X-LARGE FUSION MICRO-ADJUSTABLE FIXED WALL DISPLAY MOUNT | XSM1U



X-LARGE FUSION MANUAL HEIGHT ADJUSTABLE CART | XPA1UB



CHIEF X-LARGE FUSION FLOOR STAND | XFA1UB



LOGITECH RALLY PLUS



ACTIONTEC SCREENBEAM ENTERPRISE 960

* Dell monitors are #1 Worldwide for 6 consecutive years (2013 to 2019)! Source: IDC Worldwide Quarterly PC Monitor Tracker, Q3 2019.

** Based on Dell internal analysis, November 2018. Available on C8621QT, C7520QT and C5518QT monitors only.

1 Two passive styluses included. Functionality depends on the software used.

2 Advanced Exchange: Dell will send you a replacement monitor the next business day in most cases, if deemed necessary after phone/online diagnosis. Shipping times may vary by location and for monitors 55" and above. Fee charged for failure to return defective unit. See dell.com/servicecontracts/global.

3 For a copy of the Limited Hardware Warranty, write Dell USA LP, Attn: Warranties, One Dell Way, Round Rock, TX 78682 or see Dell.com/warranty.

4 Availability varies, please visit www.dell.com/support for details.

5 The audio line-out port does not support headphones.

Dell.com/largeformatmonitors

Product availability varies by country. Please contact your Dell representative for more information.

© 2020 Dell Inc. All rights reserved.

Trademarks or trade names may be used in this document to refer to either the entities claiming the marks and names of their products. Dell disclaims proprietary interest in the marks and names of others. Reproduction in any manner whatsoever without express written permission from Dell is strictly forbidden.

