



Optimise your view with the world's first InfinityEdge monitor


The ultimate viewing experience

Marvel at this superb view that seems to go on forever.

- Maximise your view on the world's first InfinityEdge monitor with super thin borders on all four sides.
- See accurate colours with 99% sRGB colour coverage at deltaE<2 right out of the box.
- Consistent colours across a wide 178°/178° viewing angle.

U2414H


Screen border + bezel: 6.1 mm (L/R/U)



Screen border plus – traditional plastic chin: 18.6 mm

U2417H (InfinityEdge)

Screen border + bezel: 5.3 mm (L/R/U)



Screen border only -no plastic chin: 8.3 mm

With Dell's 24" InfinityEdge monitor you enjoy an almost borderless view without the traditional plastic bezel on the bottom or sides, opening up the expanse of usable screen space.

Outstanding usability

Excellent connectivity and flexible viewing options, making it easy to use and simple to set up a nearly seamless dual monitor view.

- Further enhance your view with an almost seamless multi-monitor setup thanks to the super thin black borders on all 4 sides.
- Easy multi-monitor setup via DisplayPort-out.
- Flexible viewing options including height adjustable stand with swivel, pivot to portrait, and tilt features.
- Choice of digital connectivity options through HDMI/ MHL or mini-DisplayPort/ DisplayPort⁴.
- Connect multiple devices through four USB 3.0 ports.

Unmatched reliability

Comes with Dell's high reliability promise.

- Enjoy peace of mind with Dell's Premium Panel Guarantee¹.
- Minimise downtime with up to 3 years 24x7 support and Advanced Exchange Service with optional Dell ProSupport.²
- Enjoy high reliability from the #1 monitor brand worldwide for two consecutive years*.

For more information visit www.dell.com/monitors

Thank you for making Dell Monitors
#1
worldwide*

Easily adjust the panel to your preferred viewing position to work the way you like.







Pivot clockwise and counter-clockwise

Connectors



- A AC Power
- В HDMI/MHL
- DisplayPort (in)
- Mini DisplayPort
- E DisplayPort (out)
- Audio line-out
- **G** USB upstream
- **H** USB downstream



What's in the box?

Components

- Monitor panel
- Stand

- Power cable (varies by country)
- Mini-DisplayPort to DisplayPort
- USB 3.0 upstream

Documentation

- Factory colour calibration report
- Drivers and documentation media (CD)
- Quick Setup Guide
- · Safety and regulatory information

Dell recommends that customers dispose used computer hardware, including monitors, in an environmentally sound manner. Potential methods include reuse of parts or whole products and recycling of product, components and/or materials. For more information, please visit http://dell.com/recycling_programs and www.dell.com/environment







Dell UltraSharp 24 InfinityEdge Monitor | U2417H

Display	
Model number	U2417H
Viewable image size (diagonal)	60.47 cm (23.8 inches)
Active display area Horizontal Vertical	527.04 mm (20.75 inches) 296.46 mm (11.67 inches)
Maximum resolution	Full HD 1920 x 1080 at 60 Hz
Aspect ratio	16:9
Pixel pitch	0.2745 mm x 0.2745 mm
Brightness (typical)	250 cd/m ²
Colour gamut (typical)	91%³ (CIE1976), 99% sRGB (delta E <2)
Colour depth	16.7 million colours
Contrast ratio (typical)	1000:1
Viewing angle (typical) (vertical/horizontal)	178° / 178°
Response time (typical)	Fast mode: 6 ms gray-to-gray (typical) Normal mode: 8 ms gray-to-gray (typical)
Panel technology	In-plane switching, anti-glare with hard coat 3H
Backlight	LED
Connectivity	
Connectors	HDMI 1.4 (MHL 2.0), Mini DisplayPort1.2/ DisplayPort 1.2 ⁴ , DisplayPort out (MST), Audio Line out, 5 x USB 3.0 ports (1 upstream, 4 downstream)
Design features	
Stand	Height-adjustable stand, tilt (typical: 5° forward or 21° backward), pivot (clockwise and counterclockwise), swivel and built in cable-management
VESA mounting support (wall mount kit sold separately)	Dell Quick Release feature (100 mm x 100 mm)
Security	Security lock slot (security lock not included)
Power	
AC input voltage/frequency/current	100 to 240 VAC/50 or 60 Hz ± 3 Hz/1.6 A (maximum)
Power consumption (typical)	19W
Power consumption (ENERGY STAR®)	16.93W
Power consumption standby/sleep mode	<0.5 W
Dimensions (with stand)	
Height (compressed ~ extended)	355.3 mm (13.99 inches) ~ 485.3 mm (19.11 inches)
Width	537.6 mm (21.17 inches)
Depth	188 mm (7.40 inches)
Weight	
Weight (panel only – no stand)	3.18 kg (7.01 lb)
Weight (with stand)	6.30 kg (13.89 lb)
Shipping weight	7.35 kg (16.20 lb)
Standard service plan Up to 3 years 24x7 support and Advanced Exchange Service with optional Dell ProSupport ² & 3 Years Limited Hardware Warranty ⁵ Premium Panel Guarantee ¹	Environmental compliance ENERGY STAR®, EPEAT® Gold®, TCO Certified Displays, China Energy Label, RoHS, WEEE, ErP (EuP) Standards, Korea E-Standby

*Dell monitors are #1 Worldwide for 2 consecutive years. Source: NPD DisplaySearch Quarterly Desktop Monitor Shipment and Forecast Report (2013 and 2014). Ad#G15000115

** Registered in US and Canada only.

**For charging BC1.2 devices and also supports up to 2A when powering standard USB devices.

¹ In the event you discover even one bright pixel during the Limited Hardware Warranty period, a free panel exchange is guaranteed. (see pixel panel info located on Dell.com web page for complete details):

http://support.dell.com/support/topics/global.aspx/support/kcs/document?docid=414288

² lincludes 24X in-region phone support and replacement monitor shipped to you the next business day.

³ Colour gamut (typical) is based on CIE1976 (91x) and CIE1931 (76%) test standards.

³ Colour gamut (typical) is based on CIE1976 (91x) and CIE1931 (76%) test standards.

³ Solour gamut (typical) is based on CIE1976 (91x) and CIE1931 (76%) test standards.

³ Solour gamut (typical) is based on CIE1976 (91x) and CIE1931 (76%) test standards.

³ Colour gamut (typical) is based on CIE1976 (91x) and CIE1931 (76%) test standards.

³ Colour gamut (typical) is based on CIE1976 (91x) and CIE1931 (76%) test standards.

³ Colour gamut (typical) is based on CIE1976 (91x) and CIE1931 (76%) test standards.

³ Colour gamut (typical) is based on CIE1976 (91x) and CIE1931 (76%) test standards.

³ Colour gamut (typical) is based on CIE1976 (91x) and CIE1931 (76%) test standards.

³ Colour gamut (typical) is based on CIE1976 (91x) and CIE1931 (76%) test standards.

³ Colour gamut (typical) is based on CIE1976 (91x) and CIE1931 (76%) test standards.

³ Colour gamut (typical) is based on CIE1976 (91x) and CIE1931 (76%) test standards.

³ Colour gamut (typical) is based on CIE1976 (91x) and CIE1931 (76%) test standards.

³ Colour gamut (typical) is based on CIE1936 (91x) and CIE1931 (76%) test standards.

³ Colour gamut (typical) is based on CIE1936 (91x) and CIE1931 (76%) test standards.

³ Colour gamut (typical) is based on CIE1936 (91x) and CIE19