

Intermec PR2 (PR2A380310021)

Direct thermal, 203 dpi, 76.2 mm/sec, WLAN ETSI, USB, Smart Battery, Power Supply



Price details:

Price excl. VAT: 509.48 €

Eco fees: 0.12 €

VAT 21 %: 107.02 €

Product details:

Product code: PR2A380310021

EAN:

Manufacturer: Intermec

616.62 €

* VAT included

PDF generated on: 8 September, 2014



Product Overview

PR2/PR3 durable mobile receipt printers are ideal for invoice printing and secure-payment capture capabilities within the direct store delivery, field service, mobile point of sale, and electronic-citation markets.

Fit - Fits Your Work Environment for Increased Efficiencies and Uptime

- Smallest, lightest and most durable in its class
- Simple and intuitive LED user interface
- Only printer to offer optional, integrated, PCI-compatible MSR, with AES encryption

Flexible - Minimizes Your Ownership Costs for Lower TCO

- Industry-first remote management and health monitoring
- Modular accessories shared with Intermec mobile computers provide battery charging on board, or external to the printer
- Compatible with the Intermec FlexDock Modular Docking System for mobile computers and devices
- Secure Bluetooth® 2.0, 802.11 b/g, USB and IrDA connectivity options

Fast - Keeps Your Teams Productive

- Fastest time to first receipt in its class
- Simple drop-in media loading
- Easiest to integrate and deploy, with all common printer languages standard

Main specifications:

Print technology

Type:	Mobile
Print technology:	Direct thermal / Thermal transfer
Print speed:	76.2 mm/sec

Technical details

Size:	2 "
Built-in barcodes:	1D, 2D, Code 39, EAN128, EAN13, EAN8, PDF417, UPC-A
Colour of product:	Grey
Maximum printing width:	48 mm

Ports & interfaces

Connectivity technology:	Wired & Wireless
USB 2.0 ports quantity:	1
Standard interfaces:	USB

Weight & dimensions

Dimensions (WxDxH):	103.23 x 138.58 x 60.96 mm
Weight:	309 g
Power	
Battery technology:	Lithium-Ion (Li-Ion)
Battery recharge time:	4 h
Battery voltage:	7.4 V
Operational conditions	
Operating temperature (T-T):	-10 - 50 °C
Storage temperature (T-T):	-20 - 60 °C
Operating relative humidity (H-H):	20 - 85 %
Storage relative humidity (H-H):	5 - 95 %
Print quality	
Maximum resolution:	203 DPI
Memory	
Flash memory:	64 MB
Internal memory:	16 MB
Networking	
Ethernet LAN:	N
Wi-Fi:	Y

*PLEASE NOTE: Every effort has been made to ensure the accuracy of all information contained herein. Lasystems makes no warranty expressed or implied with respect to accuracy of the information, including price, editorials or specifications. Lasystems or its suppliers shall not be liable for incidental, consequential or special damages arising from, or as a result of, any electronic transmission or the accuracy of the information contained herein, even if Lasystems has been advised of the possibility of such damages. Product and manufacturer names are used only for the purpose of identification.