ThinkCentre Tiny-In-One 22 Gen 4 11GTPAT1EU

Product ThinkCentre TIO22Gen4Touch

Region RUCIS

Machine Type 11GT

Color Black

Display Size 21.5"

Touchscreen 10-point Multi-touch

Resolution 1920x1080

Aspect Ratio 16:9

Pixel Pitch 0.24795mm

Dot / Pixel Per Inch 102.4 dpi

Brightness 250 nits

Contrast Ratio 1000:1

Pixel Response Time 4-14 ms **Color Gamut** 72%

View Angle (H / V) 178 / 178

Stand Adjustable Stand

Camera 720p

Power Comsuption (Typical / Maximum) 14W / 25W

Power Supply 90W 88% Adapter

Base Warranty 3-year

Ann Date (mm/yy) 2020-06-09

L WWW.LENOVO.COM

Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors.

Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.

https://psref.lenovo.com

PSREF

Visit psref website for the latest version of Product specifications Reference. © Lenovo, 2020. All rights reserved.



ThinkCentre Tiny-In-One 22 Gen 4 Platform Specifications

Product Specifications Reference (PSREF)

Form factor	Tiny-in-One, offers the back of TIO, cle	ience when optional Tiny slots into	Mounting feat	ures	Wall or desk mounting using the extend arm or third-party accessories meeting the VESA FPMPMI® (100mm mount)			
Compatible Tiny:	P340 / P330 / P320 / M90q / M80q / M70q / M75q / M920(x) / M720 /			Adjustable sta	and	<i>Tilt:</i> 30° back, -5° forward;		
	M910(x) / M710 / M715 / M900(x) / M700 / M630e / M625 / M600 Tiny M90n / M75n Nano (with TIO kit)					<i>lift:</i> 5.9" (150mm); <i>swivel:</i> +/-45°:		
						<i>Pivot:</i> clockwise -5° to 90°		
Panel	TFT-LCD, In-Plane Switching technology**, White LED backlight Notes: In-Plane Switching may refer to IPS, PLS, ADS, AHVA, AAS panels 21.5" (546.1mm) diagonal 18.74" x 10.54" / 476.1mm x 267.8mm			Power supply 90 watts AC/DC adapter, 88% PSU, universal				
Viewable image size				Power consumption 25 watts max, 14 watts typical, <0.5 watts standby / suspend				
Max view area (W x H)				Limited warra	·)	3-years, Carry-In or Courier service		
Bezel Width Native resolution	Top / Side: 2mm, Bottom: 22.1mm 1920x1080 @60Hz			Environmental TCO 8.0, TCO edge 2.0, ENERGY STAR [®] 8.0, EPEAT™ Silver rating, UL GREENGUARD Certified, Erp lot5, WEEE, RoHS, TUV Eye comfort				
Presets / user settings	25			Windows cert				
Nulti-touch	Optional 10-point multi-touch, AIT technology			Ship group		TIO (Monitor), detachable stand, power adapter, power cord, information		
Aspect ratio Pixel pitch (mm)	16:9 0.24795mm			flyer, user's guide, and driver CD				
Dot/Pixel pèr Inch	102.4 dpi			Accessories		For compatible accessories, please go to http://www.lenovoquickpick.com		
Brightness Contrast ratio	250 nits or cd/m ² (t 1000:1 (typical)	ypical)						
Pixel response time	14ms (default), over drive to 4ms, 6ms			ThinkCentre Tiny-In-One 22 Gen 4 Compatible list				
Color gamut	72% NTSC (ĆIE 1931)		Model	1	P340 / P330 / P320	M93/p / M83 /	Chromebox	
Anti-reflective Anti-glare /iewing angle at 10:1 CR178° (+/- 89°) horizontal, 178° (+/- 89°) vertical			Moder		M90q / M80q / M70q / M75q / M920(x) /	M73 / M53	Onioniobox	
On screen display	On screen display with digital user controls (8 languages)				M720 / M910(x) / M710 / M715 / M900(x) /	Tiny		
Control features	Ftont: Exit button, Up / Mode-switching button (TIO / monitor mode switchs the sources of both display and side USB port),					M700 / M630e / M625 / M600 Tiny	-	
						M90n / M75n (with TIO kit)		
	Down / Brightness button, Enter / Menu button, Power button Bottom: Volume up button, Volume down button			Turn on TI				
TIO Power On features	Pressing Alt + P (on keyboard) or Power button (on TIO) can turn on both TIO and Tiny (some old Tiny cannot fully support, see compatible list) One USB Type A port (The availability and version depends on the Tiny istalled or the PC connected via USB upstream port) Side ports offered by installed Tiny (front ports)			Tiny toget		All models	All models	Not support
				Alt + P on				
Side ports (on TIO)				Turn on TI			Net even ext	
Side ports (on Tiny)				Tiny toget		All models	Not support	All models
Rear ports	One DisplayPort in port, one USB upstream port, one power connector				Dutton			
3-in-1 Cable	Undetachable 3-in-1 cable (Power connecter, USB [supports USB 3.1 Gen1 / USB 2.0], DisplayPort), only for connecting to Tiny installed (optional)							
Camera	720p camera with dual microphone and Think Shutter							
Internal Speaker	2 watt x2							
Security	Security keyhole for attachment of optional cable lock (Kensington® lock							
	compatible), locks optional Tiny with TIO together, more security features offered by Tiny installed (optional)							
Mechanical	, ,	TIO without stand	TIO with stand					
	Dimensions							
	W x D x H (inch)		19.26 x 8.68 x 16.46 - 22.37.93					
	W x D x H (mm)	489.3 x 65.3 x 339	489.3 x 220.4 x 418.2 - 568.2					
	Weight (Approx.)	7.52 lb / 3.41 kg	14.51 lb / 6.58 kg					

Lenovo, May 2020

ThinkCentre Tiny-In-One 22 Gen 4









(intel) inside