Lenovo

ThinkSmart Core for Zoom 11LT0006EU

Product

ThinkSmart Core + Controller Kit

Region

EET

Country/Region

Hungary

Machine Type

11LT

TopSeller

TopSeller

Processor

Intel Core i5-1145G7E (4C / 8T, 1.5 / 4.1GHz, 8MB)

Graphics

Integrated Intel Iris Xe Graphics

Chipset

Intel SoC Platform

Memory

8GB Soldered DDR4-3200

Storage

256GB SSD M.2 2280 PCIe 3.0x4 NVMe

Display

10.1" Display on ThinkSmart Touch Controller

Touchscreen

10-point Multi-touch

Remote Control

ThinkSmart Touch Controller

Camera

None

Microphone

None

Speakers

None

Ethernet

Integrated 100/1000M

WLAN + Bluetooth

Intel AX201 11ax, 2x2 + BT5.0, vPro

VESA Mount

Integrated VESA Mount

Case Color

Black case with red bottom

Power Supply

90W 89% Adapter

System Management

Intel vPro

Operating System

Windows 10 IoT Enterprise SAC 64, English

Base Warranty

3-year, Onsite

Included Upgrade

First Year Maintenance (5MS0Z44663), 3Y Premier Support Upgrade from 3Y Onsite (5WS0Y57697)

EAN/UPC/JAN

0196119604205

End of Support

N/A

Announce Date

2021-11-02

Recommended Services

Best

4Y Premier Support upgrade from 3Y Premier Support (5WS0Z53125)

Better

5Y Premier Support upgrade from 3Y Premier Support (5WS0Z53126)

Good

First Year Maintenance (5MS0Z44663)

WWW.LENOVO.COM

Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a particular purpose.



https://psref.lenovo.com

Visit psref website for the latest version of Product specifications Reference.
© Lenovo, 2022. All rights reserved.

ThinkSmart Core for Zoom Platform Specifications

| ThinkSmart Core | | ThinkSmart Core | ThinkSmart Core | ThinkSmart | | ThinkSmart Controller (for MT 11LS / 11LT / 11S4 / 11S5) |
|------------------------|--|--|-----------------------|---------------------|------------------------------------|---|
| Kit Options | | Full Room Kit | + Controller Kit | Core Generic | Display Multi-touch Sensors Ports | 10.1" (1280x800), < 340 nits, 16:10 aspect ratio, Anti-Fingerprint, Anti-Glare, support 30° or 60° placement Supports 10-point touch IR sensors for motion detection, up to 3 meters distance and 90° angle 1x USB-C (connect to compute unit, 10m USB-C cable incluided) 1x 3.5mm headphone / mic combo jack, 1x Kensington Security Slot |
| | ThinkSmart Core | 1x | 1x | 1x | | |
| | ThinkSmart Controller | 1x | 1x | None | | |
| | ThinkSmart Cam | 1x | None | None | | |
| | ThinkSmart Bar | 1x | None | None | Dimensions | • Width: 265.5 mm (10.5 inches) |
| | Satellite Microphone | 2x (optional) | None | None | | Height: 168.1 mm (6.6 inches) Depth: 13 mm (0.5 inches) 83.3 mm (3.3 inches) with the stand |
| Color | Raven black case with red bottom | | | | Weight | 753.8 g (1.7 lb) |
| Base Warranty | Some: 3-year Lenovo Pre | | ty | | | ThinkSmart Cam (for MT 11S4 / 11S5) |
| | Some: 3-year limited onsite warranty Compute System (for MT 11LS / 11LT / 11S4 / 11S5 / 11RW) | | | | Image | 8MP 1/1.8" CMOS sensor, up to 1080p@30fps video capture, digital PTZ (Pan / |
| Processor | Compute System (for line 11th Gen Intel® Core™ i5 | | 94 / 1195 / 11RW) | | Option | Tilt / Zoom) 100° Horizontal FoV, 68° Vertical FoV, 125° Diagonal FoV |
| Processor | Coros | c / Eroguepov | Memory Support | Integrated | Optics At features | 100° Horizontal FoV, 68° Vertical FoV, 125° Diagonal FoV |
| | | ds Base/Max(GHz) | ache (Up to) | Graphics | Al features | Auto Zoom/Frame, Speaker Tracking, Whiteboard Recognition, People Count |
| | Core i5-1145G7E 4 / 8 | 1 | 3 MB DDR4-3200 | Intel Iris® Xe | Microphone | 2x digital microphone |
| | | | 14-9200 | Graphics | Ports | 1x USB-C (connect to ThinkSmart Core compute unit) |
| Memory | 8GB DDR4-3200, dual-channel | | | | Mounting | Wall mount kit, TV mount kit, and magnetically mount on ThinkSmart Bar |
| Storage | 256GB M.2 SSD (2280) | · · · · · · · · · · · · · · · · · · · | .0 x4 | | Dimensions | Width: 105 mm (4.1 inches) Height: 36 mm (1.4 inches), 51.7 mm (2 inches) with clamp |
| Chipset | Intel SoC (System on Chip) platform | | | | | • Depth: 60.5 mm (2.4 inches) |
| Front Ports* | None | | | | Weight | 220 g (0.5 lb) |
| Rear Ports* | 2x USB 3.2 Gen 2 (One 1x USB 3.2 Gen1 | e for ThinkSamrt Bar, | one for ThinkSmart Ca | am) | | ThinkSmart Bar (for MT 11S4 / 11S5) |
| | 1x Thunderbolt™ 4 1x USB-C 3.2 Gen 1 (connect to ThinkSmart Controller) | | | | Speaker | Power output 20+20W with 4 speaker units, up to 97dB to cover large meeting room, 250 Hz to 20 KHz frequency range |
| | | | | | Microphone | 4 forming mic array with 180° coverage, 300Hz to 8KHz frequency range |
| | | | | | Noise Control | Built-in DSP for echo and noise-cancellation |
| | | | | | Ports | 1x USB-C (USB 2.0, connect to ThinkSmart Core compute unit) 1x AUX in (connect to Mic Pod) |
| WLAN | 11ac wireless, M.2 Card, Intel Wireless-AC 9560 (dual band), Wi-Fi + Bluetooth 5.0 combo adapter, Intel vPro technology support, 2x2 Bluetooth 5.0 wireless, integrated in Wi-Fi + Bluetooth combo adapter | | | | Bluetooth | Bluetooth 5.0 (A2DP, SBC, MPEG-4, AAC) |
| | | | | | Mounting | Wall / Monitor mount kit |
| Bluetooth Ethernet | Bluetooth 5.0 wireless, in Gigabit ethernet, Intel Etl | ntegrated in Wi-Fi + Bl | uetooth combo adapto | er Wake on I AN® | Dimensions | • Width: 798 mm (31.4 inches) |
| Manageability | | Intel Active Management Technology 15.0 (Intel AMT 15.0) | | | 1 | Height: 56.5 mm (2.2 inches) Depth: 91.3 mm (3.6 inches) |
| Security chip | Discrete TPM 2.0, TCG Certified | | | | Weight | • Deptn: 91.3 mm (3.6 inches) 3.6 kg (7.9 lb) |
| Security features | Kensington Security Slot the cable connection | ot, with the integrated | cable management, c | can also secure | Jigi it | Satellite Microphone (optional for MT 11S4 / 11S5) |
| | Power-on, Supervisor, hard disk password | | | | Capturing Rang | ge 1m 360 degree omni direction |
| Power seem! | Smart USB Protection watts adapter, 100V - 240V autosensing, 89% PSU | | | | Ports | 1x Mic out (connect to ThinkSmart Bar) |
| | | 240v autosensing, 8: | 970 POU | | | 1x Mic in (connect to next Mic Pod) |
| Mounting Dimensions | • Width: 226 mm (8.9 incl | has | | | Dimensions | Width: 100 mm (3.9 inches) Height: 20 mm (0.8 inches) |
| Dimensions | Height: 37.5 mm (1.5 inches) Depth: 200 mm (7.9 inches) | | | | Weight | 220 g (0.5 lb) |
| Weight | 1.1 kg (2.4 lb) | • | | | 1 | |
| | Windows 10 IoT Enterpri | se SAC 64 bit | | | 1 | |
| Operating System | | | | | | |

See footnotes for more detailed information

Lenovo, May 2022