Lenovo

Google Meet Series one Room Kits by Lenovo Gen 2 20YW0007CK

Product

Google Meet Series One Room Kits Gen 2(Medium Kit)

Region

EET

Country/Region

Czech, Slovakia

Machine Type

20YW

TopSeller

TopSeller

Processor

Intel Core i7-10510U (4C / 8T, 1.8 / 4.9GHz, 8MB)

Graphics

Integrated Intel UHD Graphics

Chipset

Intel SoC Platform

Memory

2x 4GB SO-DIMM DDR4-3200

Storage

128GB SSD M.2 2280 SATA6Gb/s

Display

10.1" Touch Controller, Charcoal

Touchscreen

2-point Multi-touch

Remote Control

None

Camera

Smart Camera, Black

Microphone

1x Mic Pod, Charcoal

Speakers

1x Smart Audio Bar, Charcoal

Ethernet

Integrated 100/1000M

WLAN + Bluetooth

Intel AX201 11ax, 2x2 + BT5.0

Case Color

Charcoal

Power Supply

240W adapter

Operating System

Chrome OS

Base Warranty

3-year Premier Support

Included Upgrade

3Y Premier Support Courier/CCI Upgrade from 3Y Courier/CCI (5WS0T24669)

EAN/UPC/JAN

0196118441160

End of Support

2028-04-07

Announce Date

2021-12-13

WWW.LENOVO.COM

Lenovo may not offer the products, services or features discussed in this document in other countries. Lenovo may withdraw an offering at any time. Information is subject to change without notice. Consult your local representative for information on offerings available in your area.

Lenovo reserves the right to change specifications or other product information without notice. Lenovo is not responsible for photographic or typographical errors. Lenovo provides this publication "as is" without warranty of any kind, either express or implied, including the implied warranties of merchantability or fitness for a



particular purpose.

https://psref.lenovo.com

Visit psref website for the latest version of Product specifications Reference.
© Lenovo, 2022. All rights reserved.



Google Meet Series One Room Kits by Lenovo Gen 2 Platform Specifications

Room Kit Options				1	1	1	Smart Camera
noon kii Options		Small Room Kit	Medium Room K	t Large	e Room Kit	Image	12 MP 1/2.3" CMOS sensor, up to 1080p@30fps video capture, f/2.8 aperture
	Compute System	1x	1x		1x	Optics	Ultra-wide angle glass optics, 120° horizontal field of view
	Camera	Smart Camera	Smart Camera	Smart	Camera XL	Microphone	Omnidirectional microphone
				-		Ports	1x RJ-45 Ethernet (PoE, connect to Compute System)
	Audio Bar	Smart Audio Bar	Smart Audio Bar		: Audio Bar + n Audio Bar	Mounting	Wall mount kit, TV mount kit, and magnetic dock
						Dimensions	(LxWxH) 84 x 107 x 42 mm
	Controller	Remote Control	Touch Controller	Touch	Controller	2/110/10/01/0	Audio Bar
	Mic Pod	None	1x		2x		Smart Audio Bar
Color	Chalk or Charcoal					Speaker	20W RMS power, 80Hz-24kHz frequency response
Base Warranty	3-year Lenovo Premier Support warranty					Microphone	8 element, linear beamforming array, 100Hz-24kHz pickup, optimal pickup range of
	Compute System					1	up to 4m
Processor	10th Gen Intel Core™ i7 Processor					Noise Control	AEC, ANC, and TrueVoice™ multi-channel noise cancellation (via onboard Google
	Processor Co	ores / Frequency reads Base/Max(GHz		Support to)	Integrated Graphics	Ports	Edge TPUs) 1x USB-C with USB 2.0 UAC (only for audio out) 1x decreases and a RCA substitute (for accieting listening decrease)
	Core i7-10510U 4	4 / 8 1.8G / 4.9G	8 MB DDR4-2666		Intel UHD	1	1x stereo analog RCA output (for assistive listening devices) 1x RJ-45 Ethernet (PoE, connect to Compute System)
TPU	Two Google Edge TPUs via M.2 slot, provides AI and machine learning capability to maximize audio and video quality				ng capability	1	2x RJ-45 Daisy Chain Ports (PoE like, connect to Add-on Audio Bar and Mic Pod)
						Mounting	Wall mount kit
,	8GB DDR4-3200* * Installed memory run at 2666MHz due to conshility of processor					Dimensions	(LxWxH) 95 x 705 x 133 mm
	* Installed memory run at 2666MHz due to capability of processor					-	Add-on Audio Bar
	128GB M.2 2280 SSD					Speaker	20W RMS power, 80Hz-24kHz frequency response
Front Ports*	Intel SoC (System on Chip) platform None					Microphone	8 element, linear beamforming array, 100Hz-24kHz pickup, optimal pickup range of up to 4m
	3x USB 3.2 Gen 1, 1x USB-C 3.2 Gen 1, 1x HDMI-in 2.0, 2x HDMI-out 2.0 with CEC, 5x RJ-45 Ethernet (one uplink port for internet connection, four downlink ports for IP-based peripherals), 1x power connector, 1x headphone / microphone combo jack (3.5mm)					Ports	1x RJ-45 Daisy Chain Port (PoE like, connect to Smart Audio Bar)
						Mounting	Wall mount kit
					porotical appead	Dimensions	(LxWxH) 95 x 705 x 133 mm
	* Depending on many factors, actual data transfer speed may be lower than theoretical speed Realtek ALC5682I-VD-CGT						Controller
							Touch Controller
Bluetooth Ethernet	11ax Wi-Fi + BT 5.2, M.2 Card, Intel Wi-Fi 6 AX201 (2.4GHz / 5GHz), 2x2 Bluetooth 5.2 wireless, integrated in Wi-Fi + Bluetooth combo adapter Gigabit ethernet, Realtek RTL8111H (1x RJ-45, uplink) + Intel Ethernet Controller I350-AM4 (4x RJ-45, downlink)					Display Multi-touch	10.1" (1280x800) , wide viewing angle (Horizontal/Vertical: +/- 89°), 350 nits, 16:10 aspect ratio, 800:1 contrast ratio, smudge resistant, Supports 2-point touch
Power supply	240 watts adapter, 100V - 240V					Sensors	Color sensor, orientation sensor
Mounting	Wall mount kit and table stand, magnetically attach to Compute System					Ports	1x RJ-45 Ethernet (PoE, connect to Compute System)
	(LxWxH) 135 x 284 x 29 mm					Mounting	Wall mount kit
Operating System Chrome OS					Dimensions	(LxWxH) 164 x 245 x 91 mm	
Camera						Remote Control	
	Smart Camera XL					Remote	2.4 RF remote
Image	20.30 MP 1" CMOS sensor, up to 1080p@30fps video capture, f/2.9 aperture, automatically support digital PTZ (Pan / Tilt / Zoom) via Google Al				aperture,	Keypad Battery and Dock	10 function keys on front (Navi keys, Microphone on/off, Menu, End, Volume up/down keys), QWERTY keyboard on rear (38 keys) Embedded rechargeable lithium ion battery with USB-powered charging dock
Optics	Wide angle glass optics, 95° horizontal field of view					Dimensions	(LxWxH) 130 x 45 x 14 mm
Microphone	Omnidirectional microphone						Mic Pod
Ports	1x RJ-45 Ethernet (PoE, connect to Compute System)					Microphone	8 element, circular beamforming array, 100Hz-24kHz pickup, optimal pickup range
Mounting	Wall mount kit, TV mount kit, and magnetic dock					- Ports	of up to 2m 2x RJ-45 Daisy Chain ports (PoE like, one input connects to Smart Audio Bar or
Dimensions	(LxWxH) 84 x 122 x 52 mm					I UIIS	previous Mic Pod, one output port connects to next Mic Pod) *Daisy Chain supports up to 4 mic pods
						Dimensions	(LxWxH) 95 x 95 x 30 mm
See footnotes for m	ore detailed informat	ion				1	Lenovo, December 2020

