Data sheet

HP USB Slim Business Keyboard (N3R87AA)





Stylish data entry

Get fast data entry and quick USB connectivity with the HP USB Business Slim Keyboard, designed to complement the 2015 class of HP Business PCs.

Multi-OS compatibility

Interact seamlessly with a full-sized keyboard layout that's optimized for use with multiple operating systems.¹

USB connectivity

Easily connect the keyboard to any USB port on your PC.

Rest easy

Get the reassurance of a one-year limited warranty.

¹ See product QuickSpecs for compatible operating systems.

HP USB Slim Business Keyboard

| Model number | QY776AA | |
|--------------------------|---|--|
| Physical characteristics | Keys | 104, 105, 106, 107, 109 layout (depending upon country) |
| | Dimensions (L x W x H) | 171.97 x 68.35 x 8.27 in (436.8± 1.5 x 137.6± 1.0 x 21.0± 1.0 cm) |
| | Weight | 1.32 lb (0.6± 0.08 kg) |
| Electrical | Operating voltage | + 4.4 – 5.25VDC |
| | Power consumption | 50-mA maximum (with 5 VDC power supplied and three LEDs ON) |
| | System interface | USB Type A plug connector |
| | ESD | Contact Discharge: 2, 4,6,8KV Air Discharge: 2, 4, 8,10,12.5KV |
| | EMI - RFI | Conforms to FCC rules for a Class B computing device |
| | Microsoft [®] PC 99 - 2001 | Functionally compliant |
| Mechanical | Кеусарѕ | Low-profile design |
| | Switch actuation | 60±12.5g nominal peak force with tactile feedback |
| | Switch life | 10 million keystrokes (Life tester) |
| | Switch type | Contamination-resistant switch membrane |
| | Key-leveling mechanisms | For all double-wide and greater-length keys |
| | Cable length | 6 ft (1.8 m) |
| | Microsoft PC 99 - 2001 | Mechanically compliant |
| Environmental | Acoustics | 43-dBA maximum sound pressure level |
| | Operating temperature | 50° to 122° F (10° to 50° C) |
| | Non-operating temperature | -22° to 140° F (-30° to 60° C) |
| | Operating humidity | 10% to 90% (non-condensing at ambient) |
| | Non-operating humidity | 20% to 80% (non-condensing at ambient) |
| | Operating shock | 40 g, six surfaces |
| | Non-operating shock | 80 g, six surfaces |
| | Operating vibration | 2-g peak acceleration |
| | Non-operating vibration | 4-g peak acceleration |
| | Drop (out of box) | 26 in (66 cm) on carpet, six-drop |
| | | sequence |
| | Drop (in box) | 30 in (76.2 cm) on concrete, 16-drop sequence |
| Approvals | UL, FCC, CE Mark, TUV, TUV GS, VCCI, BSMI, C-Tick, KC | |
| Ergonomic compliance | ANSI HFS 100, ISO 9241-4, and TUVGS | |
| Kit contents | Keyboard | Installation Guide |
| | Warranty Card | Safety and Comfort Guide |

Sign up for updates hp.com/go/getupdated



★ Rate this document

© Copyright 2015 Hewlett-Packard Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

